



For all
your adhesive
supply needs



Scan QR Code to visit our store



PRODUCT CATALOG

Non-Reflective Cloth/Gaffers Tapes...

CGT-80... Gaffers/Spike Tape (low gloss finish)

11.8 mil (0.30mm). 76 mesh. High quality polyethylene coated cloth laminated to a **low gloss** finish film, coated with a natural rubber based adhesive. Conforms well to irregular surfaces and will not twist or curl during application. Excellent water, vapor and abrasion resistance. Clean removal on most surfaces (surface type & dwell time may affect performance). Suitable for entertainment type applications (concerts, trade shows, etc.) where minimal visibility of tape is desired. Used for holding down cable, wires, electrical cords, and in stage set-ups for marking placement (i.e. "spike" tape). Suitable as a book binding tape for seaming & reinforcement. Peel Adhesion: 29 oz/in. Tensile Strength: 36 lb/in. Temperature Resistance: -31°F to 176°F. 3" neutral core/carton.

60yd COLORS AVAILABLE (11): Black, white, gray, red, yellow, dark blue, light blue, dark green, olive drab, brown & burgundy.

45yd COLORS AVAILABLE (7) in FULL CASE QUANTITIES ONLY:
Black, white, gray, red, light blue, brown & burgundy.

(Other colors available as special order; contact us for details/MOQ.)

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+

45 YD (41M) 135 FT

2"	(48mm)	24
3"	(72mm)	16
49"	(1250mm)	2

same color

60 YD (55M) 180 FT

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
2.5"	(60mm)	20
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
12"	(288mm)	4
12"	(304.8mm)	4
49"	(1250mm)	LOG
49"	(1250mm)	2
49"	(1250mm)	x 547 YD (500M) JUMBO

same color

Alternative to Shurtape #PC-625; Scapa #125.

60 yd (only) is available by the roll @ 1-5 case price +10%; minimum 6 inches per color.

CGT-80MG... Military Grade Tape (low gloss finish)

12.2 mil (0.31mm). 76 mesh. Military grade, polyethylene coated cloth with a low gloss finish, coated with a strong, natural rubber adhesive. Excellent abrasion and water resistance, as tape is composed of a water-resistant woven cloth and evenly coated with a pressure-sensitive water-insoluble adhesive. Conforms well to irregular surfaces. Clean removal on most surfaces. Tape has superior tensile strength, yet is hand-tearable. Used for packaging, box closure, and sealing, where water resistance is required. Peel Adhesion: 21 oz/in. Tensile Strength: 40 lb/in. Temperature Resistance: 104°F (176°F short term). Application Temperature: 41°F to 95°F. Meets MIL Specification ASTM D5486M, Type IV (supersedes PPP-T-60). 3" neutral core/carton.

1 COLOR AVAILABLE: Olive drab*.

(Other colors available as special order; contact us for details/MOQ.)

60 YD (55M) 180 FT

1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
49"	(1250mm)	LOG
49"	(1250mm)	2

Minimum 6 inches @ 1-5 case price +10%.

CGT-665C... Gaffers/Spike Tape (matte finish)

11.5 mil (0.29mm). Non-reflective, vinyl coated cotton cloth with a natural rubber/synthetic resin blend adhesive. Hand-tearable. High quality waterproof tape, matte surface finish. High tack and tensile strength. Highly conformable. Preferred for entertainment type applications (concerts, trade shows, etc.) where minimal visibility of tape is desired. Used for holding down cable, wires, electrical cords, and in stage set-ups for marking placement (i.e. "spike" tape). Used in the motion picture & television industries, and as a book-binding tape. Insures air tight, moisture free seals. Tensile Strength: 42 lb/in. Adhesion/Steel: 50 oz/in. Maximum Performance Temperature: 200°F. 3" neutral core/carton.

4 COLORS AVAILABLE: Black, white, gray & red.

JUMBOS AVAILABLE.

50 YD (46M) 150FT

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
2.5"	(60mm)	20
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
12"	(288mm)	4
12"	(304.8mm)	4
56"	(1422mm)	LOG (BLACK or WHITE)
59.5"	(1510mm)	LOG (GRAY or RED)

Alternative to Berry Global #510; Shurtape #P-628; Scapa #3130 & 225; 3M #6910.

Minimum 6 inches per color @ 1-5 case price +10%.

Cloth Duct Tapes...

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+
60 YD (55M) 180 FT				
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
2.5"	(60mm)	20		
3"	(72mm)	16		
4"	(96mm)	12		
6"	(144mm)	8		
49"	(1250mm)	LOG		
49"	(1250mm)	x 500M JUMBO		

CDT-8GP... General Purpose Duct Tape

8.7 mil. General purpose, polyethylene coated cloth coated with an aggressive natural rubber based adhesive. Hand-tearable and conforms well to irregular surfaces. Excellent moisture resistance. Used for bundling, AC duct seaming and joint sealing, heavy carton sealing, general maintenance repair operations (MRO), pipe wrapping, carpet fixing. Peel Adhesion: 43 oz/in. Tensile Strength: 17 lbs/in. Temperature Range: -31°F to 176°F. 3" neutral core/carton.

2 COLORS AVAILABLE: Silver (gray) & black.

Alternative to Cantech #88-21 & #93-21; Nashua #307; Berry Global #917; IPG #AC10; Scapa #460 & #590.

Minimum 6 inches per color @ 1-5 case price +10%.

CDT-36... Industrial Grade Duct Tape

10.2 mil. 38 mesh. High quality general purpose polyethylene coated cloth with a natural rubber based adhesive. Hand-tearable (tears evenly across web), conforms conform well to irregular surfaces, and will not twist or curl during application. Excellent water and abrasion resistance. Used as a quality waterproof packaging tape for export shipments; splicing, vinyl repair, protecting, bundling, and color coding; ductwork sealing and seaming. Peel Adhesion: 36 oz/in. Tensile Strength: 18 lbs/in. Temperature Range: -31°F to 176°F. 3" neutral core/carton.

18 COLORS AVAILABLE*: Silver (gray), black, white, yellow, schoolbus yellow (ochre), teal blue, sky blue, dark blue, pink, red, burgundy, purple, racing orange, tan (beige), brown, light green, dark green & olive drab.

*For clear/translucent duct tape, see CDT-30T (page 4).

60 YD (55M) 180 FT

1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
2.5"	(60mm)	20		
3"	(72mm)	16		
4"	(96mm)	12		
5"	(120mm)	8		
6"	(144mm)	8		
12"	(288mm)	4		
12"	(304.8mm)	4		
49"	(1250mm)	LOG		
49"	(1250mm)	2	same color	
49"	(1250mm)	x 500M JUMBO		

Alternative to Tesa #64662; IPG #AC30 & #AC36; 3M #6969; Scapa #248; Shurtape #PC-610 & #PC-620; Berry Global #223; Nashua #398.

Minimum 6 inches per color @ 1-5 case price +10%.

CDT-70... Contractor Grade Duct Tape

11.8 mil. 63 mesh. High tensile polyethylene coated cloth with a natural rubber based adhesive. It is a superior performance duct tape specifically designed for the high demand of contractor applications. Product has excellent shear values to surface and backing. It has good conformability and excellent resistance to tear. Used in HVAC industry to provide an excellent seal for thermal insulation and air conditioning ducts; as a moisture barrier for both indoor and outdoor applications; asbestos abatement applications; quality waterproof packaging tape for export shipments; for splicing, vinyl repair, protecting, and bundling. Peel Adhesion: 36 oz/in. Tensile Strength: 30 lbs/in. Temperature Range: -31°F to 176°F. 3" neutral core/carton.

4 COLORS AVAILABLE: Silver (gray), black, white & olive drab.

60 YD (55M) 180 FT

1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
2.5"	(60mm)	20		
3"	(72mm)	16		
4"	(96mm)	12		
6"	(144mm)	8		
12"	(288mm)	4		
49"	(1250mm)	LOG		
49"	(1250mm)	2	same color	
49"	(1250mm)	x 500M JUMBO		

Alternative to Berry Global #227; IPG #AC43; Shurtape #PC621 & #PC-721; Ideal #469; Scapa #146; Tesa #64663; Achem #DT39.

Minimum 6 inches per color @ 1-5 case price +10%.

Specialty Cloth Tapes...

CDT-30T... Translucent Duct Tape


6.3 mil. 30 mesh. Clear polyethylene film reinforced with white polyester cloth and coated on one side with a hot melt/synthetic rubber adhesive. Translucent duct tape for less visible/obvious repairs. Waterproof & hand-tearable. Bonds & conforms to most, including irregular, surfaces. Peel Adhesion: 40 oz/in. Tensile Strength: 16 lb/in. Elongation: 18%. Temperature Resistance: up to 176°F. 3" neutral core/carton.

COLOR: Translucent (Clear film with White cloth fibers).

CDT-80CAM... Camouflage Tape

11.8 mil. 76 mesh. Polyethylene coated cloth laminated to a **low gloss** finish film, coated with a natural rubber based adhesive. Hand-tearable. Peel Adhesion: 30 oz/in. Tensile Strength: 36 lb/in. Elongation: 11.5%. Temperature Resistance: up to 176°F. 3" neutral core/carton.


COLOR: Multi-colored Camouflage Pattern.



CDT-HS... Hazard/Striped Duct Tape

11.8 mil. 63 mesh. High quality polyethylene coated cloth duct tape, with natural rubber with synthetic adhesive. This striped safety warning tape is used for permanent and temporary marking of hazardous areas, aisles, stairs, wires, cords, etc. Ideal for use in manufacturing, as well as in convention/exhibition halls, residential/commercial sites. Hand-tearable and easy to use. Peels off easily upon removal, leaving no residue on most surfaces. Peel Adhesion: 36 oz/in. Tensile: 30 lbs/in. Temperature Range: -31°F to 176°F. 3" neutral core/carton.

COLOR: Black/yellow diagonal stripes.



CZT-70B/Y... Hazard/Striped CablZone Tape

11.8 mil. Polyethylene coated cloth with a natural rubber with synthetic resin adhesive only along the outer edges of the tape. The center length on the adhesive side has a plastic coating that creates an adhesive-free tunnel ("dead zone") to protect cables, cords and wires from adhesive residue. Specifically designed for laying down cables safely to avoid accidental tripping and unplugging in warehouses, convention centers, theaters, etc. Hazard stripes create additional awareness and provide extra cautionary protection in heavily traversed areas. Removes cleanly from most surfaces. Hand-tearable. Peel Adhesion: 36 oz/in. Tensile Strength: 29 lb/in (adhesive area), 36 lb/in (dead zone). Elongation: 18%. Temperature Resistance: up to 176°F. 3" neutral core/carton.

COLOR: Black/yellow diagonal stripes.

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+

30 YD (27M) 90 FT

1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
49"	(1250mm)	LOG
49"	(1250mm)	2
49"	(1250mm)	x 1000M JUMBO

Minimum 6 inches @ 1-5 case price +10%.

25 YD (23M) 75 FT

1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
49"	(1250mm)	LOG
49"	(1250mm)	2
49"	(1250mm)	x 500M JUMBO

Alternative to Shurtape #PC-625.

Minimum 6 inches @ 1-5 case price +10%.

60 YD (55M) 180 FT

1"	(24mm)	48
1.5"	(36mm)	32
2"	* (48mm)	24
3"	* (72mm)	16
4"	(96mm)	12
5"	(125mm)	8
6"	(144mm)	8
49"	(1250mm)	LOG
49"	(1250mm)	2
49"	(1250mm)	x 500M JUMBO

* Lower proportional price, as stocked pre-slit.

Minimum 6 inches @ 1-5 case price +10%.



WIDTH	RLS/CS	CASES		
		1-2	3-5	6+

39.4YD (36M) 118 FT

3"	(75mm)	16
4"	(100mm)	12
6"	(150mm)	8

Available by the roll @ 1-2 case price +10%.



CablZone

"Dead Zone" Widths

3"(75mm) = 40mm dead zone

4"(100mm) = 57mm dead zone

6"(150mm) = 80mm dead zone

Fluorescent Cloth Tapes...

CDT-70F... Fluorescent Duct Tape

11.8 mil. High tensile, high quality fluorescent PE coated cloth with a natural rubber/synthetic resin adhesive. Superior performance duct tape specifically designed for the high demand contractor applications. Easy tear and unwinding. Its water resistant adhesive system allows this product to bond to almost any surface, including porous surfaces. Used for night amusement industry such as night club, karaoke and music hall or show window that is used under black light. Adhesion/Steel: 35 oz/in. Tensile Strength: 33 lb/in. Temp. Resistance: -31°F to 106°F. 3" neutral core/carton.

4 COLORS AVAILABLE: Fluorescent pink, yellow, green & orange.

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+

60 YD (55M) 180 FT

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
2"	(48mm)	24
3"	(72mm)	16
49"	(1250mm)	LOG
49"	(1250mm)	x 500M JUMBO

Alternative to Shurtape #PC619.

Minimum 6 inches per color @ 1-5 case price +10%.

60 YD (55M) 180 FT

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
2.5"	(60mm)	20
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
12"	(288mm)	4
49"	(1250mm)	LOG
49"	(1250mm)	2
49"	(1250mm)	x 500M JUMBO

Minimum 6 inches per color @ 1-5 case price +10%.

25 YD (23M) 75FT

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
59.5"	(1510mm)	LOG

50 YD (46M) 150FT

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
59.5"	(1510mm)	LOG

Alternative to Berry Global #510; Permacel #660; Scapa #125FL; Shurtape #P-660.

Minimum 6 inches per color @ 1-5 case price +10%.


FCT-665... Fluorescent Gaffers/Spike Tape (matte finish)

11.5 mil. Heavy-duty fluorescent vinyl coated tape with a strong natural rubber adhesive. This product has a matte-finish for less reflectivity and low sheen. Used for wrapping or bundling wires, tools, and handles. Suitable for bookbinding and entertainment type applications (trade shows, photography, film industry) where minimal visibility of tape is desired. Allows for a clean removal, leaving no residue. Adhesion/Steel: 50 oz/in. Tensile Strength: 42 lb/in. Temp. Resistance: 40°F to 200°F. 3" neutral core/carton.

4 COLORS AVAILABLE: Fluorescent pink, yellow, green & orange.

600YD JUMBOS AVAILABLE.

WIDTH x LENGTH	RLS/CS	COST PER ROLL
3/4" (18mm) x 60'	100	
1.5" (36mm) x 60'	50	
2" (48mm) x 60'	40	



Vinyl Electrical Insulating Tapes...

EL760-B... COLORS

Same specs as EL7xx-B.

WIDTH x LENGTH	RLS/CS	CASES		
		1-18	19-48	49+
3/4" (18mm) x 60'	200			

(6) **COLORS AVAILABLE:** White, green, orange, red, blue & yellow.

EL7xx-B... BLACK ("xx" = Length)

7 mil (0.18mm) Electrical Insulation Tape. Plasticized PVC with rubber based adhesive. For wire and cable insulation, bundling, primary splice insulation at no more than 600V. Non-flame retardant. Adhesion: 14 oz/in. Dielectric Breakdown: 6KV. Tensile Strength: 16 lb/in. Elongation: 200%. Temp. Resistance: 176° F (80° C). **Highlighted sizes are cello-wrapped (no label) in sleeves (when pre-slit).** Other sizes/slit items are **bulk-packed** and separated by silicone sheets. 1 1/2" (38.1mm) UL listed core.



1/2" (12mm)	x	66'	192
1/2" (12mm)	x	108'	192
3/4" * (19mm)	x	30'	200
3/4" (19mm)	x	60'	100
3/4" (19mm)	x	66'	100
3/4" (19mm)	x	108'	100
1" (24mm)	x	66'	160
1" (24mm)	x	108'	96
1.5" (36mm)	x	66'	120
1.5" (36mm)	x	108'	64
2" (48mm)	x	66'	80
2" (48mm)	x	108'	48
3" (72mm)	x	108'	32
4" (96mm)	x	108'	24
49" (1250mm)	x	66'	2
49" (1250mm)	x	108'	2

*1" UL listed core.

Alternative to Permacel #220; IPG #6180; Tesa #4208; Berry Global #777.

EL760AW-L... BLACK, All Weather, Labeled

Same specs as EL766AW-L.

3/4" (19mm)	x	60'	100
Also sold in subpacks of 10 rolls: @			/roll

3/4" (19mm)	x	66'	100
Also sold in subpacks of 10 rolls: @			/roll

(11) **COLORS AVAILABLE:** Black, white, green, orange, red, blue, yellow, purple, gray, brown & pink.

EL766AWR-L... RAINBOW, All Weather, Labeled

Same specs as EL766AW-L. Each subpack contains 10 different colors.

3/4" (19mm)	x	66'	100
Also sold in subpacks of 10 rolls: @			/roll

EL766AW-B... COLORS, All Weather, Bulk

Flame Retardant & Cold Resistant. 7 mil (0.18mm). Plasticized PVC film with a rubber based adhesive in 8 different OSHA colors. **Bulk packed.** 1 1/2" (38.1mm) UL/CSA/CE listed core.

3/8" (9mm)	x	66'	264
1/2" (12mm)	x	66'	192
1" (24mm)	x	66'	96
1.5" (36mm)	x	66'	64
2" (48mm)	x	66'	48
3" (72mm)	x	66'	32
49" (1250mm)	x	66'	2

same color

(8) **COLORS AVAILABLE:** Black, white, green, orange, red, blue, yellow & gray.

3/4" (19mm)	x	66'	200
Also sold in subpacks of 10 rolls: @			/roll

Alternative to Permacel #P-29+, 3M #33.

EL7566AW-L... BLACK, All Weather, Labeled

Flame Retardant & Cold Resistant. 8 mil (0.20mm) **Black** PVC premium grade electrical insulation tape with a rubber based adhesive. Dielectric Breakdown: 6KV. Adhesion: 14 oz/in. Tensile: 17 lbs/in. Elongation: 250%. Temp. Resistance: 176°F (80°C). **Individually cello wrapped and labeled.** 1 1/2" (38.1mm) UL/CSA listed core.

3/8" (9mm)	x	66'	264
1/2" (12mm)	x	66'	192
1" (24mm)	x	66'	96
1.5" (36mm)	x	66'	64
2" (48mm)	x	66'	48
3" (72mm)	x	66'	32
4" (96mm)	x	66'	24
49" (1250mm)	x	66'	2

EL7566AW-B... BLACK, All Weather, Bulk

Flame Retardant & Cold Resistant. 8 mil (0.20mm) **Black** PVC premium grade electrical insulation tape with a rubber based adhesive. Dielectric Breakdown: 6KV. **Bulk packed.** 1 1/2" (38.1mm) UL/CSA listed core.

UL/CSA/CE Listed

Heavy-Duty SPVC Vinyl Tapes...

Heavy-duty SPVC Pipe Wrap/Surface Protection Tapes are highly resistant to sun, water, oil, acids, alkalies and corrosive chemicals. Bacteria and fungus resistant. Abrasion resistant. Provides electrical protection. Protects pipe joints, conduit couplings for overhead or direct buried applications. Application Temperature: 32°F. Water absorption rate (maximum): 0.290 (25°C, 24 hours).

PWT-10... BLACK SPVC Pipe Wrap

10 mil (0.25mm). SPVC pipe wrap/surface protection film. Matte surface, rubber adhesive. **Flame Retardant**. Adhesion: 14 oz/in. Tensile: 20 lb/in. Elongation: 250%. Dielectric Strength: 1 KV/mil. Temperature Resistance: 176°F (80°C). 3" neutral paper core.

(Formerly PWT-10C)

WIDTH	RLS/CS	CASES	
		1-11	12-29

33.3 YD (100 FT) BLACK

3/4"	(19mm)	64
1"	(25mm)	48
1.5"	(38mm)	32
2"	(50mm)	24
3"	(75mm)	16
4"	(100mm)	12
5"	(125mm)	8
6"	(150mm)	8
49"	(1250mm)	2

Alternative to 3M #50; Achem #PW10; Shurtape #PW100 Permacel #306.

PWT-10H... WHITE SPVC Pipe Wrap

Same specs as PWT-10C. 1.5" (38.1mm) core for HVAC industry.

33.3 YD (100 FT) WHITE

3/4"	(19mm)	64
1"	(25mm)	48
1.5"	(38mm)	24 or 32
2"	(50mm)	24
49"	(1250mm)	2

PWT-10G... GREEN SPVC Pipe Wrap

Same specs as PWT-10C. 1.5" (38.1mm) core for HVAC industry.

33.3 YD (100 FT) GREEN

2"	(50mm)	24
----	--------	----

PWT-20... BLACK SPVC Pipe Wrap

20 mil (0.50mm). SPVC pipe wrap/surface protection film. Matte surface, rubber adhesive. **Flame Retardant**. Adhesion: 11 oz/in. Tensile: 32 lb/in. Elongation: 360%. Temperature Resistance: 176°F (80°C). 3" neutral paper core.

(Formerly PWT-20C)

33.3 YD (100 FT) BLACK

3/4"	(19mm)	64
1"	(25mm)	48
1.5"	(38mm)	32
2"	(50mm)	24
3"	(75mm)	16
4"	(100mm)	12
5"	(125mm)	8
6"	(150mm)	8
49"	(1250mm)	LOG

Alternative to Permacel #P-320; Achem #PW20.

Hazard Identification Barricade Tapes...

BR... Barricade Tapes

Non-adhesive, polyethylene film for hazard identification. Stocked* barricade tape legends/colors are listed below.

WIDTH x LENGTH	RLS/CS	ROLL	CASES	
			1-5	6+
3" x 300'	16			
3" x 1000'	8			

WIDTH	LENGTH	STOCKED LEGENDS	COLORS
BRC-CC	3" x 300'	CAUTION • CAUTION • CAUTION	Black Legend on Yellow Film
BRC-CUIS	3" x 300'	CUIDADO • CUIDADO • CUIDADO	Black Legend on Yellow Film
BRC-CC	3" x 1000'	CAUTION • CAUTION • CAUTION	Black Legend on Yellow Film
BRC-CUIS	3" x 1000'	CUIDADO • CUIDADO • CUIDADO	Black Legend on Yellow Film
BRC-SCUI	3" x 1000'	CUIDADO • CAUTION	Black Legend on Yellow Film
BRC-CCA	3" x 1000'	CAUTION CONSTRUCTION AREA	Black Legend on Yellow Film
BRC-CDNE	3" x 1000'	CAUTION DO NOT ENTER	Black Legend on Yellow Film
BRC-COT	3" x 1000'	CAUTION OPEN TRENCH	Black Legend on Yellow Film
BRC-FLDNC	3" x 1000'	FIRE LINE DO NOT CROSS	Black Legend on Yellow Film
BRC-PLDNC	3" x 1000'	POLICE LINE DO NOT CROSS	Black Legend on Yellow Film
BRC-SLDNC	3" x 1000'	SHERIFF'S LINE DO NOT CROSS	Black Legend on Yellow Film
BRC-DD	3" x 1000'	DANGER • DANGER • DANGER	Black Legend on Red Film
BRC-DDNE	3" x 1000'	DANGER DO NOT ENTER	Black Legend on Red Film
BRC-RNP	3" x 1000'	RED - NO IMPRINT	Red
BRC-YNP	3" x 1000'	YELLOW - NO IMPRINT	Yellow
BRC-R/W	3" x 1000'	RED/WHITE STRIPES	Red/White
BRC-B/Y	3" x 1000'	BLACK/YELLOW STRIPES	Black/Yellow

*NOTE: Custom imprints, underground (detectable or non-detectable) and additional legends/colors available. Email/call for pricing and availability for custom/non-stocked barricade tapes.

Solid SPVC Vinyl Colored Tapes...

CVT-536... 36 yd.

CVT-560... 60 yd.

Colored Vinyl Tapes (matte surface-soft PVC). 3" neutral core/carton.

13 OSHA COLORS: Yellow, white, black, clear, red, orange, light blue, dark blue, gray, purple, emerald green, kelly green & dark brown.

Applications...

Used for color coding; lane marking and safety coding to meet OSHA requirements; decorating, striping on vehicles, boats, sporting equipment, etc. Masking for hard chrome plating & anodizing; harness and pipe wrapping. Duct and joint sealing.

Features/Benefits...

Product is of superior quality, with a long shelf-life, and "write-on" capability. It provides a very effective vapor and moisture barrier. It is highly conformable and resistant to aging, sun, water, fungus, bacteria, oil, acids, alkalies and corrosive chemicals. It provides good abrasion, impact and rupture resistance. 3" neutral core.

Physical Properties...

Backing
Adhesive
Total Thickness
Adhesion to Steel
Tensile Strength
Elongation
Temperature Resistance

Matte surface, soft PVC
Synthetic & Natural Rubber Resin Blend
5.2 mil (0.13mm)
18 oz/in.
14 lbs/in.
150% at break
Up to 140°F

WIDTH	RLS/CS	CASES		
		1-11	12-29	30+

CVT-536	36 YD (33M) 108 FT	3" CORE
----------------	--------------------	---------



1/4"	(6mm)	192
3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
5"	(120mm)	8
6"	(144mm)	8
49"	(1250mm)	LOG
49"	(1250mm)	2
49"	(1250mm)	54

CVT-560	60 YD (55M) 180 FT	3" CORE
----------------	--------------------	---------

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
49"	(1250mm)	LOG
49"	(1250mm)	2
49"	(1250mm)	40

SPVC Vinyl Die Cuts On A Roll...

DOTS & ARROWS



CVT-D... Dots

CVT-A... Arrows

Pressure sensitive dots & arrows. Used for aisle marking, color coding, inventory identification, defect markings, and numerous other applications. Made of durable vinyl construction, product is waterproof and will withstand heavy traffic.

11 COLORS AVAILABLE: Yellow, white, black, red, orange, light blue, dark blue, gray, purple, dark green & dark brown.

Specify DOTS or ARROWS when ordering.

SIZE	UNITS/ROLL	ROLLS	
		1-2	3+
1/2" (Dots ONLY)	1,000		
3/4" (Dots ONLY)	1,000		
1"	1,000		
2"	500		
3"	500		

Additional sizes, custom colors and die-cuts also available. Contact us for details.

Solid SPVC Vinyl Colored Tapes...

CVT-636... 36 yd.

CVT-660... 60 yd.

Colored Vinyl Tapes (matte surface-soft PVC). 3" neutral core/carton.

16 OSHA COLORS: Black, white, clear, yellow, red, orange, light green*, kelly green, emerald green, sky blue, medium blue*, dark blue, medium brown*, dark brown, gray & purple.

*Light green, emerald green, medium blue & medium brown are STOCKED in 36 yd only (available as special order).

Applications...

Used for color coding; lane marking and safety coding to meet OSHA requirements; decorating, striping on vehicles, boats, sporting equipment, etc. Masking for hard chrome plating & anodizing; harness and pipe wrapping. Duct and joint sealing.

Features/Benefits...

Product is of superior quality, with a long shelf-life, and "write-on" capability. It provides a very effective vapor and moisture barrier. It is highly conformable and resistant to aging, sun, water, fungus, bacteria, oil, acids, alkalies and corrosive chemicals. It provides good abrasion, impact and rupture resistance.

Physical Properties...

Backing	Matte surface, soft PVC
Adhesive	Synthetic & Natural Rubber Resin Blend
Total Thickness	6 mil (0.15mm)
Adhesion to Steel	18 oz/in.
Tensile Strength	14 lbs/in.
Elongation	150% at break
Temperature Range	-20°F to +140°F
Moisture Absorption	Less than 1.5%
Moisture Vapor Transmission	Less than 2.5% (gm/100 sq in/24 hrs)
Metal Corrosion	None to copper, brass, steel, aluminum
Accelerated Aging Factor	Greater than 100%
Government Specifications	(% of original adhesion to backing after aging)
	Conforms to A-A-1689B, Type II (meets cancelled spec PPP-T-66E, Type 1, Class 2)

CVT-636P... 36 yd. 3" plastic cores.

CVT-660P... 60 yd. 3" plastic cores. **WHITE ONLY**

Colored Vinyl Tapes (matte surface-soft PVC). 3" plastic core/neutral carton.

9 OSHA COLORS: Black, white, clear, yellow, red, orange, kelly green, sky blue & dark blue.

Other colors available as special order. Contact us for details.

WIDTH	RLS/CS	CASES		
		1-11	12-29	30+

CVT-636 36 YD (33M) 108 FT 3" CORE

1/4"	(6mm)	192	
3/8"	(9mm)	128	
1/2"	(12mm)	96	
3/4"	(19mm)	64	
1"	(25mm)	48	
1.25"	(31.7mm)	38	
1.5"	(38mm)	32	
2"	(50mm)	24	
2.5"	(63mm)	20	
3"	(75mm)	16	
4"	(100mm)	12	
5"	(125mm)	8	
6"	(150mm)	8	
49"	(1250mm)	LOG	neutral core
49"	(1250mm)	2	same color
49"	(1250mm)	48	crate - 1 color

Alternative to 3M #471 & #764; Permacel #P-33 & P-34; Cantech #571; Shurtape VP410; Achem #ST40; Decker #44; Patco #10; Achem #410 & #419.

CVT-660 60 YD (55M) 180 FT 3" CORE

3/8"	(9mm)	128	
1/2"	(12mm)	96	
3/4"	(19mm)	64	
1"	(25mm)	48	
1.5"	(38mm)	32	
2"	(50mm)	24	
3"	(75mm)	16	
4"	(100mm)	12	
5"	(125mm)	8	
6"	(150mm)	8	
49"	(1250mm)	LOG	neutral core
49"	(1250mm)	2	same color
49"	(1250mm)	35	crate - 1 color

*60 yd stocked in all colors EXCEPT light green, emerald green medium blue & medium brown (available as special order).

CVT-636P 36 YD (33M) 108 FT 3" CORE

1/4"	(6.3mm)	192	
1/2"	(12mm)	96	
3/4"	(19mm)	64	
1"	(25mm)	48	
1.5"	(38mm)	32	
2"	(50mm)	24	
3"	(75mm)	16	
4"	(100mm)	12	
49"	(1250mm)	LOG	plastic core
49"	(1250mm)	40	crate-1 color

Alternative to PATCO #150-PL; Achem #419P.

CVT-660P 60 YD (55M) 180 FT 3" CORE
WHITE ONLY

49"	(1250mm)	LOG	plastic core
-----	----------	-----	--------------

Slit rolls proportional cost to 36 yd.

Striped Safety Warning Tapes...

SST-618... 18 yd.

SST-636... 36 yd.

6 mil (0.15mm). Conformable Soft PVC Vinyl. Synthetic Rubber Adhesive, self-extinguishing. Will not corrode copper, brass, steel, or aluminum. For striping & warning, marking of hazardous areas and exits to comply with OSHA requirements per paragraph 1910.144 of the Federal Register. Adhesion: 13.7 oz/in. Tensile Strength: 15 lbs/in. Elongation: 210%. Temperature Resistance: 14°F to 176°F. 3" neutral paper core.

Colors Available

Black/Yellow
Red/White
Black/White
Green/White

Typical Uses...

Physical Hazard/Caution
Fire Equipment/First Aid
Traffic/Housekeeping
Decorative Identification



SST-718... 18 yd.

SST-736... 36 yd.

7 mil (0.175mm). Conformable Soft PVC Vinyl. Synthetic Rubber Adhesive, self-extinguishing. Will not corrode copper, brass, steel, or aluminum. For striping & warning, marking of hazardous areas and exits to comply with OSHA requirements per paragraph 1910.144 of the Federal Register. Adhesion: 22 oz/in. Tensile Strength: 18 lbs/in. Elongation: 200%. Temperature Resistance: up to 140°F. 3" neutral paper core.

Colors Available

Black/Yellow
Red/White
Black/White
Green/White

Typical Uses...

Physical Hazard/Caution
Fire Equipment/First Aid
Traffic/Housekeeping
Decorative Identification



WIDTH	RLS/CS	CASES		
		1-11	12-29	30+
SST-618 18 YD (16.5M) 54 FT				
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
2"	* (48mm)	24		
3"	(72mm)	16		
4"	(96mm)	12		
49"	(1250mm)	LOG	neutral core	
49"	(1250mm)	2	same color	

SST-636 36 YD (33M) 108 FT		
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
2"	* (48mm)	24
3"	* (72mm)	16
4"	(96mm)	12
49"	(1250mm)	LOG
49"	(1250mm)	2
		neutral core
		same color

* Lower proportional price, as stocked pre-slit.

SST-718 18 YD (16.5M) 54 FT

1/2"	(12mm)	96
3/4"	(19mm)	64
1"	(25mm)	48
2"	(50mm)	24
3"	(75mm)	16
4"	(100mm)	12
6"	(150mm)	8
49"	(1250mm)	LOG
49"	(1250mm)	2
		neutral core
		same color

Alternative to 3M #5700 and #5702; Achem #41N; Shurtape #VP415.

SST-736 36 YD (33M) 108 FT

1/2"	(12mm)	96
3/4"	(19mm)	64
1"	(25mm)	48
2"	* (50mm)	24
3"	* (75mm)	16
4"	(100mm)	12
6"	(150mm)	8
49"	(1250mm)	LOG
49"	(1250mm)	2
		neutral core
		same color

* Lower proportional price, as stocked pre-slit.

Vinyl Electroplating Tape...

EPT-38...SPVC Masking tape for Electroplating

6.8 mil (0.17mm) Yellow Soft PVC Film. Rubber resin adhesive. Extremely conformable, durable and highly resistant to oil, acid, alkalines, corrosive chemicals. Excellent adhesion to metals, plastics. Designed for use with PCB terminal zone contacts to prevent penetration of chemicals during plating process; as a protection tape for shot peening applications. Adhesion: 17 oz/in. Tensile Strength: 16 lbs/in. Elongation: 100% at break. Operating Temperature: 140°F (60°C) to 194°F (90°C). 3" paper core/carton.

WIDTH	RLS/CS	CASES		
		1-4	5-9	10+
36 YD (33M) 108 FT				
1/2"	(12.5mm)	96		
3/4"	(19mm)	64		
1"	(25mm)	48		
1.5"	(38mm)	32		
2"	(50mm)	24		
3"	(75mm)	16		
4"	(100mm)	12		
6"	(150mm)	8		
51"	(1300mm)	LOG	neutral core	

Alternative to Permacel #P-35; 3M #470; Plymouth Rubber #7.

Striped Safety Warning Tapes...

SST-718L... 18 yd.

SST-736L... 36 yd.

6.3 mil (0.16mm). Laminated SPVC with rubber based adhesive. Shiny surface. Resists oil, grease, solvents, moisture. Scuff resistant. For marking fire equipment/exports, hazardous areas, and first aid points. Adhesion/Steel: 17.6 oz/in. Tensile Strength: 18 lbs/in. Elongation: 180%. 3" neutral paper core.

Colors Available

Black/Yellow

Red/White [□]

Black/White

Magenta/Yellow

Typical uses...

Physical Hazard/Caution

Fire Equipment/First Aid

Traffic/Housekeeping

Radiation Hazard



[□] Only available in 18 yd.

SST-918L... 18 yd.

SST-936L... 36 yd.

9.1 mil (0.23mm). Laminated SPVC with rubber based adhesive. Shiny surface. Resists oil, grease, solvents, moisture. Scuff resistant. For marking fire equipment/exports, hazardous areas, and first aid points. Meets government specification A-A-1689B Type II. Adhesion/Steel: 22 oz/in. Tensile Strength: 33 lbs/in. Elongation: 200%. 3" neutral paper core.

Colors Available

Black/Yellow

Red/White

Black/White

Typical uses...

Physical Hazard/Caution

Fire Equipment/First Aid

Traffic/Housekeeping



SST-918LPC... 18 yd.

Same specs as SST-918L. 3" **plastic core**.

STOCKED COLORS *: Black/Yellow and Red/White.

* Black/White available as special order.

WIDTH	RLS/CS	CASES		
		1-11	12-29	30+

SST-718L 18 YD (16.5M) 54 FT

1"	(24mm)	48		
2"	(48mm)	24		
3"	(72mm)	16		
4"	(96mm)	12		
49"	(1250mm)	LOG	neutral core	
49"	(1250mm)	2	same color	

SST-736L 36 YD (33M) 108 FT

1"	(24mm)	48		
2"	(48mm)	24		
3"	(72mm)	16		
4"	(96mm)	12		
49"	(1250mm)	LOG	neutral core	
49"	(1250mm)	2	same color	

Alternative to Achem #V16.

SST-918L 18 YD (16.5M) 54 FT

1"	(25mm)	48		
2"	(50mm)	24		
3"	(75mm)	16		
4"	(100mm)	12		
6"	(150mm)	8		
49"	(1250mm)	LOG	neutral core	
49"	(1250mm)	2	same color	

SST-936L 36 YD (33M) 108 FT

1"	(25mm)	48		
2"	(50mm)	24		
3"	(75mm)	16		
4"	(100mm)	12		
6"	(150mm)	8		
49"	(1250mm)	LOG	neutral core	
49"	(1250mm)	2	same color	

Alternative to Achem #V12; ST-V10.

SST-918LPC 18 YD (16.5M) 54 FT

1"	(25mm)	48		
2"	(50mm)	24		
3"	(75mm)	16		
49"	(1250mm)	LOG	neutral core	
49"	(1250mm)	2	same color	

Dry Vinyl Tape...

DVT-76Y... Yellow

3.94 mil (0.10mm) total thickness. Non-adhesive plasticized polyvinyl chloride film tape. Easy unwinding characteristics - tape clings firmly to its own backing for tight wrap. High elongation and good strength to permit trouble-free binding of wiring harnesses for the automotive industry. Dry vinyl tape also used for plating applications - high stretch, good "cling" characteristics and great conformability provide for superior masking in hard chrome and other plating applications. UL510 Flame Resistant. Cold flexibility - no cracking. Tensile Strength: 8.6 lbs/in. Elongation: 200%. Meets certificate standard: CE. 1 1/2" (38.1mm) paper core.

WIDTH	RLS/CS	CASES		
		1-11	12-29	30+

76M (250 FT)

1/2"	(12mm)	128		
3/4"	(18mm)	80		
1"	(25mm)	64		
1.5"	(36mm)	40		
2"	(48mm)	32		
3"	(72mm)	20		
4"	(96mm)	16		
48"	(1220mm)	LOG		

Minimum 6 inches @ 1-11 case price +10%.

Polyethylene Film Tapes...

LDPE-5A... with Acrylic Adhesive

5.5 mil (0.14mm) Low Density Polyethylene Film Tapes. Good abrasions, chemical, tear and UV resistance. Excellent moisture barrier. Used for color coding, decorative markings, stripping, sealing, splicing & seaming. 3" plastic core.

Applications...

Provides high adhesion and cohesion which yields a permanent bond with virtually no edge bleed out. Excellent long term aging stability without yellowing. Will not crack or crease at low temperatures.

Physical Properties...

Adhesive	Acrylic
Tensile Strength	11 lbs/in
Elongation	400%
Adhesion to Steel	50 oz/in
Application Temperature	50°F to 120°F
Operating Temperature	-40°F to 190°F

36Yd COLORS (8): Clear*, black, white, red, green, blue, yellow & orange.

*NOTE: CLEAR is now priced separately than colors.

60Yd COLOR (1): Clear.

Other colors available as special order.

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+

36 YD (33M) 108 FT - CLEAR* ONLY

1/4"	(6mm)	192
3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
54"	(1371mm)	LOG

36 YD (33M) 108 FT - (7) COLORS (NON-CLEAR)

1/4"	(6mm)	192
3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
54"	(1371mm)	LOG

60 YD (55M) 180 FT - CLEAR ONLY

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
54"	(1371mm)	LOG

Alternative to 3M #480; Patco #502A, #503A.

LDPE-5R... with Rubber Adhesive

5.5 mil (0.14mm) Low Density Polyethylene Film Tapes. Good abrasions, chemical, tear and UV resistance. Excellent moisture barrier. Used for color coding, decorative markings, stripping, sealing, splicing & seaming. 3" plastic core.

Applications...

Ideal for polyethylene splicing; general purpose sealing, spiral wrapping. Suitable for use in nuclear and other sensitive environments. Highly conformable and adheres to most surfaces. Works well in most applications where low to moderate adhesion is required.

Physical Properties...

Adhesive	Rubber
Tensile Strength	11 lbs/in
Elongation	400%
Adhesion to Steel	25 oz/in
Application Temperature	50°F to 120°F
Operating Temperature	-40°F to 190°F

4 COLORS AVAILABLE: Clear*, black, white & red.

*CLEAR is now priced separately than colors.

Other colors available as special order.

36 YD (33M) 108 FT - CLEAR* ONLY

1/4"	(6mm)	192
3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
54"	(1371mm)	LOG

36 YD (33M) 108 FT - BLACK, WHITE OR RED

1/4"	(6mm)	192
3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
54"	(1371mm)	LOG

Alternative to 3M #483; Patco #502R & #503R.

Polyethylene Film Tapes...

LDPE-7R...

7.0 mil (0.178mm) total thickness. 4.5 mil low density polyethylene film coated on one side with a synthetic rubber adhesive. Tough polyethylene backing offers good abrasion and tear resistance. Low tack adhesive suitable for surface protection applications. Excellent for low temperature bonding. 3" paper core.

Applications...

Ideal for wire identification, surface protection, seaming and splicing of films.

Physical Properties...

Adhesive

Tensile Strength

Elongation

Peel Adhesion

Adhesion to Backing

Synthetic Rubber

18 lbs/in

80%

60 oz/in

35 oz/in

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+

60 YD (55M) 180 FT

1/4"	(6mm)	192
3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
50"	(1270mm)	LOG

Alternative to Scapa #135; Berry Global #833 & #757.

4 COLORS AVAILABLE: Clear, black, white & red.

Other colors available as special order; MOQ = 6 logs.

60 YD (55M) 180 FT

1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
50"	(1270mm)	LOG

Alternative to Scapa #234, Berry Global Red Baron #824 & #836; Permacel #224LB; Cantech #250.

2 COLORS AVAILABLE: White & red.

*Note: Clean removability is dependent upon dwell time, the conditions/temperature of exposure, surfaces, etc. Should be thoroughly tested in the specific application.

LDPE-7R/UV...

7.0 mil (0.178mm) total thickness. 4.5 mil low density polyethylene film coated on one side with a synthetic rubber adhesive. Backing has been stabilized with additives to resist the effects of UV exposure. Leaves *no residue* upon removal on most surfaces (testing required). Maintains a water tight seal in all weather conditions. Its adhesive system remains permanently tacky and bonds well to most surfaces over a wide range of temperatures. 3" paper core.

Applications...

Designed for masking of windows and doors in stucco applications. Ideal for polyethylene splicing or seaming in construction applications.

Physical Properties...

Adhesive

Tensile Strength

Elongation

Peel Adhesion

Adhesion to Backing

Synthetic Rubber

18 lbs/in

80%

60 oz/in

35 oz/in

36 YD (33M) 108 FT

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
50"	(1270mm)	LOG

60 YD (55M) 180 FT

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
50"	(1270mm)	LOG

Alternative to 3M #481, Berry Global #827; Scapa #136; PATCO #5400; Shurtape #VP555; Cantech #278.

7 COLORS AVAILABLE: Clear, black, white, red, green, blue & yellow*.

*Yellow is stocked in 36Yd only.

(*Other colors available as special order; MOQ = 6 logs.)

Non-Skid Safety Tapes...

"Sure-Step" non-skid safety tapes provide a high traction, anti-slip, waterproof surface to help prevent slips and falls. Aggressive acrylic adhesive bonds to a variety of materials and conforms to irregular surfaces. For use indoors & outdoors; on walkways, ramps, stairways; in machine shops & work areas, etc; to comply with OSHA 1910.263 (3).

White liner. 3" neutral core. All prices are per roll by case volume.

NST-20... BLACK

32 mil. 60 grit silicon carbide.

Black is available for purchase by the roll. For less than case quantities, add 10% to 1-5 case column.



NST-20C... COLORS

32 mil. 60 grit aluminum oxide. Full case quantities ONLY.

8 COLORS AVAILABLE: White, translucent (clear), gray, red, orange, yellow, dark green & dark blue.

NST-20F... FLUORESCENT COLORS

32 mil. 60 grit aluminum oxide. Full case quantities ONLY.

3 COLORS AVAILABLE: Red, orange & yellow.

NST-20B/Y... BLACK/YELLOW (STRIPES)

32 mil. 60 grit black silicon carbide, 60 grit yellow aluminum oxide. Full case quantities ONLY.



NST-20GL... LUMINOUS

41 mil. Luminescent, GLOW-in-the-DARK backing impregnated with 60 grit aluminum oxide. Full case quantities ONLY.

NST-20GS... BLACK WITH GLOW INSERT

39 mil. BLACK 60 grit aluminum oxide with 10mm GLOW-in-the-DARK insert/stripe in the center.



Non-Skid Safety Strips/Cleats...

Non-skid safety tape in pre-slotted strips & cleats. Gritty surface increases traction to help prevent slips and falls. Ideal for use on steps, ladders, swimming pools, skateboards, etc. White liner.

NST-1, 2 or 4 -B... BLACK STRIPS

Various width strips, each 12"(300mm) long. Packed 10 strips/box.

NST-624B... BLACK CLEATS

Flexible 6"(150mm) x 24" cleats.

Note: Black cleats are also available with a 3/8" yellow reflective stripe (1" from the edge of the cleat) for increased hazard awareness. Additional \$ per cleat.

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+
20 YD (60 FT) BLACK				
1"	(25mm)	12		
1.5"	(38mm)	8		
2"	(50mm)	6		
3"	(75mm)	4		
4"	(100mm)	3		
6"	(150mm)	2		
8"	(200mm)	1		
12"	(300mm)	1		
18"	(450mm)	1		
24"	(600mm)	1		
36"	(914mm)	1		

Alternative to 3M Safety Walk™, Jessup Safety Track™ 3100; TLC #CT806.

WIDTH	RLS/CS	CASES		
		1-3	4-7	8+
20 YD (60 FT) COLORS				
1"	(25mm)	12		
1.5"	(38mm)	8		
2"	(50mm)	6		
3"	(75mm)	4		
4"	(100mm)	3		
6"	(150mm)	2		
12"	(300mm)	1		

20 YD (60 FT) FL. COLORS OR BLACK/YELLOW

1"	(25mm)	12
1.5"	(38mm)	8
2"	(50mm)	6
3"	(75mm)	4
4"	(100mm)	3
6"	(150mm)	2
12"	(300mm)	1

20 YD (60 FT) LUMINOUS

1"	(25mm)	12
2"	(50mm)	6
3"	(75mm)	4
4"	(100mm)	3
6"	(150mm)	2
12"	(300mm)	1

20 YD (60 FT) BLACK WITH GLOW INSERT

2"	(50mm)	6
----	--------	---

NST-20GS is available for purchase by the roll. For less than case quantities, add 10% to 1-5 case column.

BLACK STRIPS

WIDTH	LENGTH	PCS/BOX	BOX/10
1" (25mm)	x 12" (300mm)	10	
2" (50mm)	x 12" (300mm)	10	
4" (100mm)	x 12" (300mm)	10	

BLACK CLEATS

WIDTH	LENGTH	UNITS	EACH
6" (150mm)	x 24" (609mm)	Each (Minimum 12)	
		Pack (100 Cleats)	
		Carton (200 Cleats)	

Crepe Paper Masking Tapes...

WIDTH	RLS/CS	CASES		
		1-11	12-29	30+

GPM-63... General Purpose Masking

5.5 mil (0.140mm). A **utility grade masking tape**, cream color crepe paper with a solvent based natural rubber adhesive system. Tape conforms to a broad range of surfaces. Recommended for general purpose applications such as light bundling, sealing, holding, and air-dry commercial painting (tape removed once paint has dried). Peel Adhesion 180° to SST: ≥18 oz/in. Tack: ≥10#. Tensile Strength: ≥14 lbs/in. Temperature Resistance: ≤176°F (30 min). Elongation: ≤20%. 3" TalonTape core.

49.2" (1250mm) x 1800M Jumbos Available.



60 YD (55M) 180 FT

1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	*	(12mm) 72
3/4"	*	(18mm) 48
1"	*	(24mm) 36
1.5"	*	(36mm) 24
2"	*	(48mm) 24
3"	*	(72mm) 12
4"	*	(96mm) 12
6"	*	(144mm) 8
6"	(152.4mm)	8
12"	(288mm)	6
12"	(304.8mm)	6
49.2"	(1250mm)	LOG

Alternative to Tesa #53123 & #50124; Hystik #803; 3M #200 & #2307; Shurtape #CP83 & #CP107; IPG #PG415 & #PG515; CanTech #107-00; Alpha Beta #63.

* Lower proportional price, as stocked pre-slit.

CPM-60... Colored Masking Tape

5.4 mil. Color saturated crepe paper backing with rubber adhesive. The adhesive is formulated for easy release and good adhesion to a variety of substrates. Designed for color coding for identification or differentiation. Not printable. Conformable to many irregular surfaces. Suitable for bundling, marking of defective parts or materials, produce marking, color coding, and polybag sealing. Adhesion: 32 oz/in. Tensile: 19 lbs/in. Elongation: 7%. Application Temperature: 50°F to 90°F. 3" neutral paper core.

6 COLORS AVAILABLE: Black, white, red, dark blue, dark green & yellow.

58.5" (1485mm) x 1524M (1667 yd) Jumbos Available.

60 YD (55M) 180 FT

1/4"	(6mm)	192
3/8"	(9mm)	128
1/2"	(12mm)	96
5/8"	(15mm)	80
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
12"	(288mm)	6
58.5"	(1485mm)	LOG

Alternative to IPG #561 & #PF-3; Shurtape #CP-632; CanTech 120; 3M #262 & #267.

Painter's Grade Masking Tape (UV Resistant)...

PGM-UV14... Blue UV Resistant Masking Tape

5.5 mil Painter's Grade Masking tape with a specially formulated acrylic adhesive system that provides clean removal characteristics and UV resistance - up to 14 days of outdoor exposure. Exhibits easy unwind, excellent conformability, and clean removal from a wide variety of surfaces (testing recommended). Preslit rolls are individually edge shrink wrapped - perfect for retail sales; slit rolls are bulk packed. TalonTape branded. Peel Adhesion 180° to SST: ≥13 oz/in. Tack: ≥10#. Tensile Strength: ≥16 lbs/in. Temperature Resistance: ≤194°F (45 min). Elongation: ≤20%. 3" paper core.

39" (990mm) x 1800M Jumbos Available.



60 YD (55M) 180 FT

1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36
1.5"	(36mm)	24
2"	(48mm)	24
3"	(72mm)	12
4"	(96mm)	12
39"	(990mm)	LOG

Alternative to Shurtape #CP27; IPG #PT14; 3M #2090.

Other roll widths available upon request (custom slit and bulk packed).



Kraft Flatback Tape...

KFT-530... Brown Kraft Flatback Tape

7.3 mil. Brown kraft flatback paper coated with a pressure sensitive, natural/synthetic rubber adhesive. This economical, flatback tape offers a positive seal with excellent adhesive properties, designed to minimize carton sealing failures and deter potential theft. Performs well under a wide range of temperature and humidity conditions. Used for carton sealing, packaging, core starting, tabbing, splicing, picture framing, silk screening, and beaming/leasing. Complies with postal regulation for uninsured packages. Meets PPP-T-42C, Type II; CID A-A-883B, Type II. **KFT-530 is not repulpable.** Adhesion to SST: 55 oz/in. Tensile Strength: 42 lbs/in. Elongation: 7%. Temperature Range: 40°F to 175°F. 3" neutral paper core.

KFT-PM2... Tan Kraft Flatback Tape

6.0 mil. Tan Kraft flatback paper coated with a pressure sensitive, natural rubber resin adhesive. Offers a positive seal and excellent adhesion to discourage pilfering. Good balance of quick stick and holding properties, and can be used on all types of cartons. Performs well under a wide range of temperatures and humidity conditions. Complies with USPS requirements. Meets ASTM D6123, Type II; PPP-T-42C, Type II; CID A-A-883B, Type II; Boeing BAC 5317. **KFT-PM2 is not repulpable.** Adhesion to SST: 57 oz/in. Tensile Strength: 36 lbs/in. Elongation: 3%. Temperature Range: 40°F to 225°F. 3" neutral paper core.

Flatback Paper Tape...

CFB-60... Printable Colored Flatback Tape

5.8 mil. Bright, colorful flatback papers coated with a natural rubber adhesive. The flat surface (vs. creped paper) results in high quality printing. Easy unwind characteristic for high speed printing. Tape exhibits high face to face bond strength. Used for flexographic printing, color coding and identification (write-on surface). Tensile: 32 lbs/in. Adhesion: 31 oz/in. Elongation: 3%. Meets ASTM D6123, Type II; CID A-A-883B, Type II. 3" neutral paper core.

1 STANDARD COLOR: White.

***4 ADDITIONAL STOCK COLORS (ADD 15%): Red, yellow, light blue & orange.**

Custom printing available. Call/email for information and pricing.

CFB-75... Colored Flatback Tape

7.3 mil. Moisture resistant, medium tensile strength, pressure sensitive flatback tape with a natural/synthetic rubber adhesive. Used for packaging, bookbinding, marking bins and shelves, decorative edging and color coding. Tape is NOT PRINTABLE and not repulpable. Tensile: 48 lbs/in. Adhesion: 60 oz/in. Elongation: 3%. Temperature Range: 40°F to 180°F. 3" neutral paper core.

2 COLORS AVAILABLE: Black & red.

CFB-75... as BOOKBINDING TAPE

Can be used in bookbinding applications.

(See page 25 for UPVC bookbinding tapes.)

WIDTH	RLS/CS	CASES		
		1-11	12-29	30+

60 YD (55M) 180 FT

1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
56.25"	(1428mm)	LOG
56.25"	(1428mm)	360 yd / LOG

Alternative to IPG #530, #534 & #539; Tesa #4313; HYSTIK #886; Shurtape FP97.

56.25" (1428mm) x 1200 Yd Jumbos Available.

60 YD (55M) 180 FT

1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
58.5"	(1486mm)	LOG

Alternative to IPG #PM2.

58.5" (1486mm) x 2400 Yd Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+
60 YD (55M) 180 FT WHITE* (COLORS +15%)				

1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	24
3"	(72mm)	12 or 16
4"	(96mm)	12
6"	(144mm)	8
12"	(288mm)	4
57"	(1448mm)	LOG

Alternative to 3M #250; IPG #PF2; Shurtape #FP-227; Permaceel #P-724 & #P726; Achem #IP57.

Jumbos Available.

60 YD (55M) 180 FT

1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
58"	(1473mm)	LOG

Alternative to IPG #546; 3M #256.

58" (1473mm) x 1800 Yd Jumbos Available.

600 YD (550M) 180 FT

58"	(1473mm)	LOG
Call for pricing of slit goods (must purchase full web width).		

Tamper Evident Tapes/Security Tapes...

Tamper Evident tapes with 1 mil polyester film and **hot melt rubber adhesive**. These unique, tamper-proof sealing tapes leave an **instant hidden message upon removal** to protect sealed contents against theft and contamination. Used in critical high security applications: pharmaceuticals, chemical & medical equipment, crime evidence & independent labs, currency handlers, money bags, credit card/security bags, shipping & cargo handlers, transportation in food items. Ideal for high cost and/or high demand products, such as electronics, clothing and sporting goods. Applies to corrugated cartons/packaging, stretch film, plastics, uncoated paper, metal and glass.

TEV-OVR... Solid Red, Non-Surface Printed

Solid, non-surface printed tape with hidden “OPEN VOID” message upon removal. Has an instant initial grab & can be removed immediately to show the invisible legend.



TEV-OVR



TEV-STR... **Red/White Stripes with Tamper Warning**
Add an extra measure of protection with its **red & white striped candy cane pattern** and **surface printed trilingual tamper evident warning** to deter pilferers. It also has a **trilingual “OPENED ABIERTO OUVERT”** message upon removal.

WIDTH	RLS/CS	ROLL	CASE
2" (50mm)	42	55 YD (50M)	

Specify TEV-OVR or TEV-STR when ordering.



TEV-STR surface print



TEV-STR hidden legend



Pipe Thread Seal Tape... PTFE-35S...

100% Unsintered Virgin Polytetrafluoroethylene (PTFE). A standard density, 3.5 mil white film in labeled plastic spool/box. Lubricates joints, making them easy to assemble for leak proof seals. For all industrial applications, including water, oil, gas, most chemicals, hydraulic and high pressure lines. MIL Spec T-27730A & UL31 RO. Density: 0.35 g/cm³. Tensile Strength: >8 N/mm². Elongation >50%. Temperature Range: -450°F to 500°F. 5 sub-packs per carton.

WIDTH x LENGTH	RLS/CS	1-3	4-7	8+
1/2" x 520"	500			

Alternative to 3M #48 & #547.



Social Distancing Imprinted Floor Tapes...

Anti-Skid Safety Tapes...

Continuously printed warning on vinyl tape with an embossed waterproof plastic wound on a white liner. High traction, anti-slip surface helps prevent slips/falls. Bonds to a variety of materials and conforms to irregular surfaces. For use indoors & outdoors; on walkways, ramps, stairways and other non-porous surfaces. 16” legends, repeated 40x per roll.

See page 14 for unprinted non-skid tape.

Vinyl Safety Tapes...

Pressure sensitive vinyl tapes with clear polypropylene over-laminated warnings wound on a white liner. These social distancing tapes are made from durable, resilient material designed to withstand heavy foot traffic. Available in continuously printed 16” legends, repeated 80x per roll, or die-cut in 6” circles, repeated 50x per roll.

See pages 8-11 for unprinted vinyl tapes.



6" Circles



PRODUCT	LEGENDS	SIZE	RLS/CS	ROLL	CASE
---------	---------	------	--------	------	------

ANTI-SKID TAPES (Black/Yellow)

NST-6FSH	6FT STAND HERE 6FT	3" x 18Yd	16
NST-WHUC	WAIT HERE UNTIL CALLED	3" x 18Yd	16

VINYL TAPES (Black/Yellow)

CVT-6FSH	6FT STAND HERE 6FT	3" x 36Yd	16
CVT-WHUC	WAIT HERE UNTIL CALLED	3" x 36Yd	16

VINYL DIE-CUT CIRCLES (Black/Red on White)

CVT-DKYD	KEEP YOUR DISTANCE	6" (50 Circles)	16
----------	--------------------	-----------------	----




Polypropylene Carton Sealing Tape - Imprinted Legends... with ACRYLIC WATER BASED ADHESIVE



PP20F-W... FRAGILE on White Film

2.0 mil (0.055mm). 30 μ film. **Water based acrylic adhesive**. One (1) color printing: red text on WHITE film. 3" neutral core/carton.



WIDTH x LENGTH	RLS/CS	CASES		
		1-5	6-18	19+
FRAGILE HANDLE WITH CARE				
2" (48mm)	x 110 yd	36		



PP20W-C... WARNING/AVISO on Clear Film or PP20W-W... WARNING/AVISO on White Film

2.0 mil (0.055mm). 30 μ film. **Water based acrylic adhesive**. One (1) color printing: Red text on CLEAR or WHITE film. 3" neutral core/carton.

Specify PP20W-C (clear film) or PP20W-W (white film) when ordering.

WARNING / AVISO		
2" (48mm)	x 110 yd	36

Alternative to IPG #321CP; STA #124x.



PP20S-C... STOP/CHECK on Clear Film or PP20S-W... STOP/CHECK on White Film

2.0 mil (0.055mm). 30 μ film. **Water based acrylic adhesive**. Two (2) color printing: Red & black text on CLEAR or WHITE film. 3" neutral core/carton.

Specify PP20S-C (clear film) or PP20S-W (white film) when ordering.

STOP CHECK CONTENTS (2" Pattern)		
2" (48mm)	x 110 yd	36
2" (48mm)	x 1000 yd	6

Alternative to 3M #3771; IPG #3215P; STA #124x; Achem #12B.



PP20S-C... STOP/CHECK on Clear Film or PP20S-T... STOP/CHECK on Tan Film

2.0 mil (0.055mm). 30 μ film. **Water based acrylic adhesive**. Two (2) color printing: Red & black text on CLEAR or TAN film. 3" neutral core/carton.

Specify PP20S-C (clear film) or PP20S-T (tan film) when ordering.

STOP CHECK CONTENTS (3" Pattern)		
3" (72mm)	x 110 yd	24

Alternative to 3M #3771; IPG #3215P; STA #124x.

Custom printed tapes are available. Please contact us for product information and pricing.

Custom Printed Tapes...

Terms, Options and Additional Charges:

11 Stock Ink Colors:

White	Yellow 108	Orange 165
Gray 431	Green 347	Burgundy 222
Black	Process Blue	Brown 476
Red 199	Reflex Blue	

- Non-stock PMS colors:
2 case minimum: Add \$ per color
5+ cases: Add \$ per color
Recurring charge (per order & item)
- 2 ink colors (upcharge on 1 ink price)
2 case minimum: Add 20%
5+ cases: Add 15%
- 3 ink colors (upcharge on 1 ink price)
5 case minimum: Add 30%
- Floodcoats (or >50% ink coverage):
Add 30% upcharge on 1 ink price

Art & Plate Charges:

- One time plate charges:
Standard plate up to 7": (1st color)
Oversized plates 7-14": (1st color)
Additional ink colors: per color
- Plates are to remain property of the printer.
Printing plates will be kept on file for 3 years; if not reordered in that time limit, the plates will be purged.
- Must be vector art or artwork charges may apply at /hour (1 hour minimum charge).

Other Conditions of Sale:

- Price is F.O.B. Origin. Transportation charges are prepaid and allowed to destination on custom print orders of invoice value or more, within contiguous US via lowest cost routing.
- Custom printed tape orders cannot be combined with stock orders.
- We reserve right to ship ± 15% and partial cases must be accepted.
- Print legend height is approximately 1-5/8" for 2" tapes, 2-5/8" for 3" tapes – with usually a 1/2" – 3/4" space between repeats. Maximum plate length is 14".

Lead Time:

Allow 2-3 business days for artwork approval generation. After payment and all approvals have been received (if required), allow approximately 3-4 weeks before shipping.

Custom Printed Tapes are NOT CANCELABLE or RETURNABLE.

Subject to change without notice. Contact us for the current Custom Printed Tapes Product Information & Pricing Packet.

ITEM SIZE	R/C	1 case	2-4	5-9	10-24	25-49	50-71	72+
OPP-19CP – Custom Printed Polypropylene Tape								
1.9 Mil Clear, Tan or White Tape with Hot Melt Rubber Adhesive								
1 STOCK INK COLOR								
2" (48mm) x 55 yds	36							
2" (48mm) x 110 yds	36							
2" (48mm) x 1000 yds	6							
3" (72mm) x 55 yds	24							
3" (72mm) x 110 yds	24							
3" (72mm) x 1000 yds	4							

OPP-25CP – Custom Printed Polypropylene Tape								
2.5 Mil Clear, Tan or White Tape with Hot Melt Rubber Adhesive OR 2.4 Mil Clear, Tan or White with Acrylic Water Based Adhesive (available at 10+ cases)								
1 STOCK INK COLOR								
2" (48mm) x 55 yds	36							
2" (48mm) x 110 yds	36							
2" (48mm) x 1000 yds	6							
3" (72mm) x 55 yds	24							
3" (72mm) x 110 yds	24							
3" (72mm) x 1000 yds	4							

OPP-30CP – Custom Printed Polypropylene Tape								
3.0 Mil Clear, Tan or White Tape with Hot Melt Rubber Adhesive OR 3.2 Mil Clear, Tan or White with Acrylic Water Based Adhesive (available at 10+ cases)								
1 STOCK INK COLOR								
2" (48mm) x 55 yds	36							
2" (48mm) x 110 yds	36							
2" (48mm) x 1000 yds	6							
3" (72mm) x 55 yds	24							
3" (72mm) x 110 yds	24							
3" (72mm) x 1000 yds	4							

UPVC- CP – Custom Printed UPVC Tape								
32μ Clear, Tan or White Film with Solvent Based, Natural Rubber Adhesive (other UPVC film colors & thickness available at an additional charge)								
1 STOCK INK COLOR								
1" (24mm) x 55 yds	72							
1" (24mm) x 110 yds	72							
2" (48mm) x 55 yds	36							
2" (48mm) x 110 yds	36							
3" (72mm) x 55 yds	24							
3" (72mm) x 110 yds	24							

Custom Printed Tape is also available in:								
• Other UPVC Film Colors and Thicknesses	• BOPP "Locked-In" Printing							
• Water Activated "WAT" Tapes	• Barricade Tape Printing							
	• Custom Tamper Evident Tapes							
Contact us for pricing/details.								

Polypropylene Carton Sealing Tapes...

with ACRYLIC WATER BASED ADHESIVE

OPP-16AW... CLEAR & BROWN/DARK TAN

1.6 mil (0.040mm). 23 micron film. **Water Based Acrylic Adhesive**.

Peel Adhesion: 16 oz/in. Tensile: 11 lbs/in. Elongation: 180%.

3" TalonTape core/carton.

49" (1260mm) x 4000M Jumbos Available.

OPP-18AW... CLEAR & DARK TAN/BROWN

1.8 mil (0.045mm). 25 micron film. **Water Based Acrylic Adhesive**.

Peel Adhesion: 18 oz/in. Tensile: 16 lbs/in. Elongation: 180%.

Temp. Resistance: 32°F to 140°F. 3" TalonTape core/carton.

49" (1260mm) x 4000M Jumbos Available.

Alternative to 3M #302; IPG #161; Shurtape #AP 101; STA #1060 & #1160.

OPP-20AW... CLEAR & DARK TAN/BROWN

2.0 mil (0.050mm). 28 micron film. **Water Based Acrylic Adhesive**.

Peel Adhesion: 22 oz/in. Tensile: 18 lbs/in. Elongation: 180%.

Temp. Resistance: 32°F to 140°F. 3" TalonTape core/carton.

49" (1260mm) x 4000M Jumbos Available.

Alternative to 3M #311; IPG #400; STA #1082 & #1182; Cantech #259; Taratape #38; Achem #CS20A; Shurtape #AP 301; Berry Global #183.

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+

144 YD (132M) CLEAR ONLY

6"	(150mm)	12
----	---------	----

1000 YD (914M) CLEAR & DARK TAN/BROWN[†]

3/4"	(18mm)	16
1"	(24mm)	12
1.5"	(36mm)	8
2"	† (48mm)	6
3"	(72mm)	4

[†] COLOR NOTE: Dark Tan/Brown stocked in 2" (48mm) x 1000Yd only.

OPP-26AW... CLEAR, WHITE & DARK TAN

2.6 mil (0.065mm). 38 micron film. **Water Based Acrylic Adhesive**.

Peel Adhesion: 22 oz/in. Tensile: 27 lbs/in. Elongation: 180%.

Temp. Resistance: 32°F to 140°F. 3" TalonTape core/carton.

49" (1260mm) x 3000M Jumbos Available.

Alternative to 3M #313; IPG #291; Central #420; STA #1352; Taratape #65; Achem #CS26A; Shurtape #AP 401; Berry Global #266.

1000 YD (914M) CLEAR ONLY

2"	(48mm)	6
3"	(72mm)	4



* Lower proportional price, as stocked pre-slit.

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
55 YD (50M)	CLEAR & DARK TAN/BROWN			
2"	(48mm)	36		
110 YD (100M)	CLEAR & DARK TAN/BROWN			
2"	(48mm)	36		
3"	(72mm)	24		

Alternative to 3M #302; IPG #161; Shurtape #AP 101; STA #1060 & #1160.

55 YD (50M) CLEAR & DARK TAN/BROWN		
2"	(48mm)	36
3"	(72mm)	24
110 YD (100M)	CLEAR & DARK TAN/BROWN	
2"	(48mm)	36
3"	(72mm)	24
1000 YD (914M)	CLEAR ONLY	
2"	(48mm)	6
3"	(72mm)	4

55 YD (50M) CLEAR & DARK TAN/BROWN		
3/8"	(9mm)	192
1/2"	(12mm)	144
3/4"	(18mm)	96
1"	(24mm)	72
1.5"	(36mm)	48
2"	(48mm)	36
3"	(72mm)	24
4"	(96mm)	18
6"	(144mm)	12
49"	(1260mm)	LOG

110 YD (100M) CLEAR & DARK TAN/BROWN		
3/8"	(9mm)	192
1/2"	(12mm)	144
3/4"	(18mm)	96
1"	*(24mm)	72
1.5"	(36mm)	48
2"	*(48mm)	36
3"	*(72mm)	24
4"	(96mm)	18
4.75"	(120mm)	18
49"	(1260mm)	LOG

* Lower proportional price, as stocked pre-slit.

55 YD (50M) CLEAR ONLY		
3/8"	(9mm)	192
1/2"	(12mm)	144
3/4"	(18mm)	96
1"	(24mm)	72
1.5"	(36mm)	48
2"	*(48mm)	36
3"	*(72mm)	24
4"	(96mm)	18
6"	(144mm)	12
49"	(1260mm)	LOG

110 YD (100M) CLEAR, WHITE & DK.TAN/BROWN [†]		
3/8"	(9mm)	192
1/2"	(12mm)	144
3/4"	(18mm)	96
1"	(24mm)	72
1.5"	(36mm)	48
2"	*(48mm)	36
3"	*(72mm)	24
4"	(96mm)	18
6"	(144mm)	12
49"	(1260mm)	LOG

* COLOR NOTE: Dark Tan/Brown stocked in 3" (72mm) x 110Yd only.

Polypropylene Carton Sealing Tapes...

with ACRYLIC WATER BASED ADHESIVE

OPP-32AW... CLEAR, DARK TAN & WHITE

3.2 mil (0.080mm). 48 micron film. **Water Based Acrylic Adhesive**. Premium grade, high strength, biaxially oriented polypropylene film. Designed for demanding packaging requirements. Peel Adhesion: 22 oz/in. Tensile Strength: 32 lbs/in. Elongation: 180%. Temp. Resistance: 32°F to 140°F. 3" TalonTape core/carton.

* Lower proportional cost, as stocked pre-slit.

49" (1260mm) x 2000M Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
72 YD (66M)				
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
1.5"	(36mm)	48		
2"	* (48mm)	36		
3"	* (72mm)	24		
4"	(96mm)	18		
49"	(1260mm)	LOG		

Alternative to 3M#315; IPG #341; STA #1535.

Polypropylene Carton Sealing Tapes...

ACRYLIC SOLVENT BASED ADHESIVE

OPP-22CC... CRYSTAL CLEAR

2.1 mil (0.054mm). 28 micron film. A biaxially oriented polypropylene tape coated with a solvent based acrylic adhesive. See-through "CRYSTAL CLEAR" imprinted on 3" core. Crystal clear tape is non-yellowing & UV resistant with long shelf life and no fish eyes. Used for lamination and carton sealing. May also be used in cold temperature applications. Meets spec A-A-1684C. Adhesion: 23 oz/in. Tensile Strength: 21 lbs/in. Elongation: 140%. Temp. Resistance: 32°F to 140°F.



* Lower proportional cost, as stocked pre-slit.

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
55 YD (50M)				
3/8"	(9mm)	192		
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	* (24mm)	72		
1.5"	(36mm)	48		
2"	* (48mm)	36		
3"	(72mm)	24		
4"	(96mm)	18		
49"	(1260mm)	LOG		neutral core

110 YD (100M)

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
110 YD (100M)				
3/8"	(9mm)	192		
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
1.5"	(36mm)	48		
2"	* (48mm)	36		
3"	(72mm)	24		
4"	(96mm)	18		
49"	(1260mm)	LOG		neutral core

Alternative to Shurtape #PP 803; STA #STAA326C; Achem #CC22 & #12T.

OPP-26CC... CRYSTAL CLEAR

2.7 mil (0.068mm). 40 micron film. A biaxially oriented polypropylene tape coated with a solvent based acrylic adhesive. See-through "CRYSTAL CLEAR" imprinted on 3" core. Crystal clear tape is non-yellowing & UV resistant with long shelf life and no fish eyes. Used for moderate demand lamination and carton sealing applications. May also be used in cold temperature applications. Meets spec A-A-1684C. Adhesion: 28 oz/in. Tensile Strength: 27 lbs/in. Elongation: 140%. Temp. Resistance: 32°F to 140°F.

* Lower proportional cost, as stocked pre-slit.

NOTE: 110Yd is stocked in 2"(48mm) only; other widths available as a special order (except logs).

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
55 YD (50M)				
3/8"	(9mm)	192		
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
1.5"	(36mm)	48		
2"	* (48mm)	36		
3"	* (72mm)	24		
4"	* (96mm)	18		
49"	(1260mm)	LOG		neutral core

110 YD (100M)

2"	(48mm)	36
----	--------	----

Alternative to STA #STAA326C; Achem #12W.

OPP-34CC... CRYSTAL CLEAR

3.6 mil (0.091mm). 60 micron film. A biaxially oriented polypropylene tape coated with a solvent based acrylic adhesive. See-through "CRYSTAL CLEAR" imprinted on 3" core. Crystal clear tape is non-yellowing & UV resistant with long shelf life and no fish eyes. Used for moderate demand lamination and carton sealing applications. May also be used in cold temperature applications. Meets spec A-A-1684C. Adhesion: 30 oz/in. Tensile Strength: 38 lbs/in. Elongation: 140%. Temp. Resistance: 32°F to 140°F.

* Lower proportional cost, as stocked pre-slit.

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
55 YD (50M)				
3/8"	(9mm)	192		
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
1.5"	(36mm)	48		
2"	* (48mm)	36		
3"	* (72mm)	24		
4"	(96mm)	18		
12"	(300mm)	6		
49"	(1260mm)	LOG		neutral core

Alternative to Achem #12X.

Polypropylene Carton Sealing Tapes...

with ACRYLIC SOLVENT BASED ADHESIVE

OPP-20A... CLEAR

1.9 mil (0.049mm). 25 micron film. Biaxially oriented polypropylene tape with **solvent based acrylic adhesive**. Adhesion: 21 oz/in. Tensile: 15 lbs/in. Elongation: 140%. Temperature Resistance: -4°F to 158°F. 3" neutral core/carton.

63" (1605mm) x 4000M Jumbos Available.

Alternative to Achem #127; Shurtape #PP 802 & #PP 810.

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
110 YD (100M)				
3/8"	(9mm)	192		
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
1.5"	(36mm)	48		
2"	(48mm)	36		
3"	(72mm)	24		
4"	(96mm)	18		
63"	(1605mm)	LOG	neutral core	

OPP-22A... CLEAR

2.1 mil (0.054mm). 28 micron film. Biaxially oriented polypropylene tape with **solvent based acrylic adhesive**. Adhesion: >23 oz/in. Tensile: >20 lbs/in. Elongation: 140%. Temperature Resistance: -4°F to 158°F. 3" neutral core/carton.

49" (1260mm) x 4000M Jumbos Available.

Alternative to Achem #AS22 & #122; Shurtape #PP 802; Berry Global #730.

55 YD (50M)
3/8" (9mm) 192
1/2" (12mm) 144
3/4" (18mm) 96
1" (24mm) 72
1.5" (36mm) 48
2" (48mm) 36
3" (72mm) 24
4" (96mm) 18
49" (1260mm) LOG neutral core

110 YD (100M)
3/8" (9mm) 192
1/2" (12mm) 144
3/4" (18mm) 96
1" (24mm) 72
1.5" (36mm) 48
2" (48mm) 36
3" (72mm) 24
4" (96mm) 18
49" (1260mm) LOG neutral core

OPP-26A... CLEAR †

2.6 mil (0.066mm). 40 micron film. Biaxially oriented polypropylene tape with **solvent based acrylic adhesive**. Excellent balance of adhesion and tensile strength for heavy weight carton sealing applications. Meets SPEC A-A-1684C. Adhesion: >25 oz/in. Tensile: >26 lbs/in. Elongation: 140%. Temperature Resistance: -4°F to 158°F. 3" neutral core/carton.

49" (1260mm) x 3000M Jumbos Available.

Alternative to Shurtape #PP 815; Achem #AS26 & #123; Permacel #P-915.

55 YD (50M)
3/8" (9mm) 192
1/2" (12mm) 144
3/4" (18mm) 96
1" (24mm) 72
1.5" (36mm) 48
2" † (48mm) 36
3" (72mm) 24
4" (96mm) 18
49" (1260mm) LOG neutral core

110 YD (100M)
3/8" (9mm) 192
1/2" (12mm) 144
3/4" (18mm) 96
1" (24mm) 72
1.5" (36mm) 48
2" (48mm) 36
3" (72mm) 24
4" (96mm) 18
49" (1260mm) LOG neutral core

OPP-34A... CLEAR

3.5 mil (0.089mm). 60 micron film. Biaxially oriented polypropylene tape with **PREMIUM GRADE solvent based acrylic adhesive**. Its strong adhesion to cardboard and high tensile strength make it ideal for extremely demanding packaging needs. Adhesion: >28 oz/in. Tensile: >37 lbs/in. Elongation: 140%. Temperature Resistance: -4°F to 158°F. 3" neutral core/carton.

49" (1260mm) x 2000M Jumbos Available.

Alternative to IPG #341; STA #1535; Achem #AS36 & #124; Permacel #P-919.

55 YD (50M)
3/8" (9mm) 192
1/2" (12mm) 144
3/4" (18mm) 96
1" (24mm) 72
1.5" (36mm) 48
2" (48mm) 36
3" (72mm) 24
4" (96mm) 18
12" (300mm) 6
49" (1260mm) LOG neutral core

Colored Polypropylene Carton Sealing Tapes...

with ACRYLIC ADHESIVE

OPP-20C... COLORS with Water Based Acrylic

2.0 mil (0.048mm). 28 micron film. Water Based Acrylic Adhesive. Used for carton sealing, color coding & identification. Peel Adhesion: 22 oz/in. Tensile Strength: 18 lbs/in. Elongation: 180%. Temperature Range: 32°F to 150°F. 3" neutral core/carton.

9 BRIGHT SHINY COLORS: White, black, yellow, orange, red, blue, green, pink & purple.

49" (1260mm) x 4000M Jumbos Available.

* Lower proportional price, as stocked pre-slit.

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
1000 YD (914M)				
2"	(48mm)	6		
3"	(72mm)	4		

OPP-26CAW... COLORS with Water Based Acrylic

2.6 mil (0.065mm). 38 micron film. Water Based Acrylic Adhesive. Peel Adhesion: 22 oz/in. Tensile: 27 lbs/in. Elongation: 180%. Temp. Range: 32°F to 140°F. 3" neutral core/carton.

6 BRIGHT SHINY COLORS: White, red, green, orange, yellow & blue.

OPP-22C... COLORS with Solvent Based Acrylic

2.2 mil (0.055mm). 28 micron film. Solvent Based Acrylic Adhesive. Used for carton sealing, color coding, splicing and identification. Adhesion to SST: 27 oz/in. Tensile Strength: 20 lbs/in. Elongation: 140%. Temperature Range: 32°F to 150°F. 3" neutral core/carton.

6 BRIGHT SHINY COLORS: White, yellow, orange, red, blue & green.

49" (1260mm) x 4000M Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
55 YD (50M)				
3/8"	(9mm)	192		
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
1.5"	(36mm)	48		
2"	* (48mm)	36		
3"	(72mm)	24		
4"	(96mm)	18		
49"	(1260mm)	LOG		neutral core

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
110 YD (100M)				
3/8"	(9mm)	192		
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
1.5"	(36mm)	48		
2"	* (48mm)	36		
3"	(72mm)	24		
4"	(96mm)	18		
49"	(1260mm)	LOG		neutral core

Alternative to 3M #311; IPG #321C; Cantech #261; Achem #CS20C; STA #1182.

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
110 YD (100M)				
2"	(48mm)	36		

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
1000 YD (914M)				
2"	(48mm)	6		

49" (1260mm) x 3000M Jumbos Available (White ONLY).

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
55 YD (50M)				
3/8"	(9mm)	192		
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
1.5"	(36mm)	48		
2"	(48mm)	36		
3"	(72mm)	24		
4"	(96mm)	18		
49"	(1260mm)	LOG		neutral core

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
110 YD (100M)				
3/8"	(9mm)	192		
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
1.5"	(36mm)	48		
2"	(48mm)	36		
3"	(72mm)	24		
4"	(96mm)	18		
49"	(1260mm)	LOG		neutral core

Alternative to Achem #122; Berry Global #730 Red.

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
72 YD (66M)				
3/8"	(9mm)	192		
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
1.5"	(36mm)	48		
2"	(48mm)	36		
2.5"	(60mm)	30		
3"	(72mm)	24		
4"	(96mm)	18		
49"	(1260mm)	LOG		neutral core

Alternative to Achem #123; 3M #373.

* Lower proportional price, as stocked pre-slit.

OPP-26C... COLORS with Solvent Based Acrylic

2.6 mil (0.066mm). 40 micron film. Solvent Based Acrylic Adhesive. High quality adhesive and strong film makes this tape an excellent choice for demanding carton sealing, splicing and color coding applications. Adhesion to SST: 25 oz/in. Tensile: 26 lbs/in. Elongation: 140%. Temp. Resistance: 32°F to 150°F. 3" neutral core/carton.

5 BRIGHT SHINY COLORS: White, yellow, red, blue & green.

49" (1260mm) x 3000M Jumbos Available.

Polypropylene Carton Sealing Tapes...

with NATURAL RUBBER BASED ADHESIVE (recommended for recycled cartons & cold temperature application)

OPP-18NR... Clear

1.8 mil (0.045mm). 25 micron film. **Solvent Based Natural Rubber Adhesive.** Tensile: 21 lbs/in. Adhesion to steel: 22 oz/in. Elongation: 170%. Application Temperature Range: 0°F to 150°F. 3" neutral core.

WIDTH	RLS/CS	CASES		
		1-11	12-24	25+
110 YD (100M)				
2"	(48mm)	36		

Alternative to IPG #500; STA #1580; Cantech #253.

OPP-20NR... Clear

2.0 mil (0.048mm). 28 micron film. **Solvent Based Natural Rubber Adhesive.** Tensile: 23 lbs/in. Adhesion to Steel: 22 oz/in. Elongation: 170%. Application Temperature Range: 0°F to 150°F. 3" neutral core.

110 YD (100M)		
1.5"	(36mm)	48
2"	(48mm)	36
3"	(72mm)	24

Alternative to IPG #500 & #530; STA #1582; Achem #CS20NR.

OPP-26NR... Clear

2.5 mil (0.062mm). 40 micron film. **Solvent Based Natural Rubber Adhesive.** Tensile: 30 lbs/in. Adhesion to Steel: 20 oz/in. Elongation: 190%. Application Temperature Range: 0°F to 150°F. 3" neutral core.

55 YD (50M)		
2" (48mm) 36		
110 YD (100M)		
2"	(48mm)	36
3"	(72mm)	24

Alternative to IPG #510 & #520; Achem #CS25NR.

Cellophane Stationery/Carton Sealing Tape...

CELLO... Static Free

1.8 mil (0.046mm). Pure cellulose film with a solvent based natural rubber adhesive. Transparent, hand-tearable, eco-friendly tape. Used for sealing, attaching & mending where **biodegradable** tape is required. This **STATIC-FREE** product is highly recommended for the electronics industry. Adhesion: 30 oz/in. Tack: 18#. Tensile: 20 lbs/in. Elongation: >15%. Temperature Range: 32°F to 150°F. 3" neutral paper core.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
72 YD (66M)				
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
2"	(48mm)	36		
1000 YD (914M)				
6"	(144mm)	2	*Available as special order.	

Alternative to Shurtape #CT109; Tesa #4101 PV2; 3M #610 & #5912; Clipper #4206; Scapa #1109; IPG #MC-1; Cantech #206.

Polyester Carton Sealing Tape...

PES-32G... clear

3.0 mil total thickness. 50 micron heavy duty polyester film with an aggressive hot melt adhesive. High quality, high performance packaging, sealing, and splicing tape. Superior adhesive properties to insure instant holding power. Provides a quick reliable seal when used for strip closure of regular slotted containers, overlap sealing, and fiber drum sealing. Adhesion: 65 oz/in. Tensile: 55 lbs/in. Elongation: 100%. Temp. Range: -10°F to 140°F. Meets ASTM D5486, Type II, Class 2 (replaces PPP-T-60E, A-A-1830); A-A-1684C (replaces A-A-1684B, PPP-T-70). 3" neutral core.

59" (1500mm) x 3500M Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-5	6-12	13+
60 YD (55M)				
1"	(25.4mm)	72		
1.5"	(38.1mm)	48		
2"	(50.8mm)	36		
3"	(76.2mm)	24		
59"	(1500mm)	LOG	neutral core	

Alternative to Permacel #P-929; Bemis #BT-41; Cantech #0228; IPG #780; 3M #351 (clear), #375.

Other roll widths and/or lengths available.
Contact us for a custom quote!

UPVC Carton Sealing Tapes (Packaging)...

with NATURAL RUBBER BASED ADHESIVE (recommended for recycled cartons & cold temperature application)

WIDTH	RLS/CS	CASES		
		1-9	10-24	25+

UPVC-22... Packaging

32 micron UPVC film. Solvent based natural rubber adhesive. Quiet unwind. Excellent quality carton sealing tape. Recommended for sealing cartons with coated or uncoated surfaces, corrugated cartons with high recycled paper content, and cold temperature applications. Printable, heat-shrinkable, hand-tearable, and resistant to most acids, solvents and alkalis. Total Thickness: 2.2 mil. Adhesion: 15 oz/in. Tensile: 42 lbs/in. Elongation: 75%. Temperature Resistance: 158°F. 3" neutral core.

3 COLORS AVAILABLE: White, clear & tan.

Master Jumbos Available.

NOTE: 6" and 12" PRINTER rolls available (see page 30 for details).

55 YD (50M)		
1/2"	(12mm)	144
3/4"	(19mm)	96
1"	(25mm)	72
1.5"	(38mm)	48
2"	* (48mm)	36
3"	* (72mm)	24
59"	(1500mm)	LOG

110 YD (100M)

110 YD (100M)		
3/4"	(19mm)	96
1"	(25mm)	72
1.5"	* (38mm)	48
2"	* (48mm)	36
3"	* (72mm)	24
4"	(96mm)	18
59"	(1500mm)	LOG

Alternative to Tesa #4120; NOPI #4085; IPG #530; Monta #281/220; STA #1263; Shurtape #VF719; 3M #690; Achem #CS22U.

* Lower proportional price, as stocked pre-slit.

UPVC-24C... Colors

35 micron UPVC film. Solvent based natural rubber adhesive (white adhesive). High quality, premium grade tape with quiet release, excellent aging properties and reliable performance in hot or cold weather conditions. Printable, heat-shrinkable, hand-tearable, and resistant to most acids, solvents and alkalis. Used as block-out for screen printers and for color coding, splicing, bundling, sealing cans/tins/packets. Recommended for sealing cartons with coated or uncoated surfaces, corrugated cartons with high recycled paper content, and cold temperature applications. Total Thickness: 2.4 mil. Adhesion: 15 oz/in. Tensile: 42 lbs/in. Elongation: 75%. Temperature Resistance: 158°F. 3" neutral core.

9 COLORS AVAILABLE: Black, white, red, orange, yellow, dark blue, light blue, dark green & light green.

6 BOOKBINDING COLORS AVAILABLE: Black, orange, yellow, dark blue, light blue & light green.

Master Jumbos Available.

72 YD (66M)

72 YD (66M)		
1/2"	(12mm)	144
3/4"	(19mm)	96
1"	* (25mm)	72
1.5"	* (38mm)	48
2"	* (48mm)	36
3"	(72mm)	24
4"	(96mm)	18
59"	(1500mm)	LOG

110 YD (100M) RED ONLY

2"	(48mm)	36
----	--------	----

1000 YD (914M) BOOKBINDING TAPE

1.5"	(38mm)	8
------	--------	---

Alternative to Tesa #4104 & #4124; IPG #600; Scapa # 2210; 3M #690 Paklon™; Achem #CS24U & #PV24; Shurtape #PP808.

* Lower proportional price, as stocked pre-slit.

Available in 6" and 12" PRINTER rolls (see page 30 for details).

UPVC-25F... Fluorescent Orange

39 micron UPVC film. Solvent based natural rubber adhesive (white adhesive). Bright, premium grade fluorescent orange tape with quiet release, excellent aging properties and reliable performance in hot or cold weather conditions. Printable, heat-shrinkable, hand-tearable, and resistant to most acids, solvents and alkalis. Used as block-out for screen printers and for color coding, splicing, bundling, sealing cans/tins/packets. Recommended for sealing cartons with coated or uncoated surfaces, corrugated cartons with high recycled paper content, and cold temperature applications. Total Thickness: 2.5 mil. Adhesion: 15 oz/in. Tensile: 42 lbs/in. Elongation: 90%. Temp. Resistance: 158°F. 3" neutral core.

Master Jumbos Available.

72 YD (66M)

72 YD (66M)		
3/8"	(9mm)	192
1/2"	(12mm)	144
3/4"	(19mm)	96
1"	* (25mm)	72
1.5"	* (38mm)	48
2"	* (48mm)	36
3"	(72mm)	24
4"	(96mm)	18
59"	(1500mm)	LOG

* Lower proportional price, as stocked pre-slit.

Available in 6" and 12" PRINTER rolls (see page 30 for details).

UPVC Bag Sealing/Produce Tapes...

UPVC-22BS...

2.2 mil. 32 micron UPVC Film. Solvent Based Natural Rubber Adhesive. Used for produce packaging, can sealing or bundling. Printable. Adhesion: 15 oz/in. Tensile: 42 lbs/in. Elongation: 75%. Temperature Resistance: 176°F. 3" neutral core/carton.

UPVC-24BS...

2.4 mil. 35 micron UPVC Film. Solvent Based Natural Rubber Adhesive. Seals polyethylene and other film bags swiftly and efficiently when used in a bag sealing dispenser. Used for color coding age of perishables. Printable. Adhesion: 15 oz/in. Tensile: 42 lbs/in. Elongation: 75%. Temperature Resistance: 176°F. 3" neutral core/carton.

WIDTH	RLS/CS	CASES		
		1-6	7-11	12+
3/8" (9MM)	x 180 YD (165M)	WHITE, CLEAR OR TAN		
3/8" (9mm)	96			
1/2" (12MM)	x 180 YD (165M)	WHITE ONLY		
1/2" (12mm)	72			

Alternative to Tesa #4204; 3M #690; Cantech #222; Achem #BS22 & #BS24.

3/8" (9MM)	x 180 YD (165M)			
3/8" (9mm)	96			
8 COLORS AVAILABLE:	Black, dark blue, light blue, red, orange, yellow, dark green & light green.			
1/2" (12MM)	x 180 YD (165M)	RED OR DK.GREEN		
1/2" (12mm)	72			
5/8" (15MM)	x 180 YD (165M)	RED ONLY		
5/8" (15mm)	60			

ET-606STK...

Produce tape dispenser/bag sealer with trimmer. For tape up to 12mm wide. Stainless steel. 3" core.

COST EACH	UNITS/CASE	CASE QTY
10		

/case



See page 70 for more bag seal dispensers.

ET-808K...

Produce tape dispenser/bag sealer with trimmer. For tape up to 16mm wide. Wide neck to handle thicker bags. Baked enamel finish. 3" core.

COST EACH	UNITS/CASE	CASE QTY
10		

/case



Prescription/Label Protection Tapes...

LP-16AW... Clear 1.6 mil

1.6 mil (0.041mm). 23 micron Polypropylene Film. **Water Based Acrylic Adhesive**. Prescription, label protection & lamination. High clarity. Adhesion: 19 oz/in. Tensile: 15 lbs/in. Elongation: 140%. Temp. Range: 32°F to 140°F. 3" TalonTape core/carton.

Alternative to 3M #3765; Permacel P-917; American #15T; IPG #261LPT; Central #470, R-2 #150; STA #1201; Shurtape #AP015; Achem #LP16A.

WIDTH	RLS/CS	CASES		
		1-12	13-39	40+
		72 YD (66M)		
4" (100mm)	18			
5" (125mm)	12			
5.25" (133mm)	12			
6" (150mm)	12			
		144 YD (132M)		
4" (100mm)	18			

OPP-20AW... Clear 2.0 mil

Water Based Acrylic Adhesive. See page 20 for specifications.

6"	(150mm)	12	144 YD (132M)
----	---------	----	---------------

LP-20CC... Crystal Clear 2.0 mil

2 mil (0.05mm). 28 micron Polypropylene Film. **Solvent Based Acrylic Adhesive**. Prescription, label protection & lamination. Non-yellowing & UV resistant. Adhesion: 23 oz/in. Tensile: 20 lbs/in. Elongation: 140%. Temperature Range: 32°F to 140°F. Crystal clear to the core. See-through "CRYSTAL CLEAR" imprinted in two (2) colors on 3" core. Neutral carton.

* Lower proportional price, as stocked pre-slit.

Alternative to Shurtape #PP-807; Scapa #1250; 3M #800, #821; Achem #12U; Permacel #J/LAR-910.

1/4" (6mm)	288	72 YD (66M)
3/8" (9mm)	216	
1/2" (12mm)	144	
3/4" * (19mm)	96	
1" * (25mm)	72	
1.5" * (38mm)	48	
1.75" * (44mm)	42	
2" * (50mm)	36	
3" (75mm)	24	
4" (100mm)	18	
5" (125mm)	12	
6" (150mm)	12	
49" (1260mm)	LOG	generic core
49" (1260mm)	54	crate

Office Supply Tapes...

SPP-20HTW-1... Clear Stationery Tape

Stationery tape, polypropylene, 2.0 mil (0.05mm). **Hand-tearable**. Water based acrylic adhesive. Adhesion: 22 oz/in. Tensile: 18 lbs/in. Sub-packed. 1" plastic core.

WIDTH	RLS/CS	CASES		
		1-12	13-47	48+
36 YD (1296") 33M				
1/2"	(12mm)	288		
3/4"	(18mm)	192		

Sub-packs: 1/2"=12 rolls; 3/4"=8 rolls

Alternative to 3M #600; STA #1202; Cantech #208-00.

SPP-20HTW... Clear Stationery Tape

Stationery tape, polypropylene, 2.0 mil (0.05mm). **Hand-tearable (score slit)**. Water based acrylic adhesive. Adhesion: 22 oz/in. Tensile: 18 lbs/in. Temperature Resistance: 176°F. Elongation: 120%. Rolls shrink wrapped in a sleeve and sub-packed. 3" neutral core.

72 YD (2592") 66M		
1/2"	(12mm)	144
3/4"	(18mm)	96
1"	(24mm)	72

Sub-packs: 1/2" = 12 rolls; 3/4" = 8 rolls; 1" = 6 rolls

Alternative to 3M #600; STA #1202; IPG #15T-12; Cantech #208-00.

SPP20RW-B... Clear Stationery Tape

Stationery tape, polypropylene, 2.0 mil (0.05mm). **Razor slit (not hand tearable)**. Best for use in dispensers. Water based acrylic adhesive. Adhesion: 22 oz/in. Tensile: 18 lbs/in. Temperature Resistance: 176°F. Elongation: 120%. Each roll cello-wrapped (pillow packed); no sub-packs. 3" neutral core.

72 YD (2592") 66M		
1/2"	(12mm)	144
3/4"	(18mm)	96
1"	(24mm)	72
1.5"	(36mm)	48

20HT-D... Stationery Tape on Half Dispenser

Retail put-up. 1/2" & 3/4" wide x 800" long OPP stationery tape on a half-sided dispenser. Carded (generic imprint). Water based acrylic adhesive. 6 inner cartons per box. Plastic blade.



SIZE	UNITS/CASE	CASE QTY
1/2"(12.7mm) x 800"	144 rolls	
(6 sub-packs of 24)		/case

3/4"(19.0mm) x 800"	96 rolls	
(6 sub-packs of 16)		/case

INV-20M-1... Invisible Mending Tape

Write-on invisible mending tape, 2.0 mil (25 micron film). **Translucent, frosty-white**. Specially treated matte finish polypropylene film with a solvent based acrylic adhesive. Hand-tearable, non-glare. Adhesion: 19 oz/in. Tensile: 20 lbs/in. Elongation: 140%. 1" plastic core.

36 YD (1296") 33M		
1/2"	(12mm)	288
3/4"	(18mm)	192

Sub-packs: 1/2" = 12 rolls; 3/4" = 8 rolls

Alternative to 3M #810; STA #1204; Cantech #280-00; Achem #32G.

INV-20M... Invisible Mending Tape


Prescription/label protection & overlamination, 2.0 mil (0.05mm) total. **Translucent, frosty-white**. Specially treated matte finish polypropylene film with solvent based acrylic adhesive. Write-on, NON-GLARE for bar code applications, suitable for electronic scanning. Adhesion: 19 oz/in. Tensile: 20 lbs/in. Elongation: 140%. 3" neutral paper core.

72 YD (2592") 66M		
3/8"	(9mm)	192
1/2"	(12mm)	144
3/4"	(18mm)	96
1"	(24mm)	72
1.5"	(38mm)	48
2"	(50mm)	36
3"	(75mm)	24
49"	(1260mm)	LOG
49"	(1260mm)	54

Alternative to 3M #810; STA #1214; Achem #32G, #LM23 & #MT23; Cantech #280-00.

Hook & Loop...

The Velcro® Texacro® Brand pressure sensitive Hook-n-Loop nylon fastener closure system is manufactured with woven nylon yarns. The fasteners have a rubber based adhesive backing and wound with a clear release liner. Can be sewn to fabrics or applied to rigid surfaces. Can be straight-cut or mated and cut. Adhesive Peel Strength: 14.2 oz/in. Fastener Shear Strength: 21.6 lbs/in.



AVAILABLE COLORS (STOCKED):

STRIPS: Black or white

COINS: Black

WIDTH	TYPE	# OF ROLLS		
		1-9	10-19	20+
25 YD (75 FT) STRIPS				
3/4"	Hook T91			
3/4"	Loop T93			
1"	Hook T91			
1"	Loop T93			
2"	Hook T91			
2"	Loop T93			

Specify black or white when ordering.

* 3/4" DIA. COINS (DOTS) 1028/ROLL		
3/4"	Hook 1753	
3/4"	Loop 1753	

*Coins (dots) are stocked in black only.

Other widths & colors available upon request as a special order.

Filament Reinforced Strapping Tapes...

All filament tapes can be custom converted to your needs.


Contact us for a quote on custom widths & lengths.

WIDTH	RLS/CS	CASES		
		1-11	12-29	30+

FIL-810... Uni-directional Filament

3.6 mil **110# Tensile**. Fiberglass reinforced polypropylene with clear rubber based adhesive. Commodity grade strapping tape. Adhesion: 72 oz/in. Elongation: 6.0%. 3" neutral core.

53.5" (1360mm) x approx. 1900M Jumbos Available.



60 YD (55M) 180 FT		
3/8"	(9mm)	96
1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36
1.5"	(36mm)	24
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
53.5"	(1360mm)	LOG
		neutral core

Alternative to Taratape #199CS; IPG #RG-286; Tesa #53317; 3M #8934, #8959; Cantech #179; Shurtape #GS490; Berry Global #704.

FIL-825... Uni-directional Filament

4.3 mil **130# Tensile**. Fiberglass reinforced polypropylene with clear hot melt synthetic rubber adhesive. General purpose filament tape for strapping, bundling and palletizing. Adhesion: 91 oz/in. Elongation: 6%. 3" neutral core.

53.5" (1360mm) x approx. 1500M Jumbos Available.

60 YD (55M) 180 FT		
3/8"	(9mm)	96 or 128
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
12"	(300mm)	4
53.5"	(1360mm)	LOG
		neutral core

Alternative to Taratape #190, #193; IPG #RG-3, #RG-303, #RG-788; Tesa #53318; Shurtape #GS500.

FIL-890... Uni-directional Filament

5.5 mil **200# Tensile**. Fiberglass reinforced polypropylene with clear synthetic rubber based adhesive. Industrial grade filament tape for strapping, bundling and palletizing. Adhesion: 91 oz/in. Elongation: 7%. 3" neutral core.

53.5" (1360mm) x approx. 1500M Jumbos Available.

60 YD (55M) 180 FT		
3/8"	(9mm)	96 or 128
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
12"	(300mm)	4
53.5"	(1360mm)	LOG
		neutral core

Alternative to Taratape #197; IPG #750, #RG-315; Cantech #180; 3M #897; Shurtape #GS501; Tesa #53319.

FIL-930P... Uni-directional Filament

7.5 mil **330# Tensile**. Fiberglass reinforced polyester with an aggressive, high shear resistant clear natural rubber/resin adhesive. Industrial grade filament tape suitable for HIGH DEMAND bundling, strength reinforcing applications, strapping and palletizing. High tensile strength and high adhesion. Adhesion: 40 oz/in. Elongation: 4.5%. 3" neutral core. Meets ASTM D5330, Type II, (replaces PPP-T-97E, Type II).

58.5" (1486mm) x approx. 1550M Jumbos Available.

60 YD (55M) 180 FT		
3/8"	(9mm)	96 or 128
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
12"	(300mm)	4
58.5"	(1486mm)	LOG
		neutral core

Alternative to Tesa #53311, IPG #RG16, Cantech #188-00; Shurtape #GS531; Permaceal #P-167, #P-247; 3M #880NR, #893, #898.

For "L" Clip long length applications, call for pricing & availability.


See page 65 for FILAMENT TAPE DISPENSERS.

Filament Reinforced Strapping Tapes...

FIL-835B/D... Bi-directional Filament

4.7 mil. **155# Tensile in both directions**. Fiberglass reinforced polypropylene with clear synthetic rubber adhesive. High strength, bi-directional filament tape for extremely demanding strapping, bundling and palletizing applications. High tear resistance makes it ideal for tabbing/seaming in metal fabricating industry. Adhesion: 91 oz/in. Elongation: 6%. 3" neutral core.

53.5" (1360mm) x approx. 1800M Jumbos Available.



WIDTH	RLS/CS	CASES		
		1-11	12-29	30+
60 YD (55M) 180 FT				
1/2"	(12mm)	72 or 96		
3/4"	(18mm)	48 or 64		
1"	(24mm)	36 or 48		
1.5"	(36mm)	24 or 32		
2"	(48mm)	24		
3"	(72mm)	16		
4"	(96mm)	12		
6"	(144mm)	8		
7"	(177.8mm)	8		
12"	(300mm)	4		
53.5"	(1360mm)	LOG	neutral core	

Alternative to 3M #8959; IPG #745; Cantech #190; Sicad #FGBD; Tesa #4579.

Tensilized Polypropylene Strapping Tapes...

PP-500... Tensilized Polypropylene

2.8 mil (0.072mm). **97# Tensile**. Synthetic Rubber/Resin Adhesive. Good initial tack and high shear resistance. Properly applied tape shrinks around loads and holds them tight. Impact strength allows give and take without snapping. Used for palletizing & unitizing corrugated and paperboard boxes. Adhesion to Steel: 55 oz/in. Elongation: 35%. 3" core.

4 COLORS AVAILABLE: Black, white, rust & clear.

830mm x 2300M Jumbos Available (black, white & rust).

1360mm x 2000M Jumbos Available (clear only).

WIDTH	RLS/CS	CASES		
		1-9	10-24	25+
60 YD (55M) 180 FT				
3/8"	(9mm)	192		
1/2"	(12mm)	144		
3/4"	(18mm)	96		
1"	(24mm)	72		
1.5"	(36mm)	48		
2"	(48mm)	36		
3"	(72mm)	24		
32.6"	(830mm)	LOG	BLACK, WHITE & RUST	
53.5"	(1360mm)	LOG	CLEAR ONLY	

Alternative to Tesa #4090, #4091, #4224 & #4287; STA #1222 & #RZ-105; IPG #197 & #805; Shurtape #PS-748.

PP-800... Heavy-Duty Tensilized Polypropylene

3.8 mil (0.097mm). **149# Tensile**. Synthetic Rubber Based Adhesive. Good initial tack and high shear resistance. Properly applied tape shrinks around loads and holds them tight. Impact strength allows give and take without snapping. The black backing has excellent UV resistance needed for outdoor use. Economical alternative to filament tape for palletizing, bundling, and unitizing corrugated and paperboard boxes. Adhesion to Steel: 55 oz/in. Elongation: 35%. 3" core.

3 COLORS AVAILABLE: Black, white & clear.

830mm x 2000M Jumbos Available.

60 YD (55M) 180 FT		
3/8"	(9mm)	192
1/2"	(12mm)	144
3/4"	(18mm)	96
1"	(24mm)	72
1.5"	(36mm)	48
2"	(48mm)	36
3"	(72mm)	24
32.6"	(830mm)	LOG

Alternative to Tesa #4288 & #4092 (NOPI); Taratape #200; Shurtape #PS-750; IPG #815.

360 YD (330M) for "L" Clipping available @ proportional cost.

PP-4298... Appliance Tape (non-staining & residue free)

4.5 mil (0.114mm). **149# Tensile**. Natural Rubber Based Adhesive. **Specially designed to be stain and adhesive transfer resistant**. Features extra high tack, high adhesion and chemical resistance; waterproof and non-toxic. Used for closing, holding, and securing appliances, computers, furniture and office equipment; "L" and "C" clipping. Adhesion to Steel: 32 oz/in. Elongation: 30%. 3" core.

2 COLORS AVAILABLE: Blue & ivory.

1270mm x 2000M Jumbos Available.

60 YD (55M) 180 FT		
3/8"	(9mm)	192
1/2"	(12mm)	144
3/4"	(18mm)	96
1"	(24mm)	72
1.5"	(36mm)	48
2"	(48mm)	36
3"	(72mm)	24
50"	(1270mm)	LOG

Alternative to Tesa #4298; American #497; IPG #815.

See page 65 for STRAPPING TAPE DISPENSERS.

Printers' Rolls...

OPP-P... Printers' rolls

BOPP film with **water based acrylic adhesive**. **Surface printing requires corona treatment**. Clear can be printed on the adhesive side (not recommended if there is high ink coverage due to loss of adhesive tack).

For product details, see pages 20, 21 & 23.

OPP-32P

3.2 mil (48u film) CLEAR & WHITE

6" (144mm) x	1000yd (914m)	2
12" (288mm) x	2000yd (1828m)	1

WIDTH LENGTH RLS/CS

OPP-18P

1.8 mil (25u film) TAN ONLY

12" (288mm) x	2000yd (1828m)	1
---------------	----------------	---

OPP-20P

2.0 mil (28u film) CLEAR, TAN, WHITE, BLACK, RED, PINK, ORANGE, GREEN, BLUE & YELLOW

6" (144mm) x	1000yd (914m)	2
12" (288mm) x	2000yd (1828m)	1

OPP-26P

2.6 mil (38u film) CLEAR & TAN

6" (144mm) x	1000yd (914m)	2
6" (150mm) x	1000yd (914m)	2
12" (288mm) x	2000yd (1828m)	1

UPVC-P... Printers' rolls

UPVC film with **solvent based natural rubber adhesive**. Packed 2 rolls per case for 6", and 1 roll per case for 12". Temperature Resistance: 158°F. 3" neutral core.

Physical Properties...

	32/33 micron	35/37 micron	37/39 micron	50 micron
Adhesion (oz/in)	15	15	15	15
Tensile (lbs/in)	42	42	42	42
Elongation (%)	75	75	90	75

Size: 6" (144mm & 150mm) & 12" (288mm & 300mm) x 1083 Yd (990m)

2.2 mil (32/33u film) = **WHITE, TAN & CLEAR**

2.4 mil (35/37u film) = **BLACK, LIGHT BLUE, DARK BLUE, RED, LIGHT GREEN, DARK GREEN, YELLOW, ORANGE & WHITE/WHITE**

2.5 mil (37/39u film) = **FLUORESCENT ORANGE**

2.8 mil (50u film) = **WHITE 6" x 660M (720 yd)**

Also available in 2" & 3" wide rolls and Master Jumbos.


Stretch Film...

TYPE	COLOR	GAUGE	WIDTH x LENGTH	RLS/CS
SBW-80	Stretch Banding	Clear	80 Gauge 5" x 1000'	12
SFW-80EH	Hand Wrap w/ Extended Handles	Clear	80 Gauge 20" x 1000'	4
SFW-80	Hand Wrap	Clear	80 Gauge 15" x 1500' 18" x 1500'	4
SFW-100	Hand Wrap	Clear	100 Gauge 15" x 1000' 18" x 1000'	4
SFW-120	Hand Wrap	Clear	120 Gauge 15" x 1000' 18" x 1000'	4
SFW-100B	Pilferage Deterrent Hand Wrap	Opaque Black	100 Gauge 15" x 1000'	4
MSW-75	Cast Machine Wrap	Clear	75 Gauge 20" x 5000'	1

Due to the constant fluctuation in pricing, please call for current costs.



See Page 68 for Hand Wrap & Stretch Film Dispensers



Magnetic Tapes...

These magnetic tapes are comprised of a **MULTIPOLE ONE FACE FLEXIBLE MAGNET** (composite of strontium and/or barium ferrite particles oriented with a thermoplastic polymer matrix). These permanent magnets remain magnetized indefinitely if not subjected to a demagnetizing force. Magnetic Tape orders are **NON-RETURNABLE** (suggest sampling for approval). Maximum width: 3".

Note...Wider rolls, strips and die cuts are also available. May be **custom** made for your specific applications: Precut or prescored; die-cut into any shape; with or without adhesive; different magnetizing forces and pole arrangements based on product and strength required; in thicknesses from 0.020" to 0.120".



SOLD BY SUB-PACK OR FULL CASE QUANTITIES ONLY.

MAGNETIC TAPES with INDOOR ADHESIVE

3.4 mil double coated polyester tape with an aggressive rubber based pressure sensitive adhesive laminated to the magnet and supplied on a semi-bleached kraft liner. Indoor adhesive was designed for general purpose bonding applications to foams, felts, cloths, primed wood, paper, metal, plastics and most low or un-plasticized substrates. It has an excellent balance of economy versus performance. The polyester carrier provides dimensional stability and superior die cutting properties. Quick Tack: 12.5 lbs/in. Peel Adhesion: 9.5 lbs/in. Application Temperature: Minimum 50°F. Operating Temperature Range: 0°F to 150°F.

MAG03-I...

1/32" (0.030", 0.762mm) thick with Indoor Adhesive

WIDTH x LENGTH	SUB-PACK		FULL CASE	
	RLS/SP	\$/ROLL	RLS/CS	\$/ROLL
1/2" x 200 ft	2		6	
3/4" x 200 ft	2		4	
1" x 200 ft	2		3	
2" x 200 ft		1		
3" x 200 ft		1		

MAG06-I...

1/16" (0.060", 1.524mm) thick with Indoor Adhesive

WIDTH x LENGTH	SUB-PACK		FULL CASE	
	RLS/SP	\$/ROLL	RLS/CS	\$/ROLL
1/2" x 100 ft	3		6	
3/4" x 100 ft	3		4	
1" x 100 ft	2		3	
2" x 100 ft		1		
3" x 100 ft		1		

MAGNETIC TAPES with INDOOR/OUTDOOR ADHESIVE

5.2 mil double coated polyester tape with a high performance acrylic based pressure sensitive adhesive laminated to the magnet and supplied on a semi-bleached kraft liner. Indoor/Outdoor Adhesive is for bonding applications where outstanding adhesion, high shear and good solvent resistance are required. The acrylic adhesive offers good clarity and has excellent resistance to UV light exposure. The polyester carrier provides dimensional stability and superior die cutting properties. Quick Tack: 8 lbs/in. Peel Adhesion: 10 lbs/in. Application Temperature: Minimum 40°F. Temperature Range: 0°F to 150°F.

MAG03-I/O... 1/32" (0.030", 0.762mm) Thick

WIDTH x LENGTH	SUB-PACK		FULL CASE	
	RLS/SP	\$/ROLL	RLS/CS	\$/ROLL
1/2" x 200 ft	2		6	
3/4" x 200 ft	2		4	
1" x 200 ft	1		3	
2" x 200 ft		1		
3" x 200 ft		1		

MAG06-I/O... 1/16" (0.060", 1.524mm) Thick

WIDTH x LENGTH	SUB-PACK		FULL CASE	
	RLS/SP	\$/ROLL	RLS/CS	\$/ROLL
1/2" x 100 ft	3		6	
3/4" x 100 ft	2		4	
1" x 100 ft	2		3	
2" x 100 ft		1		
3" x 100 ft		1		

MAGNETIC TAPES with WRITEABLE WHITE SURFACE

30 mil magnet with a writeable white vinyl surface (no adhesive). Applications: Automobile Signs, Marketing Displays / Premiums, Business Cards, Warehouse / Barcode Labels, Store / Retail Shelf Labels, Schedule/Planning Boards, and Control Charts.

MAG03-WO... 1/32" Thick, Write-on Surface

Porous, screen-printable matte white vinyl surface. Writeable with a permanent marker or a water-soluble marker (wipe off with a damp cloth) for non-permanent applications. Note: Wiping off will gray surface over time.

WIDTH x LENGTH	SUB-PACK		FULL CASE	
	RLS/SP	\$/ROLL	RLS/CS	\$/ROLL
1/2" x 100 ft	4		6	
3/4" x 100 ft	3		4	
1" x 100 ft	2		3	
2" x 100 ft		1		
3" x 100 ft		1		

MAG03-WOE... 1/32" Thick, Write-on/Wipe-off

Non-porous, smooth, shiny white vinyl surface. Writeable with a dry erase marker and just wipe off.

WIDTH x LENGTH	SUB-PACK		FULL CASE	
	RLS/SP	\$/ROLL	RLS/CS	\$/ROLL
1/2" x 100 ft	3		6	
3/4" x 100 ft	2		4	
1" x 100 ft	2		3	
2" x 100 ft		1		
3" x 100 ft		1		

Solid Reflective Tapes...

REF-5... Engineering Grade (5-year Warranty)

4.5 mil (0.113mm). Polyester reflective tape with acrylic adhesive, wound on a 5.0 mil polycoated Kraft paper release liner. Consists of highly reflective powder (glass beads) that reflects light back to the source. Primarily used to ensure safety in work zone areas, advertisements and traffic signage. Product is hand-tearable, may be screen-printed and die-cut. 3" neutral paper core.

5 COLORS: Silver (white), black, red, green & blue.

Physical Properties...

Peel Adhesion:	60 oz/in
Tensile Strength:	26 lbs/in
Application Temperature:	65°F (18°C)
Temperature Resistance:	-4°F to 140°F (-20°C to 60°C)

*** MINIMUM 3 INCHES PER ITEM/COLOR.**

CLOSEOUT

WIDTH	RLS/CS	* ROLL	CASE
10 YD (30 FT)			
3/8" (9.5mm)	128		
1/2" (12.5mm)	96		
3/4" (19mm)	64		
1" (25mm)	48		
1.5" (38mm)	32		
2" (50mm)	24		
3" (75mm)	16		
4" (100mm)	12		
6" (150mm)	8		
48" (1200mm)	LOG		

WIDTH	RLS/CS	* ROLL	CASE
50 YD (150 FT)			
1/2" (12.5mm)	96		
3/4" (19mm)	64		
1" (25mm)	48		
1.5" (38mm)	32		
2" (50mm)	24		
3" (75mm)	16		
4" (100mm)	12		
6" (150mm)	8		
48" (1200mm)	LOG		

REF-7... Engineering Grade (7-year Warranty)

6.0 mil (0.15mm). Enclosed lens retroreflective urethane film coated with a permanent acrylic adhesive. 6.8 mil white polyethylene coated paper release liner. Primarily designed for permanent & temporary traffic signage. Used for work zone devices and non-critical signs where retroreflection is necessary. Exceeds requirements of ASTM D4956 Type 1 and EN-12899 RA1. Uniform daytime and nighttime visual appearance. Application surface should be flat (not recommended for unpainted stainless steel surface). Product may be screen printed, thermal transfer printed, thermal die-cut, flat bed sign-cut, drum roller sign-cut, or steel rule sign-cut. 3" neutral paper core.

6 COLORS: Silver (white), yellow, red, orange, green & blue.

Physical Properties...

Peel Adhesion:	43 oz/in
Application Temperature:	65°F (18°C)
Temperature Resistance:	-10°F to 150°F (-23°C to 65°C)

*** MINIMUM 3 INCHES PER ITEM/COLOR.**

WIDTH	RLS/CS	* ROLL	CASE
10 YD (30 FT)			
3/8" (9.5mm)	192		
1/2" (12.5mm)	144		
3/4" (19mm)	96		
1" (25mm)	72		
1.5" (38mm)	48		
2" (50mm)	36		
3" (75mm)	24		
4" (100mm)	18		
6" (150mm)	12		
48" (1200mm)	LOG		

WIDTH	RLS/CS	* ROLL	CASE
50 YD (150 FT)			
1/2" (12.5mm)	72		
3/4" (19mm)	48		
1" (25mm)	24		
1.5" (38mm)	24		
2" (50mm)	12		
3" (75mm)	12		
4" (100mm)	8		
6" (150mm)	6		
48" (1200mm)	LOG		

WIDTH	RLS/CS	* ROLL	CASE
250 YD (750 FT)			
48" (1200mm)	LOG		

Alternative to Avery T-1500 Series, Nippon/Carbide 8100 Series, 3M 3200 Series.

Striped Reflective Tapes...

REF-3S... Commercial Grade (3-year Warranty)

3.7 mil (0.095mm). Polyester/vinyl **diagonal striped** reflective tape with acrylic adhesive, wound on a 5.0 mil yellow polycoated Kraft paper release liner. 3" neutral paper core.

3 STRIPED COLORS: Red/orange, blue/white & green/white.

Physical Properties...

Peel Adhesion:	50 oz/in
Tensile Strength:	10 lbs/in
Application Temperature:	Above 41°F
Temperature Resistance:	14°F to 176°F

*** MINIMUM 3 INCHES PER ITEM/COLOR.**

CLOSEOUT

WIDTH	RLS/CS	* ROLL	CASE
10 YD (30 FT)			
1" (25mm)	48		
1.5" (38mm)	32		
2" (50mm)	24		
3" (75mm)	16		
4" (100mm)	12		
6" (150mm)	8		
48" (1219mm)	LOG		

WIDTH	RLS/CS	* ROLL	CASE
50 YD (150 FT)			
1" (25mm)	48		
1.5" (38mm)	32		
2" (50mm)	24		
3" (75mm)	16		
4" (100mm)	12		
6" (150mm)	8		
48" (1219mm)	LOG		

Striped Reflective Tapes...

REF-5S... Engineering Grade (5-year Warranty)

6.8 mil (0.175mm). Polyester/vinyl **diagonal striped** reflective tape with acrylic adhesive, wound on a 6.8 mil white polycoated Kraft paper release liner. Meets Federal specifications LS-300C (Reflectivity 1, Class 1) and FP-85 (Type II). 3" neutral paper core.

2 STRIPED COLORS: Black/yellow & red/white.

Physical Properties...

Service Life	5-7 years
180° Peel Adhesion:	70 oz/in
Tensile Strength:	11 lbs/in
Application Temperature:	Above 32°F
Temperature Resistance:	-70°F to 160°F
72 hrs @ -70°F:	No effect
72 hrs @ 160°F:	Max 0.012" shrinkage from edge


WIDTH	RLS/CS	* ROLL	CASE
		50 YD (150 FT)	
3/4"	(19mm)	48	
1"	(25mm)	36	
1.5"	(38mm)	24	
2"	(50mm)	18	
3"	(75mm)	12	
4"	(100mm)	12	
6"	(150mm)	8	
48"	**(1219mm)	LOG	

* **MINIMUM 3 INCHES PER COLOR.**

** **NEW wider log width.**

Note: Black/yellow diagonal stripes are recommended for long term outdoor use (more resistant to fading).

(formerly REF-S)



Oralite® (Reflexite®) Retroreflective Tape...

REF-DOT...

Oralite® (formerly Reflexite®) Conspicuity material is composed of cube corner (microprism) retroreflective elements integrally bonded to a flexible, smooth-surfaced, tough & weather resistant UV stabilized polymeric film. The prism surfaces are coated with a vacuum deposition of aluminum to provide a mirror surface to the prism facets. The resulting tape is not more than 0.008" thick and comes with an aggressive high-tack pressure-sensitive adhesive.

Applications...

Oralite® Visibly Better™ Retroreflective conspicuity material is a tough weather & solvent resistant product designed for rugged outdoor use on the sides and rear of trucks, trailers, automobiles, and emergency vehicles to enhance safety on the roadway by improving their visibility. NOTE: NHTSA conspicuity regulations (effective 12/1/93) mandate that all new trailers (10,000 lbs GVW and 80" wide or larger) must be reflectorized with alternating red & white retroreflective sheeting on the sides, bottom of rear door, and ICC bar; and two pieces of white sheeting on the upper corners of the rear. Application Temperature: minimum 50°F.

Features/Benefits...

- Durability >>> **5-year or 10-year warranty** <<< Withstands brushing off of dirt/grime, and high pressure washing. Polyester based film resists cracking & lifting. Will retain reflectivity even after impact against loading dock or abrasion by chains.
- Unique, single-ply construction ensures impact & abrasion resistance and easy application.
- 0.008" thickness resists dirt accumulation typical of competitor's thicker (0.025"), open-cell construction. Material is extremely thin so there are no raised edges that can catch and tear.
- Unlike competing conspicuity materials, this conspicuity material features 100% adhesion, with no grid lines that can fill with water and cause premature adhesive failure.
- Super-high brightness & wide angularity: 10-year pattern. Typically 1000 candlepower with tremendous long sight distance performance; reflects at all applicable angles on the roadway.

Specification Compliance...

ASTM D4956

NHTSA 49 CFR, Part 571

ASTM D523

DOT-C2 (applicable to 2" only)

ASTM E810

FMVSS 108

LS300C

FP92


When ordering REF-DOT Conspicuity Tapes **SPECIFY:**

- Durability: 5-year OR 10-year warranty (see pricing below)
- Red/White Color Pattern: 6"/6" OR 11" (red)/7" (white)
- c) Type*: Solid OR Kiss-Cut roll


* Note: 10-year is only stocked in solid rolls; kiss-cut is available as a special, non-cancelable order; must take full web width (30").

WIDTH	RLS/CS	50YD (150 FT)		5-YEAR		10-YEAR	
		ROLL	CASE	ROLL	CASE	ROLL	CASE
1"	(25mm)	36					
1.5"	(38mm)	24					
2"	(50mm)	18					
3"	(75mm)	12					
4"	(100mm)	12					
6"	(150mm)	8					
30"	(762mm)	LOG					

REF-5DOT
5-Year Pattern



REF-10DOT
10-Year Pattern



Oralite® Conspicuity Daybright® Tape...

REF-5DB... Solid Colors (5-year Warranty)

Oralite® (formerly Reflexite®) Daybright® is a high brightness, weather resistant reflective material. It is designed to provide superior visibility and conspicuity to oncoming motorists which results in improved safety and image.

Daybright® features include Oralite's proprietary microprism technology, long distance sight detection, and thin, flexible construction which is easy to apply. The material has an aggressive high-tack pressure sensitive adhesive. The material is flexible and strong once applied; excellent impact, shrink, and solvent resistance.

6 COLORS: White, green, red, blue, orange & gold.

REF-10DB... Solid Colors (10-year Warranty)



10-Year Pattern

COLORS: Gold and blue.

CLOSEOUT

WIDTH	RLS/CS	* ROLL	CASE
-------	--------	--------	------

50 YD (150 FT)

1/2"	(12.5mm)	72	
3/4"	(19.0mm)	48	
1"	(25mm)	36	
1.5"	(38mm)	24	
2"	(50mm)	18	
3"	(75mm)	12	
4"	(100mm)	12	
6"	(150mm)	8	
30"	(762mm)	LOG	



5-Year Pattern

WIDTH	ROLL
-------	------

50 YD (150 FT)

2"	(50mm)	
----	--------	--

Note:

Available in additional colors and widths for special orders. Please call for pricing and minimums.

Oralite® Fluorescent Reflective Tape...

REF-DBF... Solid Fluorescent Colors (5-year Warranty)

Oralite® (formerly Reflexite®) Fluorescent Conformable Graphic Sheeting is a tough weather and solvent resistant product designed for rugged outdoor use. The product is die cuttable, plotter cuttable, easy to apply to smooth painted or unpainted vehicle surfaces, and highly conformable to shapes and curves. Used for increased visibility on vehicles.

Composed of cube corner (microprism) retroreflective elements integrally bonded to a flexible, smooth-surfaced, tough weather resistant, UV stabilized polymeric film. The prism surfaces are coated with a vacuum deposition of aluminum to provide a mirror surface to the prism facets. The material is flexible and strong once applied; excellent impact, shrink, and solvent resistance. Specially formulated to adhere to a variety of surfaces including: painted steel, clear coat lacquer, and aluminum. The adhesive is protected by a release liner that shall be removed by peeling, without soaking in water or solvents.

2 COLORS: Fluorescent lime-yellow & fluorescent orange.


WIDTH	RLS/CS	ROLL	CASE
-------	--------	------	------

50 YD (150 FT)

1"	(25mm)	20	
2"	(50mm)	10	
30"	(762mm)	LOG	

Note:

Available in additional colors and widths for special orders. Please call for pricing and minimums.



5-Year Pattern

Photoluminescent Tapes...


PGD-6... Safety Grade (6 Hours)

PGD-24... Ultra Premium (24 Hours)

11 mil (exclusive of liner). Flexible, photoluminescent polyester film coated with a permanent solvent based acrylic adhesive and backed with a 60# (4.5 mil) polycoated Kraft paper liner. The photoluminescent pigments absorb and store energy from normal, ambient light. In sudden darkness, the tape is immediately visible. These non-electric safety system tapes easily and inexpensively affix to walls, handrails, stairways, columns, doorframes and baseboards. Tape will glow in total darkness after exposure to artificial or natural light (fully charged within 30 minutes). **Glowes brightest the first 30 minutes after activation has ceased and remains clearly visible to the night-adapted eye in a completely dark room for approximately 6-8 hours (PGD-6) or 20-24 hours (PGD-24); see *Glow Properties.** Excellent UV stability; no significant degradation when used outdoors. Screen, flexo, thermo transfer printable. Can be die-cut and kiss-cut using steel rule dies. **Adhesion to SST: 60 oz/in** (24 hr dwell). Application Temp: $\geq 50^{\circ}\text{F}$. 3" paper core. **COLOR: Light Green.**

Applications... Used for identifying critical equipment controls, light switch covers, exit and directional signage (especially for escape routes and stairways) in hotels, hospitals, schools, public facilities, office buildings, manufacturing plants, and wherever people need a safe, reliable, high and low-level egress pathway in case of an emergency, such as sudden power outages or the spread of smoke. Tape clearly labels safety equipment and provides a safe, illuminated path through stairwells, halls, rooms, and other potentially hazardous areas. This safety system is simple and inexpensive to install (position, peel off backing, and adhere) and requires virtually no maintenance. Also used for labels, decals, novelties, sporting goods, trims, special effects, etc.

*All PGD Rolls: MINIMUM 6 INCHES PER ITEM and LENGTH.



WIDTH RLS/CS * ROLL CASE

PGD-6 10 YD (30 FT)

1/2"	(12.5mm)	144
3/4"	(19mm)	96
1"	(25mm)	72
1.5"	(38mm)	48
2"	(50mm)	36
3"	(75mm)	24
4"	(100mm)	18
6"	(150mm)	12
54"	(1372mm)	LOG

PGD-6 50 YD (150 FT)

1/2"	(12.5mm)	72
3/4"	(19mm)	48
1"	(25mm)	36
1.5"	(38mm)	24
2"	(50mm)	18
3"	(75mm)	16
4"	(100mm)	12
54"	(1372mm)	LOG

Alternative to Jessup #7520.

PGD-24 50 YD (150 FT)

1/2"	(12.5mm)	72
3/4"	(19mm)	48
1"	(25mm)	36
1.5"	(38mm)	24
2"	(50mm)	18
3"	(75mm)	12
4"	(100mm)	8
54"	(1372mm)	LOG

Alternative to Jessup #7550.

“GLOW IN THE DARK” TAPES

*Glow Properties (DIN 67510 Xe Lamp; 1000 Lx/5 min): Timespan necessary for afterglow brightness to diminish to 0.3 mcd/m² - 100X human eye perception. Duration may vary (+/-) as several factors (i.e. type/proximity/angle/wattage of light source, conditions of exposure, etc.) may impact glowing lifespan.

Non-Skid Luminescent Tapes...

“Sure-Step” non-skid, GLOW-in-the-DARK tapes provide a high traction, anti-slip, waterproof surface to help prevent slips/falls and adds additional safety by emitting a non-electrical illuminated path for up to 90 minutes (see *Glow Properties) after power outages. Aggressive acrylic adhesive bonds to a variety of materials and conforms to irregular surfaces. For exit and directional signage (especially for escape routes and stairways), walkways and ramps in machine shops, work areas, stairwells, and other potentially hazardous areas. **Adhesion to SST: ≥ 53 oz/in.** White paper liner. 3" neutral core.

NST-20GS... BLACK WITH GLOW INSERT

39 mil (exclusive of liner). 60 grit black aluminum oxide with a 10mm GLOW-in-the-DARK insert/stripe in the center.



* Available by the roll @ 1-5 case price +10%.

WIDTH RLS/CS * CASES (COST PER ROLL)
1-5 6-11 12+

20 YD (60 FT) BLACK WITH GLOW INSERT

2"	(50mm)	6
----	--------	---

NST-20GL... LUMINOUS

41 mil (exclusive of liner). Luminescent, GLOW-in-the-DARK backing impregnated with 60 grit aluminum oxide.

* Full case quantities ONLY.

20 YD (60 FT) LUMINOUS

1"	(25mm)	12
2"	(50mm)	6
3"	(75mm)	4
4"	(100mm)	3
6"	(150mm)	2
12"	(300mm)	1

Aluminum Foil Tapes (with liner)...

AF-20A-B...Matte Black, Acrylic Adhesive

Non-reflective, Matte Black lacquered 2.0 mil aluminum foil coated with an aggressive acrylic pressure sensitive adhesive; removable white paper release liner. Malleable foil conforms to irregular & curved surfaces. Tape performs well at low and high temperatures (flame retardant). Used to block lighting spills/leakages on heat generating equipment (projectors, light cans, bandoors, etc). Matte black finish does not reflect light. Total Tape Thickness: 3.6 mil. Elongation 3%. Peel Adhesion: 55 oz/in. Temperature Range: -22°F to 302°F. 3" neutral core.

WIDTH	RLS/CS	ROLL	CASE
27 YD (25M) BLACK			
2"	(50mm)	24	

AF-12R... Rubber Adhesive

1.2 mil dead soft aluminum foil, coated with an aggressive synthetic rubber adhesive; removable paper release liner. Economical aluminum foil tape for moderate demand applications. Malleable foil conforms well to irregular surfaces. Total Tape Thickness (w/o liner): 2.8 mil. Peel Adhesion: 91 oz/in. Tensile: 10.3 lb/in. Elongation: 3%. Temperature Range: -4°F to 176°F. 3" neutral core.

47.2" (1200mm) x 1200M (1312yd) Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+
50 YD (150 FT)				
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
2.5"	(63mm)	20		
3"	(72mm)	16		
4"	(96mm)	12		
6"	(144mm)	8		
47.2"	(1200mm)	LOG		

Alternative to Nashua #331; Ideal #488E.

AF-12A... Acrylic Adhesive

1.2 mil dead soft aluminum foil, coated with a solvent based acrylic adhesive; removable paper release liner. Economical aluminum foil tape for moderate demand applications. Malleable foil conforms well to irregular surfaces. Used for vapor barrier protection, waterproof sealing, heat reflection & dissipation, masking in paint stripping and electroplating. Total Tape Thickness (w/o liner): 2.8 mil. Peel Adhesion: 73 oz/in. Tensile: 10.3 lb/in. Elongation: 3%. Temperature Range: -22°F to 248°F. 3" neutral core.

47.2" (1200mm) x 1200M (1312yd) Jumbos Available.

50 YD (150 FT)		
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
2.5"	(63mm)	20
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
47.2"	(1200mm)	LOG

Alternative to Polyken #332

AF-16R... Rubber Adhesive

1.6 mil dead soft high-grade aluminum foil coated with an aggressive synthetic rubber adhesive; removable paper release liner. Malleable foil conforms well to irregular surfaces. Used to maintain the integrity of the vapor barrier, waterproof sealing, heat reflection & dissipation. Used in refrigeration industry, metal patching. Total Tape Thickness (w/o liner): 3.2 mil. Peel Adhesion: 91 oz/in. Tensile: 12.6 lbs/in. Elongation: 3%. Temperature Range: -22°F to 176°F. 3" neutral core.

47.2" (1200mm) x 1000M (1094yd) Jumbos Available.

50 YD (150 FT)		
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
2.5"	(63mm)	20
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
47.2"	(1200mm)	LOG

Alternative to Ideal #4558

AF-16A... Acrylic Adhesive

1.6 mil dead soft high-grade aluminum foil coated with an aggressive solvent based acrylic adhesive; removable paper release liner. Malleable foil conforms well to irregular and curved surfaces; and will perform well at both low and high temperatures. Used for vapor barrier protection, waterproof sealing, heat reflection & dissipation, masking in paint stripping and electroplating. Total Tape Thickness (w/o liner): 3.2 mil. Peel Adhesion: 73 oz/in. Tensile: 12.6 lbs/in. Elongation: 3%. Temperature Range: -22°F to 248°F. 3" neutral core.

47.2" (1200mm) x 1000M (1094yd) Jumbos Available.

50 YD (150 FT)		
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
2.5"	(63mm)	20
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
47.2"	(1200mm)	LOG

Other roll widths available upon request.

Aluminum Foil Tapes (with liner)...

AF-20R... Rubber Adhesive

2 mil dead soft premium grade aluminum foil coated with an extremely aggressive synthetic rubber adhesive that provides a tight positive grab when smoothed down on work surfaces; removable paper liner. Used in fiberglass duct board systems on seams & joints to maintain the integrity of the vapor barrier. Can also be used on FSK systems. Malleable foil conforms well to irregular & curved surfaces. Total Tape Thickness (w/o liner): 3.6 mil. Peel Adhesion: 91 oz/in. Tensile: 17.1 lbs/in. Elongation: 3.5%. Temperature Range: -4°F to 176°F. 3" neutral core.

47.2" (1200mm) x 1000M (1093yd) Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+
50 YD (150 FT)				
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
2.5"	(63mm)	20		
3"	(72mm)	16		
4"	(96mm)	12		
6"	(144mm)	8		
12"	(300mm)	4		
47.2"	(1200mm)	LOG		

Alternative to Ideal #488; Venture #3530; Shurtape #AF973; Fasson #0802; Polyken #337; Nashua #332; Tesa #53900.

AF-20A... Acrylic Adhesive

2 mil dead soft high tensile aluminum foil coated with an aggressive solvent based acrylic adhesive; removable paper liner. Malleable foil conforms well to irregular and curved surfaces; and will perform well at both low and elevated temperatures. Can be applied at low temps. Used for vapor barrier protection, waterproof sealing, heat reflection & dissipation, masking in paint stripping and electroplating. Total Tape Thickness (w/o liner): 3.6 mil. Peel Adhesion: 73 oz/in. Tensile: 17.1 lbs/in. Elongation: 3.5%. Temperature Range: -22°F to 248°F. 3" neutral core.

47.2" (1200mm) x 1000M (1093yd) Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+
50 YD (150 FT)				
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
2.5"	(63mm)	20		
3"	(72mm)	16		
4"	(96mm)	12		
6"	(144mm)	8		
47.2"	(1200mm)	LOG		

Alternative to Venture #3520CW; Nashua #330; IPG #AC64; Shurtape #AF100; Electro Tape #510; 3M #33805.

AF-30A... High performance, Acrylic Adhesive

3 mil high strength dead soft aluminum foil coated with an aggressive solvent based acrylic adhesive easy removable paper liner. Malleable foil conforms well to irregular and curved surfaces. Excellent performance at both low and high temperatures. Can be applied at low temps. Used for waterproof sealing, vapor barrier and air leakage protection, heat reflection/dissipation, masking in paint stripping and electroplating. Excellent for die-cutting. Total Tape Thickness (w/o liner): 5.0 mil. Peel Adhesion: 73 oz/in. Elongation: 5%. Temperature Range: -22°F to 302°F. 3" neutral core.

47.2" (1200mm) x 1000M (1093yd) Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-10	11-23	24+
60 YD (180 FT)				
1/2"	(12mm)	48		
3/4"	(18mm)	32		
1"	(24mm)	24		
1.5"	(36mm)	16		
2"	(48mm)	12		
2.5"	(63mm)	10		
3"	(72mm)	8		
4"	(96mm)	6		
6"	(144mm)	4		
12"	(300mm)	2		
47.2"	(1200mm)	LOG		

Alternative to 3M #427, #3363 & #3367; Permacel #P14; Ideal #489; Scapa #P178; Arclad #S-5795; St. Gobain #A662; Polyken #347.

AF-50A... High performance, Acrylic Adhesive

5 mil high strength aluminum foil backing, combined with a high performance solvent acrylic adhesive, protected by an easy release silicone release paper. Perfect for joining and sealing Foil-Scrim-Kraft facing laminate fiberglass blanket/duct board joints and seams. May also be used for industrial uses. Total Tape Thickness (w/o liner): 7.0 mil. Peel Adhesion: 72 oz/in. Rolling Tack (11mm ball): <6.0 in. Temperature Range: -40°F to 300°F. 3" neutral core.

47.2" (1200mm) x 800M (875yd) Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-10	11-23	24+
60 YD (180 FT)				
1/2"	(12mm)	48		
3/4"	(18mm)	32		
1"	(24mm)	24		
1.5"	(36mm)	16		
2"	(48mm)	12		
2.5"	(63mm)	10		
3"	(72mm)	8		
4"	(96mm)	6		
6"	(144mm)	4		
12"	(300mm)	2		
47.2"	(1200mm)	LOG		

Alternative to 3M #3338; Venture #1516CW.

Aluminum Foil Tapes (without liner)...

AF-20SW... Self Wound, Acrylic Adhesive

3.6 mil total. 2 mil self wound dead soft malleable aluminum foil coated with an aggressive acrylic adhesive system to create a superior bond. Malleable foil conforms well to irregular surfaces. Excellent harness wrap tape. Designed for non-critical applications such as sealing out dust and moisture, masking and duct sealing. Can be used for heat reflection in the appliance industry and as a mask for electroplating. This linerless product saves time and labor in stripping of release liner and produces less waste. Adhesion to Steel: 40 oz/in. Tensile: 26 lbs/in. Elongation: 4%. Temperature Range: -40°F to 302°F. 3" neutral core.

AF-30SW... Self Wound, Acrylic Adhesive

4.8 mil total. 3 mil high strength self wound dead soft aluminum foil coated with an aggressive acrylic adhesive system to create a superior bond. Designed to stick firmly to its own backing. Malleable foil conforms well to irregular surfaces. **Premier product for masking in paint stripping and electroplating.** Used for waterproofing, vapor barrier and air leakage protection, metal patching and sound dampening, as a sealing system in refrigerated appliances and microwave ovens. High reflectivity assures effective heat, light interference, and electrical insulation shielding. Protects outdoor cable splices. Can be applied at low temperatures. Adhesion to Steel: 40 oz/in. Tensile: 36 lbs/in. Elongation: 5%. Temperature Range: -58°F to 302°F. 3" core.

Aluminum Foil/Scrim/Kraft Tape...

AF-FSK-A... with Acrylic Adhesive

AF-FSK-R... with Rubber Adhesive

4.8 mil 3-way dead soft aluminum foil / fiberglass scrim / paper backing coated with an aggressive 2 mil adhesive and wound with a 3.2 mil removable paper release liner. Malleable foil conforms well to irregular and curved surfaces to maximize adhesive contact and provide quick, positive grab to the insulation surface. Used as a closure system for fiberglass and mineral wool insulation systems that are faced with foil, to seal seams and joints on aluminum faced fiberglass duct board, and to provide a vapor barrier that assures the integrity of the system. 3" neutral core.

Physical Properties:

	AF-FSK-A	AF-FSK-R
Adhesive Type	Solvent Based Acrylic	Synthetic Rubber Resin
Tape Thickness (w/o liner)	6.8 mil	6.8 mil
Adhesion to Steel	73 oz/in	91 oz/in
Rolling Ball Tack	6 in	8 in
Tensile Strength	27.3 lbs/in	27.3 lbs/in
Temperature Range	-22°F to 176°F	-4°F to 176°F
Application Temperature	50°F to 105°F	50°F to 105°F

47.25"(1200mm) x 730M Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+
60 YD (180 FT)				
3/4"	(19mm)	48		
1"	(25mm)	36		
1.5"	* (38mm)	24		
2"	* (50mm)	24		

Alternative to 3M #4380; Lamart #215; Venture #807-2 & #2520CW.

*CLOSEOUT WIDTH (lower proportional price).

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+
60 YD (180 FT)				
1/2"	(12mm)	72		
3/4"	* (19mm)	48		
1"	(25mm)	36		
1.5"	* (38mm)	24		
2"	(50mm)	24		
3"	(75mm)	12		
4"	* (100mm)	8		


Alternative to 3M #425 & #34383; Permacel #P-14; Lamart #213M; Polyken #345; Shurtape #AF-75; Scapa #T3612; Ideal #489.

*CLOSEOUT WIDTH (lower proportional price).

Specify AF-FSK-A or AF-FSK-R when ordering.

WIDTH	RLS/CS	CASES		
		1-5	6-11	12+
50 YD (150 FT)				
2"	(48mm)	24		
3"	(72mm)	16		
4"	(96mm)	12		
6"	(144mm)	8		
47.25"	(1200mm)	LOG		

Alternative to Nashua #338FSK.



Copper Foil Tapes...

CFL-5A... with Acrylic Adhesive

CFL-5CA... with CONDUCTIVE Acrylic Adhesive

Special electrograde, zero temper, high tensile copper foil tape. Provides excellent solderability. Malleable copper foil conforms well to irregular contours. Its aggressive acrylic adhesive system creates a superior bond. Used for RFI/EMI shielding applications in the electrical/electronics industry. Annealed and non-tarnishing. Meets Class F & UL 510 specifications. **CFL-5CA** is coated with an acrylic adhesive which is uniformly dispersed with conductive spheres to provide a very low rate of electrical resistance through the tape. Electrical resistance: 0.003 Ohms/in². 3" plastic core.

Typical Applications...

CFL-5A - EMI/RFI shielding of small electromagnetic components (i.e. transformer/reactor coils) and cable splices; repairing, modifying & prototype designing wiring boards, supplementary shielding of joints/seams; flat conductor assemblies.

CFL-5CA - Cable wrapping to provide EMI/RFI shielding, seaming of EMI/RFI shielded rooms for electrical continuity, static charge draining, surface contact to non-solderable materials (e.g. aluminum or plastics).

Physical Properties...

Adhesive	Acrylic
Backing	1.4 mil Copper Foil
Tape Thickness (w/o liner)	3.0 mil
Peel Adhesion 180° SST	50 oz/in
Tensile Strength	37 lbs/in
Elongation	6%
Temperature Range	-40°F to 248°F
Temp Resistance (short term)	up to 356°F

CFL-5A

Adhesive	Acrylic
Backing	1.4 mil Copper Foil
Tape Thickness (w/o liner)	3.0 mil
Peel Adhesion 180° SST	50 oz/in
Tensile Strength	37 lbs/in
Elongation	6%
Temperature Range	-40°F to 248°F
Temp Resistance (short term)	up to 356°F

CFL-5CA

Adhesive	Conductive Acrylic
Backing	1.4 mil Copper Foil
Tape Thickness (w/o liner)	3.0 mil
Peel Adhesion 180° SST	46 oz/in
Tensile Strength	37 lbs/in
Elongation	6%
Temperature Range	-40°F to 248°F
Temp Resistance (short term)	up to 356°F

WIDTH	RLS/CS	* ROLL	CASE
CFL-5A 36 YD (108 FT)			
1/4"	(6.3mm)	96	
3/8"	(9.5mm)	64	
1/2"	(12.7mm)	48	
3/4"	(19.0mm)	32	
1"	(25.4mm)	24	
1.5"	(38.1mm)	16	
2"	(50.8mm)	12	
3"	(76.2mm)	8	
4"	(101.6mm)	6	
12"	(304.8mm)	2 or 4	
24.8"	(630.0mm)	LOG	

* MINIMUM 6 INCHES.

Alternative to 3M #3225; Permacel # P-389; Lamart #881; Chomerics #CCH301; Venture #1650; Saint-Gobain #C661.

WIDTH	RLS/CS	* ROLL	CASE
CFL-5CA 36 YD (108 FT)			
1/4"	(6.3mm)	96	
3/8"	(9.5mm)	64	
1/2"	(12.7mm)	48	
3/4"	(19.0mm)	32	
1"	(25.4mm)	24	
1.5"	(38.1mm)	16	
2"	(50.8mm)	12	
3"	(76.2mm)	8	
4"	(101.6mm)	6	
12"	(304.8mm)	2 or 4	
24.8"	(630.0mm)	LOG	

* MINIMUM 6 INCHES.

Alternative to 3M #3313; Permacel # P-391; Lamart #882; Chomerics #CCH101; Venture #1697; Saint-Gobain #C665.

Lead Foil Tapes...

LF-5A... with Acrylic Adhesive

Highly malleable, pure lead foil with acrylic adhesive. Aggressive, removable acrylic adhesive system is resistant to weather, heat and solvents. Good tack and quick stick. Conforms to irregular and curved surfaces; can be shaped to the most intricate patterns. Meets Federal Spec HH-T-0029, Amendment 2. Polycoated paper release liner. 3" plastic core.

LF-5R... with Rubber Adhesive

Highly malleable, pure lead foil tape with rubber adhesive. Exhibits excellent adhesion to a wide variety of surfaces, especially metal, glass, films, foils, and papers. Can be shaped to the most intricate patterns. Can be die-cut into shapes. Complies with Federal Spec HH-T-29A, Amendment 2. Polycoated paper release liner. 3" plastic core.

Typical Applications...

LF-5A... Masking x-ray plates, electroplating, and chemical milling; radiation barrier, x-ray shielding; sealing double-paned windows; decorative leaded windows.

LF-5R... Masking during electroplating; adding weight to golf clubs; weight balancing; electromagnetic & radio frequency shield.

Physical Properties...

Adhesive	Acrylic
Backing	5 mil Lead Foil
Tape Thickness (w/o liner)	6.0 mil
Peel Adhesion	35 oz/in
Tensile Strength	18 lbs/in
Elongation (at break)	15%
Temperature Resistance	-30°F to 275°F

LF-5A

Adhesive	Acrylic
Backing	5 mil Lead Foil
Tape Thickness (w/o liner)	6.0 mil
Peel Adhesion	35 oz/in
Tensile Strength	18 lbs/in
Elongation (at break)	15%
Temperature Resistance	-30°F to 275°F

LF-5R

Adhesive	Rubber
Backing	5 mil Lead Foil
Tape Thickness (w/o liner)	6.0 mil
Peel Adhesion	60 oz/in
Tensile Strength	18 lbs/in
Elongation (at break)	15%
Temperature Resistance	40°F to 180°F

Specify LF-5A or LF-5R when ordering.

WIDTH	RLS/CS	* ROLL	CASE
36 YD (108 FT)			
1/4"	(6.3mm)	36	
3/8"	(9.5mm)	24	
1/2"	(12.7mm)	18	
3/4"	(19.0mm)	12	
1"	(25.4mm)	9	
1.5"	(38.1mm)	6	
2"	(50.8mm)	6	
3"	(76.2mm)	4	
4"	(101.6mm)	2	
20"	(508.0mm)	LOG	

* MINIMUM 6 INCHES PER ITEM.

Alternative to 3M #34201, #420; Lamart #245-L (acrylic), 245-LR (rubber).

Polyester Splicing & Printed Circuit Board Tapes...

MYP-25CA (Clear)... Acrylic Adhesive

2.4 mil total. 1 mil polyester film with 1.4 mils of electrical grade **acrylic adhesive**. Excellent resistance to solvents, heat and chemicals. Used for component packaging & electrical insulation, edge reinforcement on books, webs, etc. Exhibits high resistance to abrasives, acids, oils, aging, staining and water immersion. Meets UL510 Class B (130°C / 266°F). **Adhesion to SST: 35 oz/in.** Tensile Strength: 24 lbs/in. Elongation: 100%. Dielectric Strength: 5.5 kV. Max Temperature: 300°F/30min. 3" plastic core.

Also stocked in 144 yd. length. Proportional pricing.

WIDTH	RLS/CS	* ROLL	CASE
72 YD (66M)			
1/4"	(6.3mm)	144 or 192	
3/8"	(9.5mm)	96 or 128	
1/2"	(12.7mm)	72 or 96	
5/8"	(15.9mm)	60	
3/4"	(19.0mm)	48 or 64	
1"	(25.4mm)	36 or 48	
1.5"	(38.1mm)	24 or 32	
2"	(50.8mm)	24	
3"	(76.2mm)	16	
4"	(101.6mm)	12	
43.5"	(1105mm)	LOG	
43.5"	(1105mm)	LOG	x 144 YD

* MINIMUM 6 INCHES.

Alternative to 3M #853, #856; Saint Gobain #M60; Scapa #525.

MYP-25CS (Clear)... Silicone Adhesive

2.5 mil total. 1 mil polyester film with 1.5 mils of electrical grade **silicone adhesive**. Designed to be fully stable electrically and mechanically at operating temperatures up to 350°F. Adhesive is cured to provide maximum resistance to chemicals and leaves no residue during masking or holding applications. Excellent resistance to abrasives, acids, oils, aging, staining, and water immersion. Used for splicing silicone coated paper and films. Also used as outer wrap on coils, capacitors, motors, and transformers and for masking in electroplating, anodizing, and PC boards. Meets UL510 Class B (130°C / 266°F). **Adhesion to SST: 27 oz/in.** Tensile Strength: 25 lbs/in. Elongation: 100%. Dielectric Strength: 5.5 kV. Temperature Range: -100°F to 350°F. 3" plastic core.

72 YD (66M)

1/4"	(6.3mm)	144 or 192
3/8"	(9.5mm)	96 or 128
1/2"	(12.7mm)	72 or 96
5/8"	(15.9mm)	60
3/4"	(19.0mm)	48 or 64
1"	(25.4mm)	36 or 48
1.5"	(38.1mm)	24 or 32
2"	(50.8mm)	24
3"	(76.2mm)	16
4"	(101.6mm)	12
6"	(152.4mm)	8
43.5"	(1105mm)	LOG

* MINIMUM 6 INCHES.

Alternative to Permacel P-904; Saint Gobain #M52.

MYP-3US (Blue)... Silicone Adhesive

3.0 mil total. 1 mil polyester film with 2 mils of silicone adhesive. Resists fumes and chemicals, and leaves minimum residue on removal. Allows visibility of circuitry after masking. Film will not break or split during application or removal. A protective tape, designed to perform well in all phases of masking operations during printed circuit board production. Industry standard plater's tape. Protects surfaces from splashes and chemical fumes in tin/lead stripping and gold tab plating. **Adhesion: 30 oz/in.** Tensile Strength: 25 lbs/in. Elongation: 90%. Max Temp. Resistance: 220°C (428°F)/30 min. 3" plastic core.

72 YD (66M)

1/4"	(6.3mm)	144 or 192
5/16"	(7.9mm)	120
3/8"	(9.5mm)	96 or 128
1/2"	(12.7mm)	72 or 96
5/8"	(15.9mm)	60
3/4"	(19.0mm)	48 or 64
1"	(25.4mm)	36 or 48
1.5"	(38.1mm)	24 or 32
2"	(50.8mm)	24
3"	(76.2mm)	16
4"	(101.6mm)	12
6"	(152.4mm)	8
50.3"	(1280mm)	LOG

* MINIMUM 6 INCHES.

Alternative to Ideal #9190; Scapa #581; Permacel P-377; St. Gobain #M741; 3M #8951; Berry Global #781.

MYP-3RS (Red)... Silicone Adhesive

3.0 mil total. 1 mil polyester film with 2 mils of silicone adhesive. Resists fumes and chemicals, and leaves minimum residue on removal. Allows visibility of circuitry after masking. Film will not break or split during application or removal. A protective tape designed to perform well in all phases of masking operations during printed circuit board production. Engineering grade plating tape. Protects surfaces from splashes and chemical fumes in tin/lead stripping and gold tab plating. Suitable for painting. Can be used for splicing of certain silicone coated papers and films. Meets UL510 Class B (130°C / 266°F). **Adhesion: 30 oz./in.** Tensile Strength: 24 lbs/in. Elongation: 100%. Dielectric Strength: 5.5 kV. Temperature Range: -100°F to 350°F. 3" plastic core.

Also stocked in 144 yd. length. Proportional pricing.

72 YD (66M)

1/4"	(6.3mm)	144 or 192
5/16"	(7.9mm)	120
3/8"	(9.5mm)	96 or 128
1/2"	(12.7mm)	72 or 96
5/8"	(15.9mm)	60
3/4"	(19.0mm)	48 or 64
1"	(25.4mm)	36 or 48
1.5"	(38.1mm)	24 or 32
2"	(50.8mm)	24
3"	(76.2mm)	16
4"	(101.6mm)	12
6"	(152.4mm)	8
43.5"	(1105mm)	LOG
43.5"	(1105mm)	LOG

* MINIMUM 6 INCHES.

Alternative to Ideal #9111; Scapa #581; Permacel P-377; St. Gobain #M741; 3M #8951; Berry Global #781.

Polyester Splicing & Printed Circuit Board Tapes...

MYP-36GS (Emerald Green)... Silicone Adhesive

3.5 mil total. 2 mil polyester film coated with a 1.5 mil residue-free silicone adhesive. High tack and high adhesion. Tear and break resistant. Its high adhesion and extremely stable adhesive system give it excellent resistance to corrosive chemicals, suitable for photo processing chemistry, acids, oils, solvents, aging, water immersion and staining. One of the cleanest and strongest splicing tapes available. A superior performance leader card splicing tape. Used for splicing siliconized papers, films and non-woven materials in converting. Used for masking adhesive seams in metal bonding processes. Meets UL510 Class B (130°C / 266°F). **Adhesion to SST: 35 oz/in.** Tensile: 44 lbs/in. Elongation: 110%. Dielectric Strength: 6.0 kV. Temperature Range: -100°F to 350°F. Max Short Term: 225°C (437°F)/45 min. 3" plastic core.

WIDTH	RLS/CS	* ROLL	CASE
-------	--------	--------	------

72 YD (66M)

1/4"	(6.3mm)	144 or 192	
5/16"	(7.9mm)	120	
3/8"	(9.5mm)	96 or 128	
1/2"	(12.7mm)	72 or 96	
5/8"	(15.9mm)	60	
3/4"	(19.0mm)	48 or 64	
1"	(25.4mm)	36 or 48	
1.5"	(38.1mm)	24 or 32	
2"	(50.8mm)	24	
3"	(76.2mm)	16	
4"	(101.6mm)	12	
6"	(152.4mm)	8	
43.5"	(1105mm)	LOG	

* MINIMUM 6 INCHES.

Alternative to Ideal #9209, #9211, #9212, #9249; 3M #8902, #8464; Scapa #572; St. Gobain SP-2150, #M830, #M832; Adhesive Applications #S8512-2.

MYP-36US (Dark Blue)... Silicone Adhesive

3.5 mil total. 2 mil polyester film coated with a 1.5 mil residue-free silicone adhesive. It is one of the cleanest and strongest splicing tapes available with high tack and high adhesion. Good chemical and heat resistance. Bonds well to treated papers, films, foils, etc. Used for splicing siliconized papers, films and non-woven materials in converting. Used for masking adhesive seams in metal bonding processes. Meets UL510 Class B (130°C / 266°F). **Adhesion to SST: 35 oz/in.** Tensile: 44 lbs/in. Elongation: 110%. Dielectric Strength: 6.0 kV. Temperature Range: -100°F to 350°F. 3" plastic core.

72 YD (66M)

1/4"	(6.3mm)	144 or 192	
5/16"	(7.9mm)	120	
3/8"	(9.5mm)	96 or 128	
1/2"	(12.7mm)	72 or 96	
5/8"	(15.9mm)	60	
3/4"	(19.0mm)	48 or 64	
1"	(25.4mm)	36 or 48	
1.5"	(38.1mm)	24 or 32	
2"	(50.8mm)	24	
3"	(76.2mm)	16	
4"	(101.6mm)	12	
6"	(152.4mm)	8	
43.5"	(1105mm)	LOG	

* MINIMUM 6 INCHES.

Alternative to Ideal #9209, #9211, #9212, #9249; 3M #8902, #8464; Scapa #572; St. Gobain #SP-2150, #M830, #M832.

MYP-36OS (Brown/Rust)... Silicone Adhesive

3.8 mil total. 2 mil polyester film coated with a 1.8 mil residue-free silicone adhesive. One of the cleanest and strongest splicing tapes available. Its high adhesion and extremely stable adhesive system give it excellent resistance to photo processing chemicals, acids, oils, solvents, aging, staining and water immersion. Superior performance splicing tape used to bond photographic film to leader card during processing in automated equipment. Excellent masking tape for powder coating applications; used for masking adhesive seams in metal bonding processes. Used for splicing siliconized papers, films and non-woven materials in converting. **Adhesion to SST: 42 oz/in.** Tensile Strength: 44 lbs/in. Elongation: 100%. Dielectric Strength: 6.0 kV. Temperature Range: -100°F to 350°F. Max Short Term: 225°C (437°F)/45 min. 3" plastic core.

72 YD (66M)

1/4"	(6.3mm)	144 or 192	
5/16"	(7.9mm)	120	
3/8"	(9.5mm)	96 or 128	
1/2"	(12.7mm)	72 or 96	
5/8"	(15.9mm)	60	
3/4"	(19.0mm)	48 or 64	
1"	(25.4mm)	36 or 48	
1.5"	(38.1mm)	24 or 32	
2"	(50.8mm)	24	
3"	(76.2mm)	16	
4"	(101.6mm)	12	
43.5"	(1105mm)	LOG	

* MINIMUM 6 INCHES.

Alternative to Ideal #9209, #9211, #9212, #9249; 3M #8902, #8464; Scapa #572; St. Gobain #SP-2150, #M830, #M832.

MYP-571PS (Pink)... Silicone Adhesive

2.5 mil total. 1 mil translucent polyester film with 1.5 mils of silicone adhesive. Bonds quickly to silicone coated surfaces. Designed as a more stringent splicing tape for use on all types of substrates. Used in splicing of silicone treated papers, films and other substrates. Used for flexible circuit materials during manufacturing and subsequent processing, and as a protective maskant on panels subject to mild caustic or acid bath etching and plating. **Adhesion to SST: 33 oz/in.** Tensile Strength: 25 lb/in. Elongation: >90%. Max Temp. Resistance: 220°C (428°F)/30 min. 3" plastic core.

72 YD (66M)

1/4"	(6.3mm)	144	
3/8"	(9.5mm)	96	
1/2"	(12.7mm)	72	
5/8"	(15.9mm)	60	
3/4"	(19.0mm)	48	
1"	(25.4mm)	36	
1.5"	(38.1mm)	24	
2"	(50.8mm)	24	
3"	(76.2mm)	16	
50.3"	(1280mm)	LOG	

* MINIMUM 6 INCHES.

Alternative to Scapa Finite #572; CAP #SC-4055.

Glass Cloth/Thermal Spray Masking Tape...

GC-SH7... Glass Cloth/Silicone Adhesive

7.6 mil - Electrical grade glass cloth with silicone adhesive. Conformable; chemical and solvent resistant; printable. Used in strategic masking of areas in thermal spray/plasma spray applications; insulation of electrical apparatus, for sealing and bundling of non-electrical applications where flame retardancy or high heat resistance is required; coil armor wrap. Adhesion: 35 oz/in. Tensile Strength: 140 lbs/in. Elongation: 10%. Dielectric Strength: 3.5 kV. UL510 Insulation Class: 200°C, UL Class H. Temperature Range: -100°F to 500°F. Meets Spec: MIL-I-19166C, Type 7, FAR25853. Color: Natural White. 3" plastic core.

WIDTH	RLS/CS	* ROLL	CASE
36 YD (33M)			
1/2" (12.7mm)	72 or 96		
3/4" (19.0mm)	48 or 64		
1" (25.4mm)	36 or 48		
1.5" (38.1mm)	24 or 32		
2" (50.8mm)	18 or 24		
3" (76.2mm)	12 or 16		
4" (101.6mm)	8 or 12		
42.3" (1075mm)	LOG		

* MINIMUM 6 INCHES.

Alternative to 3M #69 & #361; Nitto/Permacel #P-212; Scapa #C401; T&F #3807; Greenbelt #160-5S; IPG #4618 & #RG48; Taconic #6605-07D-NL; Dewal #469; Ideal #IT-7300; St. Gobain/Furon #2915-7, #G565 & #G561; Chemfab #340-TS; Lanmar #715-7; AFC #380-07S.

GC-SA7... Aluminum Foil/Glass Cloth/Silicone Adhesive

8.7 mil - Fiberglass cloth with aluminum foil laminate. Provides high strength and reflectivity with excellent flexibility. Cloth is coated with high temperature resistant silicone adhesive. Non-corrosive and flame retardant (withstands open flame/extreme heat). Used in plasma masking, grit blasting, seaming of heat/flame barrier curtains, securing thermal insulation, shielding missile/aircraft components (control cables, harnesses, fuel lines, etc.). Prevents build-up of liquid metal on surfaces that must be protected. Adhesion: 43 oz/in. Tensile Strength: 72 lbs/in. Elongation: 11%. Temperature Range: -94°F to 500°F. Meets Spec: T-MIL-83284, ASTM D1000, ASTM 149, JIS Z0237. Color: Silver. 3" plastic core.

WIDTH	RLS/CS	* ROLL	CASE
36 YD (33M)			
1/2" (12.7mm)	72 or 96		
3/4" (19.0mm)	48 or 64		
1" (25.4mm)	36 or 48		
1.5" (38.1mm)	24 or 32		
2" (50.8mm)	18 or 24		
3" (76.2mm)	12 or 16		
4" (101.6mm)	8 or 12		
6" (152.4mm)	6 or 8		
41.1" (1045mm)	LOG		

* MINIMUM 6 INCHES.

Alternative to 3M #363 & #3633; Nitto/Permacel #P-100; St.Gobain/Furon #2925-7; Dewal #407; Scapa #290.

Skived PTFE Film Tapes...

TFES-2HD*, TFES-5, TFES-10... Self-Wound (without liner)

Pure skived PTFE with a high temp. **silicone adhesive**. Used in electrical applications such as harness/coil wraps & separators, transformers & slot liners where good insulation & heat resistance are required. For mechanical applications such as heat sealing bars & jaws, labeling machine pressure pads, chute liners, anti-friction devices, bearings, forming dies, aircraft mold release & guide rails where high temperature, maximum slip and lubricity are required. High elongation permits tight wrapping; conforms to sharp bends/irregular surfaces. *TFES-2HD is a high density, TENSILIZED skived PTFE film which provides higher tensile strength, lower elongation & higher dielectric strength than regular skived film (primarily used for electrical applications listed above & roll protection in flat die extrusion). Meets Spec AA-59474 Type-1, Superseding 23594C Type 1. 3" plastic core.

Physical Properties:

Backing Thickness	TFES-2HD	TFES-5	TFES-10
Total Tape Thickness	2 mil/0.002"	5mil/0.005"	10mil/0.010"
Break Strength	3.5 mil/0.0035"	7.2 mil/0.0072"	11.5 mil/0.0115"
Adhesion	35 lb/in	15 lb/in	60 lb/in
Elongation	34 oz/in	30 oz/in	55 oz/in
Maximum Operating Temperature	150%	200%	300%
Dielectric Strength	500°F	500°F	500°F
Alternative to:	12 kV	12 kV	20 kV
3M	#5180, 5480	#5181, 5481	
Permacel	#P422	#P421	#P424
DeWal	#204-2HD	#204-5	#204-10
St. Gobain	#2255-2	#2255-5	#2045-10
Taconic	#6445-02	#6115-05	#6115-10
Chemfab	#380-02		
Lanmar	#585-2	#585-5	

WIDTH	RLS/CS	LENGTH: 36 YD (108') 33M		18 YD (54') 16.5M	
		TFES-2HD		TFES-5	
		* ROLL	CASE	* ROLL	CASE
1/4" (6.3mm)	144				
3/8" (9.5mm)	96				
1/2" (12.7mm)	72				
3/4" (19.0mm)	48				
1" (25.4mm)	36				
1.5" (38.1mm)	24				
2" (50.8mm)	18				
3" (76.2mm)	12				
21.5" (546mm)	LOG				
36" (914mm)	LOG				

* MINIMUM 6 INCHES PER ITEM.

Kapton™ Alternative Polyimide Tapes...

KPT-(Mil)... Wave Solder/Hot Air Leveling Tape

1 and 2 mil Electrical grade Kapton™ alternative Polyimide film coated with a high performance silicone adhesive. Thin and conformable. Outstanding tear and abrasion resistance at elevated temperatures. Adhesive will thermoset to increase adhesion values. Leaves minimal residue when removed after manufacturing process; reduces clean-up time and minimizes rejects. Permits observation of board during processing. Excellent resistance to acids, oils, solvents, aging, staining, water immersion. Protects gold contacts from molten solder during hot air wave solder leveling process. Film meets UL510. Formulated to meet spec MIL-P-46112B. 3" plastic core.

Physical Properties:

KPT-1	KPT-2
1 mil	2 mil
2.6 mil	3.5 mil
Adhesion	23.8 oz/in
Tensile Strength	>20.6 lbs/in
Elongation	>30%
Dielectric Strength	>4000 V
Temperature Resistance	200°C (392 °F)/30 min
Film Color	Gold/Amber (transparent)

™DuPont Trademark

WIDTH	RLS/CS	* ROLL	CASE
KPT-1 36 YD (33M)			
1/4" (6.3mm)	144 or 192		
3/8" (9.5mm)	96 or 128		
1/2" (12.7mm)	72 or 96		
5/8" (15.9mm)	60		
3/4" (19.0mm)	48 or 64		
7/8" (22.2mm)	48		
1" (25.4mm)	36 or 48		
1.5" (38.1mm)	24 or 32		
2" (50.8mm)	24		
3" (76.2mm)	12		
4" (101.6mm)	12		
25.2" (640mm)	LOG		

* MINIMUM 6 INCHES.

Alternative to Dielectric Polymer #NT-590; Permacel #P-221; 3M #5419, #5433; Shurtape #6325-01; Scapa #557; St. Gobain/Furon #2345-1; Dewal #304-1; Ideal #9321, #IT-7170; TLC #CT961; Specialty Tapes #S2210; Lanmar #595-1; Chemfab #360-1S; Tesa #4428.

WIDTH	RLS/CS	* ROLL	CASE
KPT-2 36 YD (33M)			
1/4" (6.3mm)	144 or 192		
3/8" (9.5mm)	96 or 128		
1/2" (12.7mm)	72 or 96		
5/8" (15.9mm)	60		
3/4" (19.0mm)	48 or 64		
7/8" (22.2mm)	48		
1" (25.4mm)	36 or 48		
1.5" (38.1mm)	24 or 32		
1.75" (44.4mm)	24		
2" (50.8mm)	24		
3" (76.2mm)	12		
4" (101.6mm)	12		
19.7" (500mm)	LOG		

* MINIMUM 6 INCHES.

Alternative to Electro Tape #95-2; Ideal #9322; T&F #3903; American #304-2; Anchor #K-350; Permacel #P-222; Taconic #6325-02; Berry Global #2345-2; Tesa #4429; Dewal #303-2.

PTFE Coated Glass Fabric Tapes...

TFE- Mil thickness (-3, -5, -6, or -10)... Specify with (WL) or without (SW) liner.

Impregnated fiberglass cloth, consisting of warp & fill yarns, coated with a high temperature silicone adhesive. Excellent electrical, mechanical and chemical properties. Used as a primary insulation in a variety of electrical equipment & heat sealing bars, chute liners, gaskets, bearing surfaces, tabletop covers, guide rails and roll covers. Low friction surface; abrasion resistant. Product comes standard with liner ("WL") or available self-wound ("SW"). 1/2" AND 3/4" WIDE ROLLS MUST BE SELF WOUND. Also available without adhesive ("NA"). 3" plastic core.

Physical Properties

Backing Thickness	TFE-3WL or TFE-3SW	TFE-5WL or TFE-5SW	TFE-6WL or TFE-6SW	TFE-10WL or TFE-10SW
Total Tape Thickness	2.8 mil/0.0028"	4.6 mil/0.0046"	5.4 mil/0.0054"	9.1 mil/0.0091"
Breaking Strength (Warp Fill)	5.0 mil/0.0050"	6.8 mil/0.0068"	8.4 mil/0.0084"	12.1 mil/0.0121"
Adhesion	100 lb/in 70 lb/in	135 lb/in 120 lb/in	150 lb/in 140 lb/in	290 lb/in 180 lb/in
Elongation (Warp Fill)	43 oz/in	36 oz/in	40 oz/in	60 oz/in
Operating Temperature Range	3.4% 2.0%	2.9% 3.2%	3.0% 4.0%	4.0% 3.4%
Electrical Strength	-100°F to 500°F	-100°F to 500°F	-100°F to 500°F	-100°F to 500°F
Alternative to:	3M #5451	#5452	6.1 kV	6.5 kV
	DeWal #134-3	#134-5	#5453	#5454
St. Gobain	#SG25-03	#SG25-05	#134-6	#134-10
Greenbelt	#100-3S	#100-5S	#SG25-06	#SG25-10
W.F. Lake	#L40S-3	#L40S-5	#100-6S	#100-10S
Taconic	#6085-03	#6085-05	#L-40S-6	#L-40S-10
Chemfab	#350-35	#350-55	#6085-06	#6085-10
Lanmar	#635-3	#635-5	#350-6S	#350-10S
AFC	#25003S	#25005S	#635-6	#635-0
			#25006S	#25010S

WIDTH	RLS/CS	LENGTH: 36 YD (108') 33M							
		TFE-3WL or TFE-3SW		TFE-5WL or TFE-5SW		TFE-6WL or TFE-6SW		TFE-10WL or TFE-10SW	
		* ROLL	CASE	* ROLL	CASE	* ROLL	CASE	* ROLL	CASE
1/2" (12.7mm)	72								
3/4" (19.0mm)	48								
1" (25.4mm)	36								
1.5" (38.1mm)	24								
2" (50.8mm)	18								
3" (76.2mm)	12								
36" (914.0mm)	LOG								

PTFE Coated Glass Fabrics Without Adhesive ("NA") (cost per inch width)	TFE-3NA		TFE-5NA		TFE-6NA		TFE-10NA	
	18 YD	36 YD	18 YD	36 YD	18 YD	36 YD	18 YD	36 YD

* MINIMUM 6 INCHES PER ITEM.

UHMW Polyolefin Tapes...

UHMW-(Mil)... Acrylic Adhesive

Ultra High Molecular Weight (UHMW) Polyolefin Tapes. 3 mil, 5 mil, 10 mil, 15 mil and 20 mil films coated with a pressure sensitive acrylic adhesive. Its high chemical and abrasion resistance and extremely low coefficient of friction makes this a versatile engineering material for many severe service applications. Materials slide freely over tape surface with no slip/stick tendency. High impact strength and shock absorbing properties. Outwears Teflon™ and is a good replacement when high temperature resistance is not a requirement. Rub strips on conveyors, bearings and sliding surfaces, chutes and hopper liners, dead plates, wear pads, guide rails, furniture and drawer slides. Used primarily in automotive and mechanical applications. UHMW-3A, UHMW-5A, UHMW-10A are wound on a 3 mil white paper liner; UHMW-15A & UHMW-20A are wound on a 2 mil blue poly liner. 3" plastic core. FILM COLOR: Natural transparent.

Physical Properties...

	UHMW-3A	UHMW-5A	UHMW-10A	UHMW-15A	UHMW-20A
Backing Thickness	3 mil	5 mil	10 mil	15 mil	20 mil
Total Tape Thickness (w/o liner)	5 mil	7 mil	12 mil	17 mil	22 mil
Liner Color / Type	White Paper	White Paper	White Paper	Blue Poly	Blue Poly
Peel Adhesion	50 oz/in	50 oz/in	50 oz/in	60 oz/in	60 oz/in
Tensile Strength	20 lb/in	40 lb/in	80 lb/in	60 lb/in	60 lb/in
Elongation	300%	350%	425%	300%	300%
Max. Operating Temperature	225°F	225°F	225°F	200°F	200°F
Alternative to:	Dewal 3M Lamart Venture St. Gobain Specialty Tape Taconic Lanmar	#423-3 #5425, #9325 #150-3 #2302-3R #6311-03 #622-3R	#423-5FW #5430 #150-5 #967 #2302-5R #S882 #6311-05 #622-5R	#423-10 #5423 #150-10 #968 #2302-10R #S884 #6311-10 #622-10R	#423-15 #423-20 #2302-15 #2302-20R #6311-15 #622-20R

WIDTH	RLS/CS	LENGTH: 36 YD (33M) 108'				LENGTH: 18 YD (16.5M) 54'			
		UHMW-3A		UHMW-5A		UHMW-10A		UHMW-15A	
		* ROLL	CASE	* ROLL	CASE	* ROLL	CASE	* ROLL	CASE
1/2" (12.5mm)	72 or 96								
3/4" (19mm)	48 or 64								
1" (25mm)	36 or 48								
1.5" (38mm)	24 or 32								
2" (50mm)	18 or 24								
3" (75mm)	16								
4" (100mm)	12								
26" (673mm)	LOG								
54" (1372mm)	LOG								

NEW WIDER LOG WIDTH UHMW-3A, UHMW-5A & UHMW-10A.

* MINIMUM 6 INCHES PER ITEM.

Metalized Polyester Film Tapes...

MMYP-1... Acrylic Adhesive

1 mil Metalized Polyester Film with a brilliant, vibrant, mirror-like finish, coated with an aggressive, long lasting acrylic adhesive. Tapes have excellent chemical and thermal stability. Silver can be qualified to meet Federal Specification #L-T-100B, Type II. 3" plastic core.

Applications...

Reflective shielding; industrial and graphic arts; decorative trim, automotive trim, nameplates, electric appliances, advertising displays; suitable for micro film splicing; also can be used in photo sensing applications to detect splices and to facilitate roll changeovers- recommend test sampling first.

Physical Properties:

Adhesive	Acrylic
Total Thickness	2.1 mil
Adhesion to Steel	50 oz/in
Tensile Strength	25 lbs/in
Elongation	115%
Temperature Resistance	up to 300°F

WIDTH	RLS/CS	LENGTH: 72 YD (66M)	
		SILVER	OTHER COLORS
* ROLL	CASE	* ROLL	CASE
1/4" (6.3mm)	192		
3/8" (9.5mm)	128		
1/2" (12.7mm)	96		
3/4" (19.0mm)	64		
1" (25.4mm)	48		
1.5" (38.1mm)	32		
2" (50.8mm)	24		
3" (76.2mm)	16		
4" (101.6mm)	12		
6" (152.4mm)	8		
38.4" (975mm)	LOG		

* MINIMUM 6 INCHES PER COLOR.

Alternative to 3M #850; Ideal #505; TLC #CT941M; Achem #MP50; Tesa #4137; Venture #1555CW; St. Gobain/Furon #MT150 & #PS100; Specialty Tapes #S298; Decker #136.

4 COLORS AVAILABLE: SILVER, BLACK, GOLD & RED.

(Other colors available as special order)

38.4" (975mm) x 660M (722 yd) Jumbos Available.

Double Coated PVC Tapes...

DC-4414W... PVC (White)

5.5 mil exclusive of liner. 1.5 mil White PVC film coated on both sides with a **solvent based acrylic adhesive**. Gold siliconized paper liner. Extremely aggressive adhesive bonds well to nearly all materials, even to difficult surfaces like foams, PE and PP films. Excellent temperature, UV, aging, water vapor resistance. Used extensively for mounting signs and large format graphics. For bonding trims in automotive and other industries; securing attachment of extruded plastic profiles in furniture industries. **Adhesion: 80 oz/in (1 min dwell); 102 oz/in (24 hr dwell)**. Temperature Resistance: -40°F to 158°F. 3" neutral core/carton.

39.4" (1000mm) x 500M Jumbos Available.

DC-4420... PVC (White)

9.1 mil exclusive of liner. 1.5 mil White PVC film coated on both sides with a **solvent based acrylic adhesive**. Gold siliconized paper liner. Extremely aggressive adhesive bonds well to nearly all materials, even to difficult surfaces like foams, PE and PP films. Excellent temperature, UV, aging, and water vapor resistance. Used for bonding rubber, plastic, metal and wood substrates; for permanent mounting of nameplates and decorative trim on appliances and furniture. **Adhesion to SST: 110 oz/in (1 min dwell)**. Elongation: 35%. Minimum Application Temp: 15°C (59°F). Temperature Resistance: -40°F to 158°F continuous. 3" neutral core/carton.

54" (1372mm) x 600M Jumbos Available.

Add -PC for plastic cores +\$ per case or log.

Other roll widths and/or lengths available upon request.

DC-4420LB... PVC (Clear or *Black)

7.87 mil (0.20mm) exclusive of liner. 3.2 mil (80 micron) PVC film coated on both sides with a **modified acrylic adhesive**, solvent free, based on aqueous dispersions. 90gsm Gold glassine paper release liner. Extremely aggressive adhesive bonds well to nearly all materials, even to difficult surfaces like foams, PE and PP films. Excellent temperature, UV, aging, and water vapor resistance. Used for bonding rubber, plastic, metal and wood substrates; for permanent mounting of nameplates and decorative trim on appliances and furniture. **Adhesion: 157 oz/in (1 hr dwell)**. Shear Resistance: 14 lbs/in². Temperature Resistance: -40°F to +176°F. 3" neutral core/carton.

39.4" (1000mm) x 500M Jumbos Available.

***FOR BLACK FILM, ADD 5% (x 1.05).**



DC-4425AR... PVC (White)

9.84 mil exclusive of liner. 3.2 mil white PVC film coated on both sides with an aggressive, solvent-free, **modified acrylic adhesive**. 90gsm Gold glassine paper release liner. Its adhesive strength builds with time. Moisture and temperature resistant. Exhibits good tack and adheres extremely well to rough surfaces, such as chipboards, and LSE substrates, such as foam, PE and PP films. APEO/APE Free. **Adhesion: 168 oz/in**. Tack: 62 oz/in. Temperature Resistance: -40°F to 266°F. 3" neutral core/carton.

39.4" (1000mm) x 500M Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+

36 YD (33M)		
3/8"	(9mm)	96
1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36 or 48
1.5"	(36mm)	24
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
39.4"	(1000mm)	LOG

36 YD (33M)		
3/8"	(9mm)	96
1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36 or 48
1.5"	(36mm)	24
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
54"	(1372mm)	LOG

60 YD (55M)		
1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36
1.5"	(36mm)	24
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
54"	(1372mm)	LOG

Alternative to Tesa #4970; Scapa #S301; #3M #419; IPG #597; Lohman #370.

36 YD (33M) CLEAR OR *BLACK (+5%)

3/8"	(9mm)	96
1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36 or 48
1.5"	(36mm)	24
2"	(48mm)	18 or 24
3"	(72mm)	12
4"	(96mm)	12
39.4"	(1000mm)	LOG

60 YD (55M) CLEAR OR *BLACK (+5%)

3/8"	(9mm)	96
1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36
1.5"	(36mm)	24
2"	(48mm)	18 or 24
3"	(72mm)	12
39.4"	(1000mm)	LOG

36 YD (33M)

3/8"	(9mm)	96
1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36 or 48
1.5"	(36mm)	24
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
39.4"	(1000mm)	LOG

Double Coated Polyester Tapes...

DC-1114... Polyester (Clear)

3.5 mil (0.09mm) exclusive of liner. 0.5 mil thin clear polyester film coated on both sides with an aggressive synthetic **hot melt rubber adhesive**, and wound on a 2.7 mil white siliconized paper release liner. Superior moisture resistance in humid conditions once bonded. Excellent quick-stick. Ideal for laminating difficult substrates and various webs, such as foams and foils. Perfect for splicing of papers, plastics, films, foils, etc. Used in general purpose bonding and mounting (e.g. nameplates, mouse pad assembly). **Adhesion to SST: 64 oz/in.** Elongation: 130%. Environmentally friendly; solventless adhesive. Temperature Resistance: -4°F to 140°F. 3" neutral core/carton.

DC-4106LW... Polyester (Clear)

2.4 mil (0.06mm) exclusive of liner. 0.5 mil clear polyester film coated on both sides with a modified **solvent free water based acrylic adhesive**. Light blue siliconized paper liner. Adheres to most materials, even difficult surfaces like foams and PE film. Good alternative to adhesive transfer tapes as it is thin, hand tearable, and easier to apply by hand. Very good temperature, UV, aging and water vapor resistance. No plasticizer migration. Can be used for splicing, bonding, and laminating paper, corrugated paper, films, plastics, foils, etc. For mounting nameplates, keyboard assemblies; laminating various webs. **Adhesion: >47 oz/in.** Temperature Resistance: -40°F to 212°F. 3" neutral core/carton.

DC-4109CS/G... Polyester (Clear)

3.5 mil (0.09mm) exclusive of liner. 0.5 mil clear polyester film coated on both sides with an aggressive, quick stick, **solvent free water based acrylic adhesive**. Gold glassine paper release liner. High peel and shear strength. Excellent moisture resistance in high humidity, UV and aging resistance. **Wide web width for laminating.** For high speed flying splice of paper, corrugated paper, plastics, films, foils, etc.; mounting nameplates, keyboard assembly; laminating dissimilar metals; automotive applications. **Adhesion: >44 oz/in.** Temperature Resistance: -40°F to 392°F. 3" neutral core/carton.

(Replaced DC-4109RS)

DC-4109CS... Polyester (Clear)

3.5 mil (0.09mm) exclusive of liner. 0.5 mil clear polyester film coated on both sides with an aggressive, quick stick, **solvent free water based acrylic adhesive**. White glassine paper release liner. Excellent peel and shear strength. Superior moisture resistance in high humidity. For high speed flying splice of paper, corrugated paper, plastics, films, foils, etc.; mounting nameplates, keyboard assembly; laminating dissimilar metals. **Adhesion: >44 oz/in.** Temperature Resistance: -40°F to 392°F. 3" neutral core/carton.

Alternative to Venture #514CW & #518; 3M #415; Adchem #254M; Anchor #593; Berry Global #126; Int'l Tape #202 & #203.

DC-4109/R... Polyester (Bright Red)

3.5 mil (0.09mm) exclusive of liner. 0.5 mil **bright red** polyester film coated on both sides with an aggressive, **clear acrylic adhesive**. White kraft paper liner. High tack/adhesion/shear strength, excellent temperature performance. For splicing paper, plastics, films, foils, low/high energy surfaces, and continuous web processes when a visual splice is critical. **Adhesion: 95 oz/in.** **Tack: 77 oz/in.** Elongation: 110%. Temperature Resistance: -22°F to 320°F (428°F short term). 3" neutral core/carton.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
60 YD (55M)				
1/4"	(6mm)	192		
3/8"	(9mm)	128		
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
3"	(72mm)	16		
4"	(96mm)	12		
6"	(144mm)	8		
54"	(1370mm)	LOG		

Alternative to Adchem #3175M; Venture #512; Scapa #S-662.
54" (1370mm) x approx. 1000M Jumbos Available.

60 YD (55M)		
1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
39.4"	(1000mm)	LOG

Alternative to Tesa #4972.
39.4" (1000mm) x 1000M Jumbos Available.

60 YD (55M)		
1/4"	(6mm)	192
3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
59"	(1500mm)	LOG

59" (1500mm) x 800M Jumbos Available.

60 YD (55M)		
1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
6"	(144mm)	8
39.4"	(1000mm)	LOG

39.4" (1000mm) x 1000M Jumbos Available.

60 YD (55M)		
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
48.4"	(1230mm)	LOG

Alternative to 3M #9420 & #9737R; Berry Global #756; Scapa #5234R; Venture #515R; Int'l Tape #713R; Newbond #TF2404.

48.4" (1230mm) x 800M Jumbos Available.

Double Coated Polyester Tapes...

DC-4123... Polyester (Clear) - Red PP Liner

7.5 mil exclusive of liner. 0.5 mil clear polyester film coated with a very aggressive, high tack, high shear **solvent based acrylic adhesive**. This product comes with a dimensionally stable Red PP release liner making it suitable for precision die-cut applications. It has excellent temperature, UV, aging, and water vapor resistance. Also has good plasticizer resistance. **Adhesion to SST: (1 min. dwell): 88 oz/in.** Temperature Resistance: up to 320°F long term, 356°F short term. Elongation: 100%. Tensile Strength: 14 lbs/in. Used for bonding, joining, laminating when high tack and high shear are critical. 3" neutral core/carton.

Alternative to Tesa #4965, Lohman #373, Adchem #488M-PP-54.

Minimum 6 inches @ 1-2 case price +10%.

54" (1372mm) x 700M Jumbos Available.

Also stocked in 180yd length @ 60yd proportional pricing.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
36 YD (33M)				
3/8"	(9mm)	96		
1/2"	(12mm)	72		
3/4"	(18mm)	48		
1"	(24mm)	36		
1.5"	(36mm)	24		
2"	(48mm)	18		
3"	(72mm)	12		
54"	(1372mm)	LOG		
60 YD (55M)				
3/8"	(9mm)	96		
1/2"	(12mm)	72		
3/4"	(18mm)	48		
1"	(24mm)	36		
1.5"	(36mm)	24		
2"	(48mm)	18		
3"	(72mm)	12		
54"	(1372mm)	LOG		

Double Coated Polypropylene Tapes...

DC-1503... Polypropylene (Clear)

3.8 mil (0.097mm) exclusive of liner. 1.1 mil clear BOPP film coated on both sides with a **synthetic rubber resin adhesive**. Gold siliconized paper release liner. Solvent-free adhesive, ideal for fixing photographs. Used for core start-ups, splicing, holding, joining, attaching, mounting, and laminating applications. Good tack on flat surfaces. **Adhesion to SST: 73 oz/in (exposed side); 110 oz/in (liner side).** Tensile Strength: 23 lbs/in. Elongation: 140%. Temperature Resistance: 140°F. 3" neutral core/carton.

53.5" (1360mm) x 1200M Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
60 YD (55M)				
3/8"	(9mm)	96 or 128		
1/2"	(12mm)	72 or 96		
3/4"	(18mm)	48 or 64		
1"	(24mm)	36 or 48		
1.5"	(36mm)	24 or 32		
2"	(48mm)	18 or 24		
3"	(72mm)	12 or 16		
53.5"	(1360mm)	LOG		

Alternative to Tesa #64621; 3M #9576; Venture #1162, #1163; Boma #4140.

DC-1511... Polypropylene (White)

4.3 mil (0.110mm) exclusive of liner. 2.0 mil white non-oriented polypropylene coated on both sides with a high grade **hot melt rubber adhesive**. White siliconized paper release liner. High stretch for curved surfaces. High adhesion to paper, plastic and metal surfaces, excellent aging properties. Good adhesion to rough surfaces. Hand tearable. Economical carpet tape. **Adhesion to SST: 71 oz/in.** Tensile Strength: 5 lbs/in. Elongation: 800%. Environmentally friendly; solventless adhesive. Temperature Resistance: -4°F to 140°F. 3" neutral core/carton.

Alternative to Int'l Tape #850; Tesa #64622.

54" (1370mm) x approx. 1000M Jumbos Available.

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
54"	(1370mm)	LOG

25 YD (23M)

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
54"	(1370mm)	LOG

36 YD (33M)

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
54"	(1370mm)	LOG

55 YD (50M)

1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36
1.5"	(36mm)	24
2"	(48mm)	18
3"	(72mm)	12
54"	(1372mm)	LOG

Alternative to Tesa #51970.

Minimum 6 inches @ 1-2 case price +10%.

DC-3522... Polypropylene (Clear)

8.5 mil (0.215mm) exclusive of liner. 2.2 mil high performance clear polypropylene film coated on both sides with an age-resistant, **solvent based acrylic adhesive**. Gold siliconized paper liner. Extremely aggressive, ensuring permanency of the bond, even when exposed to elements (UV, humidity, solvents and chemicals). Bonds well to nearly all materials - metal, plastic, HSE, LSE, rough surfaces, etc. Used for mounting plastic/wood trims, fabrication of heavy decorative materials and displays, mounting transparent signs, bonding vinyl decals, and attaching plastic corner guards or extrusions. **Adhesion: 80 oz/in.** Temperature Resistance: -40°F to 248°F (320°F short term). 3" neutral core/carton.

54" (1372mm) x 600M Jumbos Available.

Double Coated Tapes With Differential Adhesion...

DC-3107R/P... Polyester (Clear)

2.8 mil exclusive of liner. 0.5 mil clear polyester film **differentially coated** with a high tack and low tack pure poly acrylic adhesive. Wound on a siliconized 90gsm white paper release liner. Exhibits excellent processing characteristics. Adheres well to a wide variety of materials, including plastics, films, wood, glass, aluminum and other metals. Removable/low adhesive side provides good bond strength and easy removability. **Adhesion (20 mins): 26 oz/in (exposed), 7 oz/in (liner). Adhesion (24 hrs): 33 oz/in (exposed), 22 oz/in (liner).** Application Temperature: 50°F. Temperature Range: -40°F to 302°F. 3" neutral core/carton.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
55 YD (50M)				
1/4"	(6mm)	192		
3/8"	(9mm)	128		
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
3"	(72mm)	16		
4"	(96mm)	12		
61"	(1550mm)	LOG		

DC-4110R/P... Polyester (Clear)

3.7 mil exclusive of liner. 1.0 mil clear polyester film **differentially coated with a high tack and low tack solvent based acrylic adhesive.** 76# White kraft paper liner. The **exposed/unwind side** is coated with an aggressive, high peel and tack acrylic adhesive. The **liner side** is coated with a removable, low tack adhesive system that leaves no residue upon removal on most surfaces and no ghosting on glasses; reusable when bonded to clean surfaces. Good initial tack and adhesion to most materials, including low surface energy (LSE) substrates like PE or PP. Good UV resistance. For securing/mounting objects, displays, notices, ads, and point-of-purchase/window displays that can easily be removed/replaced/repositioned. **Adhesion: 49 oz/in (exposed), 7 oz/in (liner). Tack: 56 oz/in (exposed), 11 oz/in (liner).** Temperature Range: -4°F to 212°F. 3" neutral core/carton.

60 YD (55M)

1/4"	(6mm)	192
3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
54"	(1370mm)	LOG

54" (1370mm) x 690M Jumbos Available.

Double Coated Paper Tapes...

DC-2306... Crepe Paper

6.0 mil (9.2 mil with liner). 3.5 mil high quality saturated crepe paper coated on both sides with a medium tack, high shear, synthetic copolymer **rubber based adhesive.** 60# white calendered siliconized Kraft paper release liner. Good adhesion with excellent repositionability. Used for general purpose bonding of papers, films, fabrics, etc; **DISCONTINUED / SOLD OUT (replacement TBD)** holding wood cuts & dies with little to no residue upon removal; and mounting golf club grip handles depending on lubricant type. Do NOT laminate/bond to materials containing migrating plasticizers. **Adhesion: 80 oz/in.** Tensile: 16 lbs/in. Elongation: 5%. Application Temp: 60°F to 120°F. Temp. Range: 0°F to 180°F. 3" neutral core/carton.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
36 YD (33M)				
1/4"	(6mm)	192		
3/8"	(9mm)	128		
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
DISCONTINUED / SOLD OUT (replacement TBD)				
3"	(72mm)	16		
4"	(96mm)	12		
6"	(144mm)	8		
54"	(1372mm)	LOG		

Alternative to Int'l Tape #282; Adchem #262C; 3M #400.

DC-2315... Crepe Paper with Crepe Liner

6.0 mil (10.4 mil with liner). 4.3 mil crepe paper coated on both sides with an aggressive **natural rubber/resin adhesive.** White **crepe paper release liner.** Good quick stick; great adhesive strength; bonds to most surfaces. Used in the printing industry, textile manufacturing (twisting/spinning process), steel rule die-makers/die-cutters (make-ready), & carpet installation. For bonding, mounting, holding, joining, core start-ups, and splicing applications. Used for repairing/replacing golf club grips. **Adhesion: 47 oz/in.** Quick Stick: 20 oz/in. Tensile: 23 lbs/in. Elongation: 8.5%. 3" neutral core/carton.

48" (1219mm) x 720Yd Jumbos Available.

36 YD (33M)

1/4"	(6mm)	192
3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
12"	(300mm)	4
48"	(1219mm)	LOG

Alternative to IPG #592; Shurtape #GG 200; #DF 63.

Double Coated Paper Tapes...

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+

DC-4309LW... Paper

3.5 mil exclusive of liner. 1.5 mil (0.35mm) white paper coated on both sides with a high tack **modified solvent free water based acrylic adhesive**; white 80 gr. siliconized paper liner. Adheres to nearly all materials, even difficult surfaces like foams & PE films. Very good temperature, UV, aging & water vapor resistance. Used for splicing, mounting, bonding, holding nameplates & laminating. **Adhesion (1 hr. dwell): >58 oz/in.** Elongation: 5%. Temp. Resistance: -40°F to +212°F. 3" neutral core/carton.

39.4" (1000mm) x 1000M Jumbos Available.

36 YD (33M)

1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
39.4"	(1000mm)	LOG

DC-4317VS... Paper

6.7 mil exclusive of liner. 4 mil white paper coated on both sides with an aggressive **modified solvent free water based acrylic adhesive**; 90gsm gold glassine paper release liner. Good direct & durable adhesive strength; good dynamic & static shear strength. Good water vapor, temperature, UV & aging resistance. No plasticizer migration on most surfaces. Moderate chemical resistance (should be tested). Excellent corrugated splicing tape. Used for other holding, joining, attaching & laminating applications. **Adhesion (1 hr. dwell): 96 oz/in.** Temp. Range: -40°F to 248°F. Elongation: 5%. 3" neutral core/carton.

39.4" (1000mm) x 1000M Jumbos Available.

36 YD (33M)

1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
39.4"	(1000mm)	LOG

DC-2307... Flatback Paper

7.0 mil (12 mil with liner). Flatback paper coated on both sides with a high shear/aggressive **solvent based natural rubber** resin adhesive. White **crepe paper liner** allows for both automatic & hand dispensing applications. Bonds to most surfaces. Conforms well to rough & irregular surfaces. Excellent for installation of golf club grips. Meets spec CID A-A-180C, Type II (replaces UU-T-91E). **Adhesion: 52 oz/in.** Quick Stick: 20 oz/in. Unwind: 11 oz/in. Tensile: 34 lbs/in. Elongation: 3%. 3" neutral core/carton.

48" (1219mm) x 720Yd Jumbos Available.

36 YD (33M)

1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
6"	(144mm)	8
12"	(300mm)	4
48"	(1219mm)	LOG

Alternative to IPG #591; Tesa #4903; Shurtape #GG200; #DF65; Cantech #406-00.

Most of our items can be custom converted (other rolls widths and/or lengths). Contact us for details!

Double Coated Tissue Tapes...

DC-4210VS-B... Tissue (Black)

3.9 mil (0.10mm) exclusive of liner. 0.5 mil **black**, non-woven tissue coated on both sides with a modified, **solvent-free acrylic adhesive**, wound on a gold release liner. Exhibits a strong direct tack and continuous adhesive strength, as well as dynamic shear strength on most surfaces. No plasticizer migration on most surfaces. Excellent corrugators' splicing tape. Used in manufacturing for continuous web processes when a visual splice is needed. Good temperature, UV and aging resistance. **Adhesion to SST (1 hr dwell): >47 oz/in.** Tack to PE: 26 oz/in. Dynamic Shear: 38 lb/in². Elongation: 1%. Temperature Range: -40°F to 248°F; short term up to 392°F. 3" neutral core/carton.

39.4" (1000mm) x 1000M Jumbos Available.

DC-4210VS... Tissue

3.9 mil (0.10mm) exclusive of liner. 0.5 mil **white**, non-woven tissue coated on both sides with a modified, **solvent-free acrylic adhesive**, wound on a gold glassine release liner. Exhibits a strong direct tack and continuous adhesive strength, as well as dynamic shear strength on most surfaces even when heat is applied. Good temperature, UV and aging resistance. No plasticizer migration on most surfaces. Excellent corrugators' splicing tape; made specifically for corrugated, paper and film splicing. Adheres to foam, metal, glass, plastic, non-woven, felt, and LSE substrates like PE and PP films. Used in wide web laminating jobs. **Adhesion to SST (1 hr dwell): >47 oz/in.** Tack to PE: 26 oz/in. Dynamic Shear: 38 lb/in². Temperature Range: -40°F to 248°F; short term up to 392°F. 3" neutral core/carton.

59" (1500mm) x 800M Jumbos Available.

(Replaced DC-4210RS)

DC-4215WO... Tissue

5.9 mil (0.15mm) exclusive of liner. 0.5 mil white, non-woven tissue coated on both sides with an aggressive, modified solvent free **water based acrylic adhesive**, wound on a 50# siliconized gold glassine release liner. Provides a strong durable bond with good dynamic and static shear strength on most surfaces. Excellent adhesion to non-polar PE films and foams which are difficult surfaces to splice or laminate. Very resistant to humidity and weather when bonded. Very good temperature, UV, and aging resistance; however, tape exhibits moderate resistance against solvents. Superior conformability to irregular surfaces due to its heavy adhesive coat weight. Designed for heavy-duty splicing and permanent holding, with excellent performance on smooth or rough surfaces. Used for core start-ups, splicing of heavy webs such as wallpaper, holding, joining, attaching and mounting. **Adhesion to SST: >84 oz/in.** Temperature Range: -40°F to 320°F. 3" neutral core/carton.

39.4" (1000mm) x 800M Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+

60 YD (55M)

3/8"	(9mm)	128		
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
3"	(72mm)	16		
4"	(96mm)	12		
39.4"	(1000mm)	LOG	neutral core	

55 YD (50M)

3/8"	(9mm)	128		
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
3"	(72mm)	16		
4"	(96mm)	12		
59"	(1500mm)	LOG	neutral core	

110 YD (100M)

3/8"	(9mm)	128		
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
3"	(72mm)	16		
59"	(1500mm)	LOG	neutral core	

Alternative to Tesa #4959, #50453 & #7158; Venture #585; Shurtape #DF-633; Scapa #5711; 3M #400, #404, #406.

36 YD (33M)

3/8"	(9mm)	128		
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
3"	(72mm)	16		
39.4"	(1000mm)	LOG	neutral core	

60 YD (55M)

3/8"	(9mm)	128		
1/2"	(12mm)	96		
3/4"	(18mm)	64		
1"	(24mm)	48		
1.5"	(36mm)	32		
2"	(48mm)	24		
3"	(72mm)	16		
39.4"	(1000mm)	LOG	neutral core	

Most of our items can be custom converted (other rolls widths and/or lengths). Contact us for details!

Double Coated Tissue Tapes...

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+

DC-1210... Tissue

4.0 mil exclusive of liner. 1.8 mil tissue substrate coated on both sides with an aggressive **synthetic hot melt rubber adhesive**. 2.6 mil gold siliconized glassine paper release liner. Excellent quick stick and peel strength. Good for flying splice or static splicing where high resistance to heat is not required. Excellent for nameplates, trophies, core start-ups; laminating cork, cloth or felt; splicing papers, textiles or plastics. **Adhesion: 90 oz/in.** Tensile: 5.7 lbs/in. Operating Temperature: up to 140°F. Elongation: 5%. 3" neutral core/carton.

53.5" (1360mm) x 1200M Jumbos Available.

60 YD (55M)

3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
53.5"	(1360mm)	LOG

Alternative to Tesa #4903; 3M #406; Venture #520; Adchem #2627; Boma #4150; Int'l Tape #207.

DC-3208SA... Tissue

3.2 mil exclusive of liner. White, non-woven tissue carrier coated on both sides with a **solvent based acrylic adhesive**, wound on white PE coated paper liner. Quickly bonds to smooth surfaces like metal plates, films and plastics. Used to fix and laminate various substrates of electronic devices and components. For general holding, attaching, joining, and laminating application. Rolling Ball Tack: <100mm. **Adhesion: 54 oz/in.** Application Temperature: 50°F to 105°F. Temperature Resistance: up to 248°F. 3" neutral core/carton.

48.8" (1240mm) x 1250M Jumbos Available.

55 YD (50M)

3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
48.8"	(1240mm)	LOG

neutral core

110 YD (100M)

1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
48.8"	(1240mm)	LOG

neutral core

Alternative to IPG #DCT101A; V. Himark #F2410.

DC-3212SA... Tissue

4.7 mil exclusive of liner. White, non-woven tissue carrier coated on both sides with a **solvent based acrylic adhesive**, wound on a siliconized gold glassine paper release liner. It exhibits good permanent adhesive strength as well as good static and dynamic shear properties on most surfaces, even when heat is applied. No plasticizer migration on most surfaces. Perfect for splicing of plastic film, paper and foil of industrial grade. Excellent corrugators' flying splice tape. Can also be used for general holding, joining, attaching, and laminating applications. Rolling Ball Tack: <50mm. **Adhesion: 83 oz/in.** Application Temperature: 50°F to 105°F. Temperature Resistance: up to 248°F. 3" neutral core/carton.

47.2" (1200mm) x 1000M Jumbos Available.

55 YD (50M)

3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
47.2"	(1200mm)	LOG

neutral core

110 YD (100M)

3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
4"	(96mm)	12
47.2"	(1200mm)	LOG

neutral core

Alternative to Tesa #7158, #50658, #4959, #50605; Shurtape DT200; 3M #469; Achem DT63Q; V. Himark #L2450.

Double Coated Cloth Tapes...

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+

DC-5215... Polyester Fabric Tape

6.1 mil exclusive of liner. White polyester fabric coated on both sides with a **white synthetic hot melt rubber adhesive**. The product has an easy release, gold siliconized paper liner. Good tack and aggressive adhesion; bonds well to various surfaces and shapes. Suitable for use on most carpets and floorings. Hand-tearable and highly conformable. Not resistant to plasticizers. **Adhesion to Steel: 91 oz/in (exposed side); 73 oz/in (liner side)**. Tensile Strength: 15 lbs/in. Elongation 10%. Temperature Resistance: 140°F. 3" neutral core/carton.

53.5" (1360mm) x 850M Jumbos Available.

25 YD (23M)

1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
53.5"	(1360mm)	LOG

36 YD (33M)

1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
53.5"	(1360mm)	LOG

DC-5225... Polyester Fabric Tape

9.3 mil exclusive of liner. White polyester fabric coated on both sides with a white, aggressive **synthetic hot melt rubber adhesive**. Gold siliconized paper liner. High tack and excellent adhesion; ideal for use on rough surfaces. Used for laying carpet, fixing and splicing of textiles, securing polyethylene film to brick and cinder block walls, other general mounting on rough or fibrous surfaces. Provides additional support during prepping applications of abatement areas. Hand-tearable. Not resistant to plasticizers. **Adhesion to Steel: 128 oz/in (exposed side); 99 oz/in (liner side)**. Tensile Strength: 18 lbs/in. Elongation 15%. Temperature Resistance: 140°F. 3" neutral core/carton.

53.5" (1360mm) x 650M Jumbos Available.

25 YD (23M)

1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
53.5"	(1360mm)	LOG

36 YD (33M)

1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
53.5"	(1360mm)	LOG

Alternative to Tesa #4934; Shurtape #DF-642; Int'l Tape #319; Sicad #730-GDA; Venture #581.

DC-5227X... Exhibition Carpet Tape. Removable.

11 mil exclusive of liner. Natural colored cotton/polyester blended cloth coated on both sides with a high shear, moderate tack **natural rubber based adhesive. Residue free**. Blue silicone coated polyethylene release liner allows for complete, tear free liner pull and removal. Used for carpet hold-down and other general purpose uses in aircraft mfg. Used extensively in the convention and trade show industry as it will leave no adhesive residue upon removal from most substrates. **Adhesion to Steel: 40 oz/in**. Tensile Strength: 20 lbs/in. 3" neutral core/carton.

60" (1524mm) x 684 Yd Jumbos Available.



25 YD (23M)

1"	(24mm)	48
1.5"	(36mm)	32
2"	* (48mm)	24
3"	* (72mm)	16
4"	(96mm)	12
60"	(1524mm)	LOG

36 YD (33M)

1"	(24mm)	48
1.5"	(36mm)	32
2"	* (48mm)	24
3"	(72mm)	16
4"	(96mm)	12
60"	(1524mm)	LOG

Alternative to Berry Global #105C; Shurtape #DF-545.

* Lower proportional price, as stocked pre-slit.

Double Coated Scrim Tape...

DC-4608MF... Double Coated Scrim Tape

3.15 mil exclusive of liner. An aggressive clear PES/PVA scrim coated on both sides with a modified **solvent free water based acrylic adhesive**. 90gsm Gold glassine paper release liner. The adhesive system of this double coated tape has excellent tack combined with high adhesive strength. Bond well to nearly all materials, even to difficult surfaces like foams, PE and PP films. APEO/APE Free. Hand tearable. Excellent temperature, UV, aging and water vapor resistance. Acrylic adhesive provides long term performance. Scrim reinforcement provides for improved lay down. Used for permanent bonding of various materials such as fabrics, wallboard, plastic, metal and wood surfaces. Used for laminating foams and films. Used to make frames self-adhesive. **Adhesion: 76 oz/in.** Temperature Resistance: -40°F to 194°F. 3" neutral core/carton.

39.4" (1000mm) x 800M Jumbos Available.

54" (1371mm) x 800M Jumbos Available.

59" (1500mm) x 800M Jumbos Available.

***COMING SOON (late 2024): NEW WIDER WIDTH!**

59" (1500mm) will replace 39.4" (1000mm) once stock is depleted.

DC-4623MF... Heavy-Duty Scrim Tape

9.1 mil exclusive of liner. Thick polyester reinforced transfer tape (PES/PVA Scrim) with an aggressive, modified **solvent free water based acrylic adhesive**. 90gsm Gold glassine paper release liner. The adhesive system is extremely aggressive, and will bond well to nearly all materials; even to difficult surfaces like foam, PE and PP films. It has good temperature, UV, aging, and water vapor resistance. Used for permanent bonding of plastic, metal and wood (P.M.W.) surfaces. APEO/APE Free. Primarily designed for use in bonding carpet and plastic baseboard molding to walls, ceilings, modular units, etc. **Adhesion: 120 oz./in.** Temperature Resistance: -40°F to 194°F. 3" neutral core/carton.

54" (1371mm) x 800M Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+

36 YD (33M)		
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
39.4"	(1000mm)	LOG
54"	(1371mm)	LOG
59"	* (1500mm)	LOG

60 YD (55M)		
1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36
1.5"	(36mm)	24
2"	(48mm)	18
3"	(72mm)	12
39.4"	(1000mm)	LOG
54"	(1371mm)	LOG
59"	* (1500mm)	LOG

227M		
39.4"	(1000mm)	LOG
54"	(1371mm)	LOG
59"	* (1500mm)	LOG

25 YD (23M)		
3/8"	(9mm)	128
1/2"	(12mm)	96
3/4"	(18mm)	64
1"	(24mm)	48
1.5"	(36mm)	32
2"	(48mm)	24
3"	(72mm)	16
54"	(1371mm)	LOG

36 YD (33M)		
3/8"	(9mm)	96
1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36
1.5"	(36mm)	24
2"	(48mm)	18
3"	(72mm)	12
54"	(1371mm)	LOG

55 YD (50M)		
3/4"	(18mm)	48
1"	(24mm)	36
1.5"	(36mm)	24
2"	(48mm)	18
54"	(1371mm)	LOG

Most of our items can be custom converted (other rolls widths and/or lengths). Contact us for details!

Ultra High Bond Tapes...

Double Coated Acrylic Foam

This is a foamed acrylic system with a special composition giving excellent all around bonding properties and unique characteristics that allows for very high performance in the most demanding of applications. The pressure sensitive acrylic composition provides for very good tack, excellent adhesion to a variety of surfaces and high shear strength performance. Tape is carried on a **RED release coated polyethylene liner** that is easily removed.

FA-UHB10C... CLEAR Foamed Acrylic Tape

10 mils (0.25mm) exclusive of liner. Clear foamed acrylic with RED PE liner. Ideal for structural bonding applications to mount/fix car side molding and emblems. For mounting illuminated signs, for fabricating road signs, joining of metals and plastic trims in furniture construction and architectural applications. **90° Peel Adhesion: 86 oz/in (20 min); 115 oz/in (24 hrs)**. Tensile Strength: 99 lb/in². Dynamic Shear (SST): 132 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

Peel Adhesion: 86 oz/in (20 min); 115 oz/in (24 hrs). Tensile Strength: 99 lb/in². Dynamic Shear (SST): 132 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

FA-UHB16E... GRAY Foamed Acrylic Tape

16 mils (0.40mm) exclusive of liner. Gray foamed acrylic with RED PE liner. Used for bonding components in the electronics industries, such as computers, consumer electronics, white goods, bonding thin sheet metal and plastics. **90° Peel Adhesion: 125 oz/in (20 min); 161 oz/in (24 hrs)**. Tensile Strength: 88 lb/in². Dynamic Shear (SST): 132 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

FA-UHB16W... WHITE Foamed Acrylic Tape

16 mils (0.40mm) exclusive of liner. White foamed acrylic with RED PE liner. Used for bonding components in the electronics industries, such as computers, consumer electronics, white goods, bonding thin sheet metal and plastics. **90° Peel Adhesion: 125 oz/in (20 min); 161 oz/in (24 hrs)**. Tensile Strength: 88 lb/in². Dynamic Shear (SST): 132 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

FA-UHB20C... CLEAR Foamed Acrylic Tape

20 mils (0.50mm) exclusive of liner. Clear foamed acrylic adhesive with RED PE liner. Used as a mounting tape in the illuminated sign industry, for fabricating road signs, joining of metals and plastic trims in furniture construction and architectural applications. **90° Peel Adhesion: 129 oz/in (20 min); 161 oz/in (24 hrs)**. Tensile Strength: 99 lb/in². Dynamic Shear (SST): 99 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

FA-UHB25E... GRAY Foamed Acrylic Tape

25 mils (0.64mm) exclusive of liner. Gray foamed acrylic adhesive with RED PE liner. Ideal for structural bonding applications to mount/fix car side molding and emblems. Bonding of metal furniture, cabinets, lockers, plastic extrusion fixing. **90° Peel Adhesion: 161 oz/in (20 min); 233 oz/in (24 hrs)**. Tensile Strength: 99 lb/in². Dynamic Shear (SST): 132 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

WIDTH	RLS/CS	* ROLL	CASE
36 YD (108 FT) 33M			
1/4"	(6.3mm)	48	
3/8"	(9.5mm)	32	
1/2"	(12.7mm)	24	
3/4"	(19.0mm)	16	
1"	(25.4mm)	12	
35.4"	(900.0mm)	LOG	

Alternative to 3M #9473; Hi-Bond #4025C; ORAFOL ORABOND™ #UHB03025T, #3596.

WIDTH	RLS/CS	* ROLL	CASE
72 YD (216 FT) 66M			
1/4"	(6.3mm)	48	
3/8"	(9.5mm)	32	
1/2"	(12.7mm)	24	
3/4"	(19.0mm)	16	
1"	(25.4mm)	12	
37"	** (940.0mm)	LOG	

Alternative to 3M #4920; Hi-Bond #6040G.

** NEW wider log width.

WIDTH	RLS/CS	* ROLL	CASE
72 YD (216 FT) 66M			
1/4"	(6.3mm)	48	
3/8"	(9.5mm)	32	
1/2"	(12.7mm)	24	
3/4"	(19.0mm)	16	
1"	(25.4mm)	12	
35.4"	(900.0mm)	LOG	

Alternative to 3M #4920; Hi-Bond #4040W.

WIDTH	RLS/CS	* ROLL	CASE
36 YD (108 FT) 33M			
1/4"	(6.3mm)	48	
3/8"	(9.5mm)	32	
1/2"	(12.7mm)	24	
3/4"	(19.0mm)	16	
1"	(25.4mm)	12	
35.4"	(900.0mm)	LOG	

Alternative to 3M #4905; Hi-Bond #4050C; ORAFOL ORABOND™ #UHB03050T, #3597.

WIDTH	RLS/CS	* ROLL	CASE
36 YD (108 FT) 33M			
1/4"	(6.3mm)	48	
3/8"	(9.5mm)	32	
1/2"	(12.7mm)	24	
3/4"	(19.0mm)	16	
1"	(25.4mm)	12	
35.4"	(900.0mm)	LOG	

Alternative to 3M #4936, #4936F, #4919F, #5925, #4929, #4646, RP25; Hi-Bond #6064G; ORAFOL ORABOND™ #UHB04064G #3594.

*** NOTE: For ALL UHB products, MINIMUM 3 INCHES per item.**

Ultra High Bond Tapes...

Double Coated Acrylic Foam

FA-UHB25W... WHITE Foamed Acrylic Tape

25 mils (0.64mm) exclusive of liner. White foamed acrylic adhesive with RED PE liner. Ideal for structural bonding applications to mount/fix car side molding and emblems. Used for bonding of metal furniture, cabinets, lockers, plastic extrusion fixing. **90° Peel Adhesion: 161 oz/in (20 min); 233 oz/in (24 hrs).** Tensile Strength: 99 lb/in². Dynamic Shear (SST): 132 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

WIDTH	RLS/CS	* ROLL	CASE
-------	--------	--------	------

36 YD (108 FT) 33M

1/4"	(6.3mm)	48
3/8"	(9.5mm)	32
1/2"	(12.7mm)	24
3/4"	(19.0mm)	16
1"	(25.4mm)	12
35.4"	(900.0mm)	LOG

Alternative to 3M #4930, #4930F; Hi-Bond #4064W; ORAFOL ORABOND™ #UHB03064W, #3595.

FA-UHB31E... GRAY Foamed Acrylic Tape

31 mils (0.8mm) exclusive of liner. Gray foamed acrylic adhesive with a special composition giving excellent all around bonding properties and unique characteristics that allows for very high performance in the most demanding of applications. **90° Peel Adhesion: 233 oz/in (20 min); 394 oz/in (24 hrs).** Tensile Strength: 121 lb/in². Dynamic Shear (SST): 128 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

36 YD (108 FT) 33M

1/4"	(6.3mm)	48
3/8"	(9.5mm)	32
1/2"	(12.7mm)	24
3/4"	(19.0mm)	16
1"	(25.4mm)	12
35.4"	(900.0mm)	LOG

Alternative to 3M #5314, #4214, #5345, #5665; ADCO #AT-6030; Hi-Bond #6080G; ORAFOL ORABOND™ #UHB03080G, #3598.

FA-UHB40C... CLEAR Foamed Acrylic Tape

39 mils (1.0mm) exclusive of liner. Clear foamed acrylic adhesive with RED PE liner. Used in the manufacture of laminated safety and hurricane impact glass. Bonding, sealing and fixing of shower screens, glass/plastic display cabinets, refrigerated/chilled drink cabinets. **90° Peel Adhesion: 179 oz/in (20 min); 233 oz/in (24 hrs).** Tensile Strength: 88 lb/in². Dynamic Shear (SST): 88 lb/in². Temperature Resistance: -40°F to 392°F. UV Resistance: Good. 3" plastic core.

36 YD (108 FT) 33M

1/4"	(6.3mm)	48
3/8"	(9.5mm)	32
1/2"	(12.7mm)	24
3/4"	(19.0mm)	16
1"	(25.4mm)	12
35.4"	(900.0mm)	LOG

Alternative to Hi-Bond #4100C; ORAFOL ORABOND™ #UHB03100T, #3599; 3M #4910.

FA-UHB45E... GRAY Foamed Acrylic Tape

43 mils (1.1mm) exclusive of liner. Gray foamed acrylic adhesive with RED PE liner. Ideal for structural bonding applications in the transportation industry. Used in automotive aftermarket industry, body shops, crash repair, mounting/fixing car side molding and emblems. **90° Peel Adhesion: 251 oz/in (20 min); 430 oz/in (24 hrs).** Tensile Strength: 99 lb/in². Dynamic Shear (SST): 121 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

36 YD (108 FT) 33M

1/4"	(6.3mm)	48
3/8"	(9.5mm)	32
1/2"	(12.7mm)	24
3/4"	(19.0mm)	16
1"	(25.4mm)	12
35.4"	(900.0mm)	LOG

Alternative to 3M #4941, #4941F, #4947F, #4949, #4611, #5344, #5605, #5952; ADCO #1140; Hi-Bond #6110G; ORAFOL ORABOND™ #UHB03110G, #3600.

FA-UHB45W... WHITE Foamed Acrylic Tape

43 mils (1.1mm) exclusive of liner. White foamed acrylic adhesive with RED PE liner. Ideal for structural bonding applications in the transportation industry. Bonding of plastic and wooden window glazing bars, fixing architectural cladding panels. **90° Peel Adhesion: 233 oz/in (20 min); 323 oz/in (24 hrs).** Tensile Strength: 110 lb/in². Dynamic Shear (SST): 121 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

36 YD (108 FT) 33M

1/4"	(6.3mm)	48
3/8"	(9.5mm)	32
1/2"	(12.7mm)	24
3/4"	(19.0mm)	16
1"	(25.4mm)	12
35.4"	(900.0mm)	LOG

Alternative to 3M #4622, #4945, #4946, #4950; ORAFOL ORABOND™ #3601, #UHB03110W; Hi-Bond #4110W.

* NOTE: For ALL UHB products, MINIMUM 3 INCHES per item.

Ultra High Bond Tapes...

Double Coated Acrylic Foam

FA-UHB60C... CLEAR Foamed Acrylic Tape

59 mils (1.5mm) exclusive of liner. Clear foamed acrylic with RED PE liner. Ideal for all around bonding in the most demanding applications. **90° Peel Adhesion: 215 oz/in (20 min); 258 oz/in (24 hrs)**. Tensile Strength: 66 lb/in². Dynamic Shear (SST): 77 lb/in². Temperature Resistance: -40°F to 392°F. UV Resistance: Good. 3" plastic core.

FA-UHB60E... GRAY Foamed Acrylic Tape

59 mils (1.5mm) exclusive of liner. Gray foamed acrylic adhesive with RED PE liner. Ideal for all around bonding in the most demanding applications. **90° Peel Adhesion: 233 oz/in (20 min); 412 oz/in (24 hrs)**. Tensile Strength: 99 lb/in². Dynamic Shear (SST): 121 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

FA-UHB80C... CLEAR Foamed Acrylic Tape

79 mils (2.0mm) exclusive of liner. Clear foamed acrylic adhesive with RED PE liner. Ideal for all around bonding in the most demanding applications. Used for structural bonding applications, bonding plastic & wooden window glazing bars, fixing architectural panels. **90° Peel Adhesion: 226 oz/in (20 min); 287 oz/in (24 hrs)**. Tensile Strength: 66 lb/in². Dynamic Shear (SST): 66 lb/in². Temperature Resistance: -40°F to 392°F. UV Resistance: Good. 3" plastic core.

FA-UHB80E... GRAY Foamed Acrylic Tape

79 mils (2.0mm) exclusive of liner. Gray foamed acrylic adhesive with RED PE liner. Ideal for structural bonding applications in the transportation industry; fixing body & roof panels in the bus and truck industry, mounting/fixing car side molding & emblems. **90° Peel Adhesion: 215 oz/in (20 min); 358 oz/in (24 hrs)**. Tensile Strength: 99 lb/in². Dynamic Shear (SST): 121 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

FA-UHB80W... WHITE Foamed Acrylic Tape

79 mils (2.0mm) exclusive of liner. White foamed acrylic adhesive with RED PE liner. Ideal for all around bonding in the most demanding applications. Used for structural bonding applications, bonding plastic & wooden window glazing bars, fixing architectural panels. **90° Peel Adhesion: 215 oz/in (20 min); 358 oz/in (24 hrs)**. Tensile Strength: 99 lb/in². Dynamic Shear (SST): 121 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

FA-UHB120W... WHITE Foamed Acrylic Tape

118 mils (3.0mm) exclusive of liner. White foamed acrylic adhesive with RED PE liner. Ideal for structural bonding applications in the transportation industry; fixing body and roof panels in the bus and truck industry, mounting/fixing car side molding and emblems. **90° Peel Adhesion: 215 oz/in (20 min); 358 oz/in (24 hrs)**. Tensile Strength: 99 lb/in². Dynamic Shear (SST): 121 lb/in². Temperature Resistance: -40°F to 356°F. UV Resistance: Good. 3" plastic core.

WIDTH	RLS/CS	* ROLL	CASE
-------	--------	--------	------

27.34 YD (82 FT) 25M

1/4"	(6.3mm)	48
3/8"	(9.5mm)	32
1/2"	(12.7mm)	24
3/4"	(19.0mm)	16
1"	(25.4mm)	12
35.4"	(900.0mm)	LOG

Alternative to 3M #4915; ADCO #1160; Hi-Bond #4150C.

27.34 YD (82 FT) 25M

1/4"	(6.3mm)	48
3/8"	(9.5mm)	32
1/2"	(12.7mm)	24
3/4"	(19.0mm)	16
1"	(25.4mm)	12
35.4"	(900.0mm)	LOG

Alternative to 3M #4956, #4979F, #5356, #5567, #5962; ADCO #4655, #4956; Hi-Bond #6150G; ORAFOL ORABOND™ #UHB04150G, #3603.

18 YD (54 FT) 16.5M

1/4"	(6.3mm)	48
3/8"	(9.5mm)	32
1/2"	(12.7mm)	24
3/4"	(19.0mm)	16
1"	(25.4mm)	12
35.4"	(900.0mm)	LOG

Alternative to 3M #4918; Hi-Bond #4200C.

18 YD (54 FT) 16.5M

1/4"	(6.3mm)	48
3/8"	(9.5mm)	32
1/2"	(12.7mm)	24
3/4"	(19.0mm)	16
1"	(25.4mm)	12
35.4"	(900.0mm)	LOG

Alternative to 3M #4991; Hi-Bond #6200G; ORAFOL ORABOND™ #UHB04200G, #3602.

18 YD (54 FT) 16.5M

1/4"	(6.3mm)	48
3/8"	(9.5mm)	32
1/2"	(12.7mm)	24
3/4"	(19.0mm)	16
1"	(25.4mm)	12
35.4"	(900.0mm)	LOG

Alternative to 3M #4912; ADCO #4955; Hi-Bond #4200W.

18 YD (54 FT) 16.5M

1/4"	(6.3mm)	48
3/8"	(9.5mm)	32
1/2"	(12.7mm)	24
3/4"	(19.0mm)	16
1"	(25.4mm)	12
35.4"	(900.0mm)	LOG

Alternative to 3M #4959; Hi-Bond #6300W.

* NOTE: For ALL UHB products, MINIMUM 3 INCHES per item.

Ultra High Bond Tapes...

Acrylic Transfer Tapes (AT-UHB mil thickness) & Double Coated (DC-UHB mil thickness)

Ultra High Bond Acrylic Adhesive Tapes are carried on a 7 mil white polyethylene release liner. Tape bonds to most surfaces, but thorough evaluation is recommended when bonding on low energy surface materials such as PVC, ABS, PE, PP. Not recommended for bonding Teflon™, Tedlar™, Silicone or EPDM. Temperature Range: -30°F to 200°F. Application Temperature: 50°F to 100°F. 3" plastic core.

AT-UHB10... 10 mil

AT-UHB40... 40 mil

This structural grade **solid acrylic adhesive transfer** system has been skillfully engineered to provide a strong, moistureproof bond between various substrates. It is flexible, moldable, & compressible. Due to its clarity, can be used to bond glass and other clear materials. Bonds permanently to most clean, dry, oil-free, non-porous surfaces, including aluminum, stainless steel, glass, painted metal, and many others. Used in attachment of dissimilar surfaces. Used for auto and truck trim attachment; in aviation, marine, electronics, furniture, signage & appliance industries. Applications: replacing mechanical fasteners, bonding nameplates & decorative trim; window fabrication (standard and high impact resistant); bonding/seaming metal in electrical panels, HVAC units; fabrication of bullet proof products. Maintains bond at sub-zero temperature. Excellent UV, solvent & moisture resistance (Note: as with similar products, tape will yellow when exposed to UV, but performance is not affected). 3" plastic core. COLOR: WATER CLEAR.

Physical Properties...

Specific Gravity	1.04
Tensile Strength	150 psi
Elongation	1000%
Peel Adhesion	160 oz/in.
Cleavage Strength	20 psi
Dynamic Shear Strength	60 psi

DC-UHB25... 25 mil

DC-UHB45... 45 mil

This structural grade tape is comprised of an integral core of **solid acrylic polymer**, coated on both sides with a uniform high-tack acrylic adhesive. Provides a superior, permanent bond between a wide variety of substrates, including glass, some plastics, composites, sealed wood, metals and painted metals. Applications: rugged metal to metal bonds to replace welding, rivets, bolts, screw and cementing; signs, graphic arts assemblies; furniture/appliance mfg, RV skin to frame assembly. Withstands a wide range of weathering and temperature conditions without losing adhesion. Non-staining, will not harden/become brittle with age. Maintains adhesion at sub-zero temperatures. Solid acrylic core gives tape superior strength, can be easily applied and cleanly cut, yet is flexible, moldable, compressible & conformable to intricate shapes. Solid core is key for structural assembly, used primarily in transportation industry, automotive, truck, trailer & bus, OEM & aftermarket, as it isolates and dampens vibration and shock. DC-UHB45 approved for certain GM, Ford and Chrysler specifications. 3" plastic core. COLOR: TRANSLUCENT.

Physical Properties...

Density	62.5 lbs/ft ³
Tensile Strength	200 psi
Elongation	500%
Peel Adhesion	240 oz/in.
Cleavage Strength	30 psi
Dynamic Shear Strength	90 psi

WIDTH	RLS/CS	* ROLL	CASE
AT-UHB10	10 mil.	60 YD (55M)	
1/4"	(6.3mm)	48	
3/8"	(9.5mm)	32	
1/2"	(12.7mm)	24	
3/4"	(19.0mm)	16	
1"	(25.4mm)	12	
18"	(457.0mm)	LOG	

* MINIMUM 3 INCHES.

Alternative to 3M #9473; ADCO #AT-1, AT-1010; Hi-Bond #VST-4025C.

WIDTH	RLS/CS	* ROLL	CASE
AT-UHB40	40 mil.	36 YD (33M)	
1/4"	(6.3mm)	48	
3/8"	(9.5mm)	32	
1/2"	(12.7mm)	24	
3/4"	(19.0mm)	16	
1"	(25.4mm)	12	
18"	(457.0mm)	LOG	

* MINIMUM 3 INCHES.

Alternative to 3M #4910; ADCO #AT-1, AT-1040; Hi-Bond #VST-4100C.

NOTE: AT-UHB60 (60 mil) is available as a special, non-cancelable order; must take full web width (18").

WIDTH	RLS/CS	* ROLL	CASE
DC-UHB25	25 mil.	72 YD (66M)	
1/4"	(6.3mm)	48	
3/8"	(9.5mm)	32	
1/2"	(12.7mm)	24	
3/4"	(19.0mm)	16	
1"	(25.4mm)	12	
18"	(457.0mm)	LOG	

* MINIMUM 3 INCHES.

Alternative to 3M #4925, #4929, #4930, #4936; ADCO #AT-3, AT-3025; Scapa #S5300A; Hi-Bond #VST-6025G.

WIDTH	RLS/CS	* ROLL	CASE
DC-UHB45	45 mil.	36 YD (33M)	
1/4"	(6.3mm)	48	
3/8"	(9.5mm)	32	
1/2"	(12.7mm)	24	
3/4"	(19.0mm)	16	
1"	(25.4mm)	12	
18"	(457.0mm)	LOG	

* MINIMUM 3 INCHES.

Alternative to 3M #4940, #4943, #4949, #4950, #6381 to #6384 (retail); ADCO #AT-3, AT-3045; Scapa #S5300B; Hi-Bond #VST-6110W.

NOTE: DC-UHB60 (60 mil) & DC-UHB80 (80 mil) are available as a special, non-cancelable order; must take full web width (18").

Single Sided Low Density PVC Foam Tape...

SF-VFLD... GRAY OR BLACK PVC Foam Tape

Description...

A **low density** (between 6-10 lbs/ft³) closed cell PVC foam tape coated on one side with a high performance **acrylic** adhesive, and carried on a white siliconized paper liner. Good combination of flexibility & conformability with strength, wear and temperature resistance (remains pliable at -4°F to 176°F). Excellent weatherability and chemical resistance. It is a clean, waste free substitute for liquid sealants. An economical, general purpose foam tape. Used in applications requiring positive seals on irregular surfaces or when flexibility and conformability to seal tight radius curves are critical considerations.


Applications...

Used extensively in the automotive, HVAC, and construction industries to provide air and weather tight seals; for gasketing, cushioning, vibration control in speakers, vehicles, electronic components, door frames, etc.

Physical Properties...

Force to Compress 25% (range)	3.0-4.0 psi
Compression Deflection (range)	1.0-2.5 psi
Tensile Strength (Minimum)	>15 psi
Adhesion to SST (Minimum)	>12 oz/in

Alternative to Norton V700 series; Gaska #V710 and #V810; Novagard LD series.



3/4" (0.75") THICK x 15 FT - BLACK (ONLY)

3/4"	(18mm)	32
7/8"	(21mm)	27
1"	(24mm)	24
1.5"	(36mm)	16
2"	(48mm)	12
58"(54")*	(1372mm)	LOG

* **Usable width.**

CASES

WIDTH RLS/CS 1-2 3-5 6+

1/16" (0.063") THICK x 150 FT - BLACK (ONLY)

3/16"	(4.7mm)	128
1/4"	(6mm)	96
3/8"	(9mm)	64
1/2"	(12mm)	48
5/8"	(15mm)	38
3/4"	(18mm)	32
7/8"	(21mm)	27
1"	(24mm)	24
1.5"	(36mm)	16
2"	(48mm)	12
56"(54")*	(1372mm)	LOG

1/8" (0.125") THICK x 75 FT - BLACK OR GRAY

3/16"	(4.7mm)	128
1/4"	(6mm)	96
3/8"	(9mm)	64
1/2"	(12mm)	48
5/8"	(15mm)	38
3/4"	(18mm)	32
7/8"	(21mm)	27
1"	(24mm)	24
1.5"	(36mm)	16
2"	(48mm)	12
58"(54")*	(1372mm)	LOG

3/16" (0.188") THICK x 50 FT - BLACK OR GRAY

1/4"	(6mm)	96
3/8"	(9mm)	64
1/2"	(12mm)	48
5/8"	(15mm)	38
3/4"	(18mm)	32
7/8"	(21mm)	27
1"	(24mm)	24
1.5"	(36mm)	16
2"	(48mm)	12
58"(54")*	(1372mm)	LOG

1/4" (0.25") THICK x 35 FT - BLACK OR GRAY

1/4"	(6mm)	96
3/8"	(9mm)	64
1/2"	(12mm)	48
5/8"	(15mm)	38
3/4"	(18mm)	32
7/8"	(21mm)	27
1"	(24mm)	24
1.5"	(36mm)	16
2"	(48mm)	12
58"(54")*	(1372mm)	LOG

3/8" (0.375") THICK x 30 FT - BLACK (ONLY)

3/8"	(9mm)	64
1/2"	(12mm)	48
5/8"	(15mm)	38
3/4"	(18mm)	32
7/8"	(21mm)	27
1"	(24mm)	24
1.5"	(36mm)	16
2"	(48mm)	12
58"(54")*	(1372mm)	LOG

1/2" (0.5") THICK x 25 FT - BLACK OR GRAY

1/2"	(12mm)	48
5/8"	(15mm)	38
3/4"	(18mm)	32
7/8"	(21mm)	27
1"	(24mm)	24
1.5"	(36mm)	16
2"	(48mm)	12
58"(54")*	(1372mm)	LOG

Single Sided Medium Density PVC Foam Tape...

SF-VFMD... BLACK PVC Foam Tape

Description...

A medium density (between 13-17 lbs/ft³) closed cell PVC foam tape coated on one side with a high performance **acrylic** adhesive. White siliconized paper liner. Higher density provides for a tougher more durable tape product for more demanding applications. Excellent combination of flexibility & conformability with strength, wear and temperature resistance (remains pliable at -4°F to 176°F). Excellent weatherability & chemical resistance. A clean, waste free substitute for liquid sealants.

Applications...

Used extensively in the automotive, HVAC, and construction industries to provide air and weather tight seals; for gasketing, cushioning, vibration control in speakers, vehicles, electronic components, door frames, etc.

Physical Properties...

Force to Compress 25% (Range)	6.5-9.5 psi
Compression Deflection (Range)	4.0-6.0 psi
Tensile Strength (Minimum)	>45 psi
Adhesion to SST (Minimum)	>12 oz/in

1/4" (0.25") THICK x 35 FT - BLACK FOAM

1/4" (6mm)	96
3/8" (9mm)	64
1/2" (12mm)	48
5/8" (15mm)	38
3/4" (18mm)	32
1" (24mm)	24
1.5" (36mm)	16
2" (48mm)	12
58"(54")* (1372mm)	LOG

WIDTH	RLS/CS	CASES		
		1-2	3-5	6+
1/16" (0.063") THICK x 150 FT - BLACK FOAM				
3/16"	(4.7mm)	128		
1/4"	(6mm)	96		
3/8"	(9mm)	64		
1/2"	(12mm)	48		
3/4"	(18mm)	32		
1"	(24mm)	24		
1.5"	(36mm)	16		
2"	(48mm)	12		
58"(54")*	(1372mm)	LOG		

1/8" (0.125") THICK x 75 FT - BLACK FOAM

1/4"	(6mm)	96
3/8"	(9mm)	64
1/2"	(12mm)	48
3/4"	(18mm)	32
1"	(24mm)	24
1.5"	(36mm)	16
2"	(48mm)	12
58"(54")*	(1372mm)	LOG

3/16" (0.188") THICK x 50 FT - BLACK FOAM

1/4"	(6mm)	96
3/8"	(9mm)	64
1/2"	(12mm)	48
3/4"	(18mm)	32
1"	(24mm)	24
1.5"	(36mm)	16
2"	(48mm)	12
58"(54")*	(1372mm)	LOG

* Usable width.

Alternative to Norton #V760; Gaska #V1110 and #V1510; Novagard HD series.

Window Glazing Tape: Double Coated PE Foam with Poly Liner...

DC-PEF06P... 1/16" Foam Tape

DC-PEF12P... 1/8" Foam Tape

High performance **closed cell cross-linked polyethylene foam** coated on both sides with a high performance **acrylic adhesive (2 mils per side)**. Designed for window glazing. Adhesive system is formulated to bond with glass, wood, and aluminum substrates with quick stick, high peel adhesion and very good shear strength. Outstanding resistance to weather for outdoor applications. Superior seal against dust and moisture due to flexible, soft foam. Easy peel **4 mil blue polypropylene release liner** for continuous and complete liner removal during window glazing applications. Other uses include mounting of emblems, nameplates, plastic strips, and mirrors. 3" neutral paper core/carton.

Physical Properties:

	DC-PEF06P	DC-PEF12P
Thickness, Density	1/16" (62 mil), 4#	1/8" (124 mil), 2#
Peel Adhesion to SST (1 min)	55 oz/in	27 oz/in
Peel Adhesion to SST (24 hrs)	73 oz/in	46 oz/in
Shear Adhesion @ 1kg psi	168+ hours	
Service Temperature	-22°F to 212°F (short term up to 266°F)	


WIDTH	RLS/CS	CASES		
		1-2	3-5	6+
1/16" x 50 YD (150 FT) - WHITE OR BLACK FOAM				
1/4"	(6mm)	48		
3/8"	(9mm)	32		
1/2"	(12mm)	24		
5/8"	(15mm)	20		
3/4"	(18mm)	16		
7/8"	(21mm)	14		
1"	(24mm)	12		
61"(59")*	(1500mm)	LOG		

1/8" x 25 YD (75 FT) - BLACK FOAM

1/4"	(6mm)	48
3/8"	(9mm)	32
1/2"	(12mm)	24
5/8"	(15mm)	20
3/4"	(18mm)	16
7/8"	(21mm)	14
1"	(24mm)	12
60"(59")*	(1500mm)	LOG

* Usable width.

Other roll widths available upon request.



Double Coated Polyethylene Foam Tapes...

Closed cell, cross-linked polyethylene foam tapes coated on both sides with a high performance **acrylic or rubber adhesive**. Tapes are permanent and designed to have exceptional durability in demanding environments. Suitable for applications where moisture resistance is required. Good resistance to humidity, mild acids, oil and grease. Excellent conformability and compressibility. Adheres well to textured and irregular surfaces. Can be easily die-cut. 3" neutral core/cartons.

Applications... Used for mounting nameplates, signs, small die cast parts, mirrors, maps, etc. Used for sound and vibration dampening in business machines, industrial equipment, electronic component packaging and glass panel mounts, seals, gaskets, etc. In general, the **acrylic adhesive** system is recommended for outdoor applications due to its higher temperature, UV, weather, chemical and plasticizer resistance. The **rubber adhesive** system is recommended for high shear demands as its quick grab nature is ideal for immediate load applications (mirrors) and for textured surfaces. The rubber system also exhibits higher adhesion to low-energy surfaces (some plastics, films).

When ordering, specify: Foam Color (White or Black^a) and Adhesive Type (Acrylic or Rubber)

WIDTH	RLS/CS	CASES		
		1-2	3-5	6+

DC-PEF03A... 1/32" Acrylic Based Adhesive

DC-PEF03R... 1/32" Rubber Based Adhesive

Physical Properties...

Foam	Cross-linked Polyethylene
Thickness, Density	1/32" (31 mils), 5#
Colors (2)	White or Black ^a
Adhesion (1 min, 24 hr dwell)	69 oz/in., 82 oz/in. (acrylic) 73 oz/in., 91 oz/in. (rubber)
Shear Adhesion @ 1kg psi	168+ hours
Release Liner	2.8 mil. 50# White Siliconized Paper

1/32" x 72 YD (216 FT) - WHITE OR BLACK^a FOAM

1/4"	(6mm)	48 or 96
3/8"	(9mm)	32 or 64
1/2"	(12mm)	24 or 48
5/8"	(15mm)	20 or 40
3/4"	(18mm)	16 or 32
7/8"	(21mm)	14 or 28
1"	(24mm)	12 or 24
1.5"	(36mm)	8 or 16
2"	(48mm)	6 or 12
3"	(72mm)	4 or 8
50"(48")*	(1220mm)	LOG

^a For double coated BLACK foam, ADD 5% (x1.05).

Alternative to 3M #4482, #4462 & #4492; IPG #8132; Scapa #SA432V & #SA5432V; Venture #632 & #732; Int'l Tape #332, #1328, #132 & #432; Press-on P-3200R/A.

* Usable width.

DC-PEF06A... 1/16" Acrylic Based Adhesive

DC-PEF06R... 1/16" Rubber Based Adhesive

Physical Properties...

Foam	Cross-linked Polyethylene
Thickness, Density	1/16" (62 mils), 4#
Colors (2)	White or Black ^a
Adhesion (1 min, 24 hr dwell)	55 oz/in., 73 oz/in. (acrylic) 59 oz/in., 82 oz/in. (rubber)
Shear Adhesion @ 1kg psi	168+ hours
Release Liner	2.8 mil. 50# White Siliconized Paper

1/16" x 36 YD (108 FT) - WHITE OR BLACK^a FOAM

1/4"	(6mm)	48 or 96
3/8"	(9mm)	32 or 64
1/2"	(12mm)	24 or 48
5/8"	(15mm)	20 or 40
3/4"	(18mm)	16 or 32
7/8"	(21mm)	14 or 28
1"	(24mm)	12 or 24
1.5"	(36mm)	8 or 16
2"	(48mm)	6 or 12
3"	(72mm)	4 or 8
61"(59")*	(1500mm)	LOG

^a For double coated BLACK foam, ADD 5% (x1.05).

Alternative to 3M #4446 & #4496; IPG # 8116; Scapa #SA416V & #SR516V; Venture #617 & #716; Int'l Tape #316, #116, #116B & #416; Press-on P-3200R/A.

* Usable width.

DC-PEF12A... 1/8" Acrylic Based Adhesive

DC-PEF12R... 1/8" Rubber Based Adhesive

Physical Properties...

Foam	Cross-linked Polyethylene
Thickness, Density	1/8" (125 mils), 2#
Color (1)	White
Adhesion (1 min, 24 hr dwell)	27 oz/in., 46 oz/in. (acrylic) 30 oz/in., 50 oz/in. (rubber)
Shear Adhesion @ 1kg psi	168+ hours
Release Liner	2.8 mil. 50# White Siliconized Paper

1/8" x 18 YD (54 FT) - WHITE FOAM

1/4"	(6mm)	48 or 96
3/8"	(9mm)	32 or 64
1/2"	(12mm)	24 or 48
5/8"	(15mm)	20 or 40
3/4"	(18mm)	16 or 32
7/8"	(21mm)	14 or 28
1"	(24mm)	12 or 24
1.5"	(36mm)	8 or 16
2"	(48mm)	6 or 12
3"	(72mm)	4 or 8
60"(59")*	(1500mm)	LOG

Alternative to Arlon #10C & #103; Scapa #SR508V; Int'l Tape #308 & #108; IPG #8108; Venture #608 & #708; Press-on P-3200R/A.

* Usable width.

Glazing foam tape, see page 59.

Permanent Transfer Tapes with Extended Liner...

Permanent Hot Melt Rubber Transfer Tape...

A 1.0 mil (3.3 mil total) synthetic rubber adhesive with a 42# silicone coated paper liner with finger-lift edge. Provides a permanent surface-to-surface bond with strong initial tack. Will not bleed through lightweight materials and has high overall adhesion. Perfect for paper to paper attachments, signs & posters, envelope sealing & direct mail pieces. Also good for paper web splicing, labels & business forms, high speed presses & collaborators, as well as spot & strip tape applications. Adhesive Thickness: 1.0 mil. Liner Thickness: 2.3 mil. 180° Peel Adhesion: 105 oz/in. Loop Tack: 126 oz/in. Shear Strength (1000g): 48+hrs. Operating Temperature: 0°F to 140°F.

STOCK	ROLL WIDTH	ADHESIVE WIDTH	LENGTH	RLS/CS	CASE QTY (\$/ROLL)	
					1-2	3+
PERMANENT / PERMANENT						
8502	1/2"	1/4"	3000'	10		
8503	3/4"	1/2"	3000'	7		
8504	1"	3/4"	3000'	5		
7323	3/4"	1/2"	4500'	7		

Note: Reverse wound (GSO) available. Specify "GSO" with item # when ordering.



Heavy Duty/Dispenser Pack...

A versatile double coated tissue tape with extended liner

A 3.2 mil (5.7 mil total) synthetic rubber adhesive with exceptional holding strength and an aggressive adhesive system with a 42# coated paper liner with finger-lift edge. Superior performance on heavier weight papers and light board stocks. Works well on curved and uneven surfaces. Available with or without dispenser. Perfect for mounting heavy posters & signs, promotional displays, inventory tags on cartons, and mounting name plates. Good for permanent poly bag sealing, board envelope and box fabrication, business forms presses and collators, tag and label mounting, as well as packaging and box closure. Adhesive & Carrier Thickness: 3.2 mil. Liner Thickness: 2.5 mil. 180° Peel Adhesion: 90 oz/in. Loop Tack: 70 oz/in. Shear Strength (1000g): 48+ hrs. Operating Temperature: 20°F to 140°F.



STOCK	ROLL WIDTH	ADHESIVE WIDTH	LENGTH	RLS/CS	CASE QTY (\$/ROLL)	
					1-2	3+
HEAVY DUTY						
7308	1/2"	1/4"	216'	48		
7309	3/4"	1/2"	216'	32		
7310	1"	3/4"	216'	24		
7312	3/4"	1/2"	1300'	7		
0321	1/2"	1/4"	2000'	10		
0322	3/4"	1/2"	2000'	7		
0317	1"	3/4"	2000'	5		

STOCK	ROLL WIDTH	ADHESIVE WIDTH	LENGTH	RLS/CS	CASE QTY (\$/ROLL)	
					1-2	3+
HEAVY DUTY DISPENSER PACK						
8600	* 1/2"	1/4"	108'	12		
8601	* 3/4"	1/2"	108'	12		
8602	* 1"	3/4"	108'	12		

*Provided in a convenient hand held dispenser.

Permanent/Removable Extended Liner Tapes...

HI/LO Permanent/Removable Polyester-Supported Tape...

A 2.8 mil (5.3 mil total) differential synthetic rubber with a polyester carrier and a 42# coated paper liner with finger-lift edge. Clear, lightweight adhesive for temporary bonding and repositioning on one side, permanent adhesive for long-term bonding on the other. Perfect for business forms, mailers & envelopes, labels and advertisements. Adhesive & PET Carrier Thickness: 2.8 mil. Liner Thickness: 2.5 mil. 180° Peel Adhesion: 50 oz/in (permanent side); 14 oz/in (removable side). Operating Temperature: 20°F to 140°F.

STOCK	ROLL WIDTH	ADHESIVE WIDTH	LENGTH	RLS/CS	CASE QTY (\$/ROLL)	
					1-2	3+
PERMANENT / REMOVABLE (HI / LO)						
7211	1/2"	1/4"	1300'	10		
7212	3/4"	1/2"	1300'	7		
7216	1"	3/4"	1300'	5		

Light Duty Regular Removable Transfer Tape...

A 1.0 mil (3.5 mil total) removable transfer tape with synthetic rubber based adhesive and a 42# coated Kraft paper liner with finger-lift edge. Clear, lightweight adhesive for temporary bonding with clean removable from a variety of surfaces. Good for lightweight attachments that require a short term bond. Business and hospital forms, mailers and envelopes, labels and advertisements. Adhesive Thickness: 1.0 mil. Liner Thickness: 2.5 mil. 180° Peel Adhesion: 2.1 oz/in. Loop Tack: 17.6 oz/in. Operating Temperature: 20°F to 150°F.

STOCK	ROLL WIDTH	ADHESIVE WIDTH	LENGTH	RLS/CS	CASE QTY (\$/ROLL)	
					1-2	3+
LIGHT DUTY REMOVABLE						
7301	1/2"	1/4"	3000'	10		
7302	3/4"	1/2"	3000'	7		
7303	1"	3/4"	3000'	5		

Note: Reverse wound (GSO) available. Specify "GSO" with item # when ordering.

Adhesive Transfer Tapes...

TR-7502... Transfer

2.0 mil (0.050mm) Glass stabilized **modified acrylic adhesive** wound on a gold siliconized paper release liner. Glass stabilization allows for lathe slitting and cleaner unwinding. Moderate adhesion to most surfaces makes this a very economical choice for general purpose bonding/mounting applications. Extra wide web (59") makes tape suitable for laminating. **Peel Adhesion: 27 oz/in (1 min dwell); 37 oz/in (24 hr dwell).** Temperature Range: -22°F to 230°F (284°F short term). 3" neutral core/carton.

61" (1550mm) x 800M Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
60 YD (55M)				
1/4"	(6mm)	144		
3/8"	(9mm)	96		
1/2"	(12mm)	72 or 96		
3/4"	(18mm)	48 or 64		
1"	(24mm)	36 or 48		
1.5"	(36mm)	24 or 32		
2"	(48mm)	18 or 24		
3"	(72mm)	12 or 16		
4"	(96mm)	12		
6"	(144mm)	8		
12"	(300mm)	4		
61"	(1550mm)	LOG	neutral core	

110 YD (100M)

1/2"	(12mm)	72
3/4"	(18mm)	48
1"	(24mm)	36
1.5"	(36mm)	24
2"	(48mm)	18
3"	(72mm)	12
4"	(96mm)	12
61"	(1550mm)	LOG
		neutral core

Alternative to Shurtape #TA-450; Tesa #4900; 3M #927; Berry Global #065; Achem #At15SA; Venture # 3802; Adchem #7332; Scapa #UP2020.

TR-7502X... Transfer

2.0 mil (0.052mm) Glass stabilized **modified acrylic adhesive** wound on a gold siliconized paper release liner. Glass stabilization allows for lathe slitting and cleaner unwinding. More aggressive adhesive than TR-7502. Tape bonds well to most surfaces such as papers, films, metals, etc. Extra wide web (59") makes tape suitable for use as a laminating adhesive for foams or fabrics. **Peel Adhesion: 45 oz/in (1 min dwell); 55 oz/in (24 hr dwell).** Temperature Range: -22°F to 230°F (284°F short term). 3" neutral core/carton.

59" (1500mm) x 800M Jumbos Available.

60 YD (55M)

1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24 or 32
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
6"	(144mm)	8
12"	(300mm)	4
59"	(1500mm)	LOG
		neutral core

Alternative to Shurtape #TA-450; Tesa #4900; 3M #927; Berry Global #065; Adchem #728; Scapa #U-263-1 & #UP2040.

TR-7901... Transfer

2.0 mil (0.050mm). Glass stabilized **modified acrylic adhesive** wound on a brown siliconized paper release liner. Glass stabilization allows for lathe slitting and cleaner unwinding. High quick tack and good shear strength makes this the best choice for more demanding bonding/joining applications. Used for core starting, splicing of papers, films, metals and other webs. Can be used as a laminating adhesive for foams or fabrics. **Peel Adhesion: 50 oz/in (1 min dwell); 69 oz/in (24 hr dwell).** Temperature Range: -22°F to 230°F (284°F short term). 3" neutral core/carton.

59" (1500mm) x 800M Jumbos Available.

60 YD (55M)

1/4"	(6mm)	144
3/8"	(9mm)	96
1/2"	(12mm)	72 or 96
3/4"	(18mm)	48 or 64
1"	(24mm)	36 or 48
1.5"	(36mm)	24
2"	(48mm)	18 or 24
3"	(72mm)	12 or 16
4"	(96mm)	12
6"	(144mm)	8
12"	(300mm)	4
59"	(1500mm)	LOG
		neutral core

Alternative to IPG #8120; Permacel #593; Tesa #4985; Venture #3802; 3M #924; Scapa #U-263-1; Specialty Tape #D991.

Custom Widths and Lengths Available for all "TR" Adhesive Transfer Tapes.

929TR... For tape up to 1" wide max.

Hand held dispenser for **2 mil transfer tapes** on 3" cores (cannot be used with 60yd TR-7505 or 110yd TR-7502, TR-7502X or TR-7901). Acts like an ATG gun. Lays down tape with a trigger action. Winds up release liner for later disposal. Holds rolls up to 1" wide with max OD of 5-1/4". 3" cores.



COST EACH	UNITS/CASE	CASE QTY
	6	/case

Adhesive Transfer Tapes...

TR-7505... Transfer

4.7 mil (0.120mm) Glass stabilized **modified acrylic adhesive** with brown siliconized paper release liner. Glass stabilization allows for lathe slitting & cleaner unwinding. Thick adhesive coating coupled with high quick tack & good shear strength makes this the best choice for more demanding bonding/joining applications, especially for textured, rough surfaces. Used for core starting, splicing of papers, films, metals & other webs. Extra wide web (59") makes tape suitable as a laminating adhesive for foams or fabrics. **Peel Adhesion: 78 oz/in (1 min dwell); 105 oz/in (24 hr dwell).** Temp. Range: -22°F to 230°F (284°F short term). 3" neutral core/carton.

59" (1500mm) x 500M Jumbos Available.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
60 YD (55M)				
1/4"	(6mm)	144		
3/8"	(9mm)	96		
1/2"	(12mm)	72		
3/4"	(18mm)	48		
1"	(24mm)	36 or 48		
1.5"	(36mm)	24		
2"	(48mm)	18 or 24		
3"	(72mm)	12 or 16		
4"	(96mm)	12		
12"	(300mm)	4		
59"	(1500mm)	LOG	neutral core	

Alternative to Scapa #U261; Shurtape #TA-499; Tesa #4988; 3M #468, #950; Achem #AT505A; Arclad #7335, #7511.

Reverse Wound Adhesive Transfer Tapes...

ALL our ATG tapes (widths & lengths) fit in our ATG-150 dispenser.

ATG-7501... Reverse Wound Transfer

Transfer tape. 1.6 mil (0.040mm). Glass stabilized acrylic adhesive. Gold paper liner. Good adhesion to paper, most plastic films, metal foils, etc. **Peel Adhesion: 24 oz/in (1 min dwell); 33 oz/in (24 hr dwell).** Temperature Range: -22°F to 230°F (284°F short term). Reverse wound on 1" plastic core.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
36 YD (33M)				
1/4"	(6mm)	144		
1/2"	(12mm)	72		
3/4"	(19mm)	48		
60 YD (55M)				
1/4"	(6mm)	144		
1/2"	(12mm)	72		
3/4"	(19mm)	48		

ATG-7502... Reverse Wound Transfer

Transfer tape. 2.0 mil (0.050mm). Glass stabilized acrylic adhesive. Gold paper liner. Good adhesion to paper, most plastic films, metal foils, etc. For picture framing, product assembly, design & packaging prototypes. **Peel Adhesion: 27 oz/in (1 min dwell); 37 oz/in (24 hr dwell).** Temperature Range: -22°F to 230°F (284°F short term). Reverse wound on 1" plastic core.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
36 YD (33M)				
1/4"	(6mm)	144		
3/8"	(9mm)	96		
1/2"	(12mm)	72		
3/4"	(19mm)	48		
60 YD (55M)				
3/4"	(19mm)	48		

Sub-packs: 1/4"=24 rolls; 3/8"=16 rolls; 1/2"=12 rolls; 3/4"=8 rolls
Alternative to 3M #924, #987; Scapa #TD-200; Shurtape #TG-356; Tesa (NOPI) 7002-PV9.

ATG-7502X... Reverse Wound Transfer

Transfer tape. 2.0 mil (0.052mm). Glass stabilized acrylic adhesive. Gold paper liner. More aggressive than ATG-7502. Excellent adhesion to paper, most plastic films, metal foils. For picture framing, product assembly, design/packaging prototypes. **Peel Adhesion: 27 oz/in (1 min dwell); 37 oz/in (24 hr dwell).** Temperature Range: -22°F to 230°F (284°F short term). 1" plastic core.

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
36 YD (33M)				
1/2"	(12mm)	72		
3/4"	(19mm)	48		
60 YD (55M)				
1/2"	(12mm)	72		

Sub-packs: 1/2"=12 rolls; 3/4"=8 rolls
Alternative to 3M #976; Scapa #TD-200; Shurtape #TG-356; Tesa (NOPI) 7002-PV9.

ATG-7505... Reverse Wound Transfer

Transfer tape. 4.7 mil (0.120mm). Glass stabilized acrylic adhesive. Brown paper liner. High quick tack, good shear & holding power. Used for gap filling, mounting nameplates & trim-joining. Good bond to irregular surfaces. **Peel Adhesion: 78 oz/in (1 min dwell); 105 oz/in (24 hr dwell).** Temp. Range: -22°F to 230°F (284°F short term). 1" plastic core.



WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
18 YD (16.5M)				
1/4"	(6mm)	144		
1/2"	(12mm)	72		
3/4"	(19mm)	48		
36 YD (33M)				

WIDTH	RLS/CS	CASES		
		1-2	3-11	12+
36 YD (33M)				
1/4"	(6mm)	144		
1/2"	(12mm)	72		
3/4"	(19mm)	48		

Sub-packs: 1/4"=24 rolls; 1/2"=12 rolls; 3/4"=8 rolls
Alternative to 3M #926, #969; Scapa #TD-500; Tesa 425BPV5.

ATG-150...

Tape dispenser for reverse wound transfer tapes on 1" plastic cores. Dispenser has a special pin spool allowing use of complete roll without any waste, friction or effort. Rear wheel has an adjustable gear for tension control. Weighs less than a lb. with tape!



COST EACH	UNITS/CASE	CASE QTY
	24	/case

FITS ALL OUR ATG TAPES (widths & lengths).
Dispenser comes with an adapter kit to stabilize narrow width (1/4") rolls.

Pressure Sensitive Envelopes...

Smaller envelopes are packed 1,000 per case; larger envelopes (designed to hold full sheets of paper) are packed 500 per case. Envelopes printed black and orange. Back loading design. NOTE: FIRST DIMENSION IS SLIT LOCATION.

ENV-P4555S... PACKING LIST ENCLOSED (1/4 FACE)
O.D. Size: 4.5" x 5.5". End loading slit. 1,000 envelopes/case.


ENV-P4555F... PACKING LIST ENCLOSED (FULL FACE)
O.D. Size: 4.5" x 5.5". End loading slit. 1,000 envelopes/case.

ENV-I4555S... INVOICE ENCLOSED (1/4 FACE)
O.D. Size: 4.5" x 5.5". End loading slit. 1,000 envelopes/case.

ENV-C4555... CLEAR - NO IMPRINT
O.D. Size: 4.5" x 5.5". End loading slit. 1,000 envelopes/case.


COST PER CASE			
1-9	10-24	25-49	50+

4.5" x 5.5" ENVELOPES	PACKED 1,000/CASE
-----------------------	-------------------




ENV-C7555... CLEAR - NO IMPRINT
O.D. Size: 7.5" x 5.5". Top loading slit. 1,000 envelopes/case.

7.5" x 5.5" ENVELOPES	PACKED 1,000/CASE
-----------------------	-------------------




ENV-P55100E... PACKING LIST ENCLOSED (1/4 FACE)
O.D. Size: 5.5" x 10". End loading slit. 1,000 envelopes/case.

5.5" x 10" ENVELOPES	PACKED 1,000/CASE
----------------------	-------------------




ENV-C55100E... CLEAR - NO IMPRINT
O.D. Size: 5.5" x 10". End loading slit. 1,000 envelopes/case.

9.5" x 12" ENVELOPES	PACKED 500/CASE
----------------------	-----------------



ENV-C1012NP... CLEAR - NO IMPRINT
O.D. Size: 10" x 12". End loading slit. For holding 8.5" x 11" paper.
500 envelopes/case.

10" x 12" ENVELOPES	PACKED 500/CASE
---------------------	-----------------




Pouch Tapes...

2 mil clear polypropylene film with an orange ink border printed with "DOCUMENTS ENCLOSED". The film is coated with an acrylic adhesive only along the edges. The adhesive-free center creates a see-through pouch when applied to a surface. Linerless & easy to use - just peel & stick. Peel Adhesion: 32 oz/in.

DE5x6...
O.D. Size: 5" x 6"; I.D. Pouch Size: 3 1/4" x 4 1/2".
500 pouches per roll, 8 rolls per case.

ITEM	RLS/CS	CASES (COST PER ROLL)			
		1-2	3-6	7-15	16+
DE5x6	8				
DE6x8	8				

DE6x8...
O.D. Size: 6" x 8"; I.D. Pouch Size: 4 1/2" x 6 1/2".
500 pouches per roll, 8 rolls per case.



Retail Dispensers with Tape...

20HT-D...

Stationery tape on 1/2" dispenser.

Retail put-up. 1/2" & 3/4" wide x 800" long OPP stationery tape on a half-sided dispenser. Carded (generic imprint) and plastic blade. Water based acrylic adhesive. 6 inner cartons per box.

COST EACH	UNITS/CASE	CASE QTY
N/A	144	
	1/2" x 800"	/case

COST EACH	UNITS/CASE	CASE QTY
N/A	96	
	3/4" x 800"	/case



EX-243L...

Crystal clear tape with dispenser.

Retail put-up. 2" x 800" roll of 2 mil crystal clear tape on a 1.5" core with a plastic, hand-saver dispenser. Carded (generic imprint) and metal blade.

COST EACH	UNITS/CASE	CASE QTY
N/A	48	
		/sub-pack

COST EACH	UNITS/CASE	CASE QTY
N/A	144	
		/case



Hand Held Tape Dispensers...

ET-166...

Filament/strapping tape dispenser. For tape up to 1" wide. Maximum roll diameter of 5 1/2". 3" core.

COST EACH	UNITS/CASE	CASE QTY
100		
		/case



ET-226...

Filament/strapping tape dispenser; also used for carton sealing tapes. For tape up to 2" wide. Maximum roll diameter of 5-1/2". Metal frame. 3" core.

COST EACH	UNITS/CASE	CASE QTY
60		
		/case



ET-0050...

Heavy duty carton sealing tape dispenser; also used for filament/strapping tapes. All metal construction with built-in internal hand brake for tension control. For tape up to 2" wide. Maximum roll diameter of 4 3/4". Includes extra blade. 3" core.

COST EACH	UNITS/CASE	CASE QTY
24		
		/case



ET-366...

Carton sealing tape dispenser; also used for filament/strapping tapes. For tape up to 3" wide. Maximum roll diameter of 5 1/2". Metal frame with safety blade cover. 3" core.

COST EACH	UNITS/CASE	CASE QTY
32		
		/case



Note: Please inquire for pricing and availability on dispenser replacement parts.

Carton Sealing Hand Held Tape Dispensers...

EC-233...

For tape up to 2" wide. Maximum roll diameter of 5". Metal frame carton sealing tape dispenser. Side loader with adjustable brake. Natural rubber roller and static cling strip keeps tape in ready-to-use position. Packed individually in a colorful retail box. 3" core.

COST EACH	UNITS/CASE	CASE QTY
	40	
		/case




EC-208...

For tape up to 2" wide. Maximum roll diameter of 5½". Metal frame carton sealing tape dispenser with safety blade cover. Side loader with adjustable brake. Natural rubber roller and static cling strip keeps tape in ready-to-use position. Packed individually in a colorful retail box. 3" core.

Replaces EC-209.


COST EACH	UNITS/CASE	CASE QTY
	40	
		/case



SNC-289... Low Noise

2" Mousetrap dispenser with blade cover. Rubber roller with static cling strip.
U.S. Pat. No. 6641081.

COST EACH	UNITS/CASE	CASE QTY
	24	
		/case



EC-238... Heavy Duty

For tape up to 2" wide. Maximum roll diameter of 5½". Heavy-duty metal frame carton sealing tape dispenser. Natural rubber roller and static cling strip keeps tape in ready-to-use position. Side loader with adjustable brake. 3" core.

COST EACH	UNITS/CASE	CASE QTY
	30	
		/case



Note: Please inquire for pricing and availability on dispenser replacement parts.

Carton Sealing Hand Held Tape Dispensers...

EC-326...

For tape up to 3" wide. Maximum roll diameter of 5". Metal frame carton sealing tape dispenser. 3" core. **Side loader with adjustable brake.**

COST EACH	UNITS/CASE	CASE QTY
-----------	------------	----------

24		
----	--	--

/case



SNC-389... Low Noise

3" Mousetrap dispenser with blade cover. Natural rubber roller to create static to keep tape in ready-to-use position and static cling strip.

COST EACH	UNITS/CASE	CASE QTY
-----------	------------	----------

24		
----	--	--

/case



EC-306...

For tape up to 3" wide. Maximum roll diameter of 6". Metal frame carton sealing tape dispenser. 3" core. **Side loader with adjustable brake.**

COST EACH	UNITS/CASE	CASE QTY
-----------	------------	----------

12		
----	--	--

/case



EC-338... Heavy Duty

For tape up to 3" wide. Maximum roll diameter of 5 1/2". Heavy-duty metal frame carton sealing tape dispenser. Natural rubber roller to create static to keep tape in ready-to-use position. 3" core. **Side loader with adjustable brake.**

COST EACH	UNITS/CASE	CASE QTY
-----------	------------	----------

20		
----	--	--

/case



EC-401... Heavy Duty

For tape up to 4" wide. Maximum roll diameter of 5 3/4". Carton sealing & label protection tape dispenser. 3" core. **Metal Frame Top loader without brake.**

COST EACH	UNITS/CASE	CASE QTY
-----------	------------	----------

10		
----	--	--

/case



EC-438... Commercial Grade

For tape up to 4" wide. Maximum roll diameter of 5 3/4". This **commercial grade**, cantilever designed dispenser has a special hardened steel-tooth blade, soft rubber roller, ABS resin handle, and a **heavy-gauge stamped-steel frame** for extra rigidity. 3" core. **Side-loading with an adjustable brake.**

COST EACH	UNITS/CASE	CASE QTY
-----------	------------	----------

5		
---	--	--

/case



Note: Please inquire for pricing and availability on replacement parts for hand held tape dispensers.

Stretch Film Dispensers & Accessories...

SD-259B... Stretch film/strapping cutter

Specially angled cutter head safely glides through stretch film without bunching/sticking, and without cutting merchandise or user. Color: Blue.



COST EACH	UNITS/CASE	CASE QTY
N/A	12	
		/sub-pack

Case of 720 has 60 sub-packs of 12 cutters.

N/A	720	
		/case

SF-750...

Plastic handwrap handle for 3" (75mm) core.



COST EACH	UNITS/CASE	CASE QTY
/ea.	100	
		/case

SF-755... (Priced & Sold by Pair)

For film up to any width. **Handy-cup stretch film core holder/Dispenser** with improved ergonomic design to reduce hand-fatigue. Excellent premium/promotional item. 3" core.



COST EACH	UNITS/CASE	CASE QTY
/pr.	75	/pr.
		/case

SF-2781A...

For film up to 18" wide. **Adjustable stretch film dispenser with aluminum base/stand.** Designed to accommodate various stretch film widths and cores! Flexible ribbed rubber grips help maximize comfort and minimize fatigue. Easily adjust the shaft height (convert the dispenser from 12" to 18" wide), film tension and dispensing speed. Base roller disk reduces friction and helps maintain the film's width while in use. Fits 1.5", 2" and 3" cores.



COST EACH	UNITS/CASE	CASE QTY
	6	
		/case

Tabletop Tape Dispensers...

ET-12281...

For tape up to 2" wide. Maximum roll diameter of 5.5". **Twin-roll bench top dispenser with C-clamp.** C-clamp quickly attaches to a bench/table (no screws required). Holds single roll up to 2" wide; or 2 rolls, each up to 1" wide. 3" core. Wide 2.75" blade with safety cover.



COST EACH	UNITS/CASE	CASE QTY
	24	
		/case

Tabletop Tape Dispensers...

EX-191BK...

For tape up to 1" wide. Maximum roll diameter of 5". Desktop dispenser with 1" and 3" cores. Lowest cost desk dispenser.

Replacement Parts:
219103 3" Plastic Core
219104 1" Plastic Core

COST EACH	UNITS/CASE	CASE QTY
	6	/case



ET-11171...

For tape up to 1" wide. Maximum roll diameter of 5". High quality, **steel desktop dispenser**. Holds single roll up to 1" wide. 3" core. Extra wide, anti-rust stainless steel blade with safety cover. Weighted rubber lined base for stability.

Replaces ET-117.

COST EACH	UNITS/CASE	CASE QTY
10		/case



ET-12270...

For tape up to 2" wide. Maximum roll diameter of 5". **Twin-roll steel desktop dispenser**. Holds single roll up to 2" wide; or 2 rolls, each up to 1" wide. 3" core. Extra wide, anti-rust stainless steel blade with safety cover. Weighted rubber lined base for stability.

Replaces ET-227.

COST EACH	UNITS/CASE	CASE QTY
10		/case



ET-13370...

For tape up to 3" wide. Maximum roll diameter of 5". **Multi-roll steel desktop dispenser**. Holds single roll up to 3" wide; 2 or 3 rolls, each up to 1" wide. 3" core. Extra wide, anti-rust stainless steel blade with safety cover. Weighted rubber lined base for stability.

Replaces ET-337.

COST EACH	UNITS/CASE	CASE QTY
6		/case



NEW

ET-447...

For tape up to 4" wide. Maximum roll diameter of 5.5". **Multi-roll steel desktop dispenser**. Holds single roll up to 4" wide; 2 rolls, each up to 2" wide; 2 rolls, up to 1" and 3" wide; or 4 rolls, each up to 1" wide. 3" core. Anti-rust stainless steel blade with safety cover. Weighted rubber lined base for stability.

COST EACH	UNITS/CASE	CASE QTY
6		/case



NEW

EX-4471...

For tape up to 4" wide. Maximum roll diameter of 5.5". **Heavy-duty, quadruple-roll steel desktop dispenser**. Tiered metal bars help guide & prevent tapes from overlapping. Provides fast access to various types of tape. Anti-rust stainless steel blade. Weighted rubber lined base for stability.

Replaces MD-4B.

COST EACH	UNITS/CASE	CASE QTY
6		/case




Produce / Bag Seal Tape Dispensers...

Instructions for Bag Seal Tape Dispensers

1. Insert dispenser core into tape core, and slip into dispenser's core holder.
2. Pull tape over the top of dispenser, making sure that the adhesive side is facing UP.
3. Twist bag and pull down, through dispenser.
4. Use blade on bottom to trim bag.

See page 26 for Bag Sealing Tape.



ET-605K... For tape up to 12mm wide

Produce tape dispenser / bag sealer with trimmer.

Baked enamel finish. 3" core.

COST EACH	UNITS/CASE	CASE QTY
	10	/case



ET-606STK... For tape up to 12mm wide

Produce tape dispenser / bag sealer with trimmer.

Stainless steel. 3" core.

COST EACH	UNITS/CASE	CASE QTY
	10	/case



Replacement Sets/Parts:

- For both ET-605K & ET-606STK

605CST: Core Set

- Core, Friction Washer

605GST: Gear Set

- Gear, Spacer Axle

605PSS: Pressure Slide Set

- Pressure Slide, Spring, Spacer Axle

605SLS: Stop Lever Set

- Stop Lever, Spring, Spacer Axle

605BHS: Inside Blade Set

- Blade, Blade Holder, Blade Screw, Spacer Axle, Spring

605016: Trimmer Blade Pack (20)

605003R: Spacer Axle


605021R: Screw

ET-808K... For tape up to 16mm wide

Produce tape dispenser / bag sealer with trimmer.

Wide neck to handle thicker bags. Baked enamel finish. 3" core.

COST EACH	UNITS/CASE	CASE QTY
	10	/case



Replacement Sets/Parts:

808BHS: Inside Blade Set

- Blade, Blade Holder, Blade Screw, Spring

808004: Tape Core

605016: Trimmer Blade Pack (20)

808003: Gear

ET-635... For tape up to 25.4mm wide

Produce tape dispenser / bag sealer / wrapper / bundler with safety lock.


Heavy-duty steel with non-slip pad for stability.

Exposed wrapping platform (good for thick bags and/or wide objects). Used for bag sealing (narrow to wide neck widths), wrapping produce, and bundling wires/cables/supplies. Spring-loaded toothed blade for easy wrapping & cutting. **Fits 1", 3" and 3.5" cores.**

COST EACH	UNITS/CASE	CASE QTY
	6	/case



Unique tri-core:



Transfer & Double Coated Tape Dispensers...

ATG-150... For ATG tape up to 1" wide

Tape dispenser for **ATG/reverse wound transfer tapes** on 1" plastic cores. Designed to fit all our ATG tapes (widths & lengths). Dispenser comes with an adapter kit to stabilize narrow width (1/4", 6mm) rolls. Special pin spool allows use of complete roll without any waste, friction or effort. Lays down tape with a trigger action. Winds up release liner for later disposal. Rear wheel has an adjustable gear for tension control. Weighs less than a lb. with tape! 1" cores.



COST EACH	UNITS/CASE	CASE QTY
24		/unit

Adapter Kit
(for narrow width rolls)

929TR... For transfer tape tape up to 1" wide

Hand held dispenser for **2 mil transfer tapes** on 3" cores (cannot be used with 60yd TR-7505 or 110yd TR-7502, TR-7502X or TR-7901). Acts like an ATG gun. Lays down tape with a trigger action. Winds up release liner for later disposal. Holds rolls up to 1" wide with max OD of 5-1/4". 3" cores.



COST EACH	UNITS/CASE	CASE QTY
6		/case

925DC-1... For double coated tape up to 1" wide

Double coated hand held tape dispenser. Applies tape to working surfaces while rewinding the liner on the take-up spool. Heavy formed steel frame for long life. Adjustable tension brakes on tape roll holder and scrap rewind spool insure proper performance with any weight tape. Ideal for longer length lay-down applications. Consider our 926DC-2 for shorter length applications. Not recommended for thick, difficult to cut tapes. Holds rolls up to 1" wide with max OD of 5-1/2". 1" & 3" cores.



COST EACH	UNITS/CASE	CASE QTY
6		/case

925DC-2... For double coated tape up to 2" wide

Double coated hand held tape dispenser. Applies tape to working surfaces while rewinding the liner on the take-up spool. Heavy formed steel frame for long life. Adjustable tension brakes on tape roll holder and scrap rewind spool insure proper performance with any weight tape. Ideal for longer length lay-down applications. Consider our 926DC-2 for shorter length applications. Not recommended for thick, difficult to cut tapes. Holds rolls up to 2" wide max OD of 5-1/2". 3" core.



COST EACH	UNITS/CASE	CASE QTY
6		/case

Replacement Part:
#DP-09355012 Blade (each)

926DC... For double coated tape up to 2" wide

Tabletop double coated tape dispenser. Dispenses double sided tape or other tapes with removable liner. One easy pull releases tape and peels off backing, rewinding it on the take-up spool. Tape roll holder and scrap rewind spool have independent adjustable brakes to insure proper performance with any weight tape. Clean cutting tempered steel blade is easily replaced. Holds rolls up to 2" wide with max OD of 7.1" (180mm). 3" core. Size: 3" W x 12" L.



COST EACH	UNITS/CASE	CASE QTY
6		/case

Converter Accessories...

Siliconized Paper Release Separators...

Due to the constant fluctuation in pricing,
please contact us for current costs.

CIRCLE (3" I.D. Hole)... Packed 10,000 sheets per case

ITEM	SIZE	COST/CASE
RS6X3D	6" O.D.	

PE COATED... Packed 2,000 to 2,500 sheets per case

Used for UHB (Ultra High Bond) Tapes

ITEM	SIZE	COST/CASE
RSH95X95PE	9.5" x 9.5"	
RSH12X12PE	12" x 12"	

STANDARD... Packed 2,500 sheets per case

ITEM	SIZE	COST/CASE
RS9.5X9.5	9.5" x 9.5"	
RS9.5X12.5	9.5" x 12.5"	
RS10.5X16	10.5" x 16.5"	
RS10.75X16	10.75" x 16"	
RS11X11	11" x 11"	
RS11.5X11.5	11.5" x 11.5"	
RS12X12	12" x 12"	
RS13.5X19	13.5" x 19"	
RS13.75X19	13.75" x 19"	
RS14X11	14" x 11"	
RS14X14	14" x 14"	
RS14.5X9.75	14.5" x 9.75"	
RS14.5X10	14.5" x 10"	
RS17X11	17" x 11"	

Steel Replacement Blades... M-2 Tool Steel

(Contact us for more details)

SIZE	COST EACH
8.07" O.D. x .100" Thick x 1" ID	
22" O.D. x .190" Thick x 1" ID	

Mold-Lube Lubricant...

Siltex Mold-Lube

SIZE	COST EACH
5 gallon	
55 gallon	

PE Plastic Mandrel Sleeve Covers...

SIZE	COST EACH
1" (19mm I.D.) x 25.4mm O.D. x 53" prox.	
1.5" (31.7mm I.D.) x 38.1mm O.D. x 65" prox.	
3" (69mm I.D.) x 76.2mm O.D. x 65" prox.	

4863RW... Mandrel Dimpled Roller Wrap

26 mil (0.65mm) exclusive of liner. **Gray embossed silicone laminated fabric** coated with a **silicone based acrylic adhesive**, wound on a 3 mil (0.08mm) red polypropylene liner. Highly resistant to "sticky" substances while providing a reliable "non-slip" effect on smooth substrates. Used in adhesive tape manufacturing, general converting, printing, textiles, and in the paper, foil, film industries. Adhesion to Steel: 33 oz/in. Tensile Strength: 100 lbs/in. Elongation: 20%. Temperature Resistance: Up to 302°F (150°C). 3" neutral core.

COST EACH	RLS/CS	CASE QTY	
2"(50mm) x 25M			
6	(/sub-pack)	
N/A	24	(/case)



Alternative to Tesa #4863.




Converter Equipment...

New and used converting equipment available. Contact us for details!

SLITTERS...




LOGGERS...



REWINDERS...



CORE CUTTERS...



Product Data Index

PRODUCT DESCRIPTION	PAGE	ITEM NUMBER	PAGE
Aisle Marking Tapes & Dispenser	8-11	4863RW	73
Aluminum Foil Tapes	36-38	AF-12A/R,-16A/R,-20A/R/SW,-20A-B,-30A/SW,-50A,-FSK-A/R	36-38
Appliance Tapes	29	AT-UHB10,-UHB40	57
ATG Tapes	63	ATG-150 (dispenser)	71
Bag Sealing Tapes (UPVC)	26	ATG-7501,-7502,-7502X,-7505	63
Barricade Tapes	7	BRC	7
Bookbinding Tape	2,25	CDT-8GP,-30T,-36,-70,-70F,-80CAM,-HS	3-5
CablZone Tapes	4	CELLO	24
Camouflage Tape	4	CFB-60,CFB-75	16
Carpet Tapes (Double Coated)	48,52	CFL-5A,CFL-5CA	39
Carton Sealing Tapes	16-26,28-29	CFT-15	5
Cellophane Tapes	24	CGT-80,-80F,-80MG,-665C	2,5
Circuit Board Tapes	40-41	CPM-60	15
Conspicuity Tapes	32-34	CUSTOM PRINTED TAPES	19
Converter Accessories	73	CVT-536,-560,-636,-636P,-660,-660P,-A,-D	8-9
Copper Foil Tapes	39	CVT-6FSH,-DKYD,-WHUC	17
Custom Printed Tapes	17,19	CZT-70B/Y	4
Differential Adhesive Tapes, Double Coated	48,61	DC-1114,-4106LW,-4109RS/CS/CSG/R,-4123 (Polyester)	46-47
Dispensers & Replacement Parts	65-73	DC-1210,-3208SA,-3212SA,-4210RS/VS/VS-B,-4215WO (Tissue)	50-51
Double Coated Tapes	45-57,59-61	DC-1503,-1511,-3522 (Polypropylene)	47
Dry Vinyl Tapes	11	DC-2306,-2307,-2315,-4309LW,-4317VS (Paper)	48-49
Duct Tapes	3-5	DC-3106R/P,3107R/P,-4110R/P (Differential Adhesion)	48
Electrical Tapes	6	DC-4414W,-4420,-4420LB,-4425AR (PVC)	45
Electroplating Tapes	10,12-13,36-39,42	DC-5215,-5225,-5227X (Cloth)	52
Extended Liner Tapes	61	DC-4608MF,-4623MF (Scrim)	53
Filament Tapes	28-29	DC-PEF03A/R,-PEF06A/R,-PEF12A/R,-PEF06P,-PEF12P	59-60
Flatback Paper Tapes	16,49	DC-UHB25,-UHB45	57
Fluorescent Tapes	5,14,25,34	DE5x6,DE6x8	64
Foam Tapes	54-60	DVT-76Y	11
Foil Tapes	36-39	EC/ET/EX-xxx (Dispensers)	64-73
Friction Tape	5	EL760, EL766, EL7108, EL760AW, EL766AW, EL766AWR, EL7566AW	6
Gaffers Tapes	2,4,5	ENV-Cxxx,-Ixxx,-Pxxx	64
Glass Cloth Tapes	42-43	EPT-38	10
Glazing Tape	59	FA-UHB10C,16E/W,20C,25E/W,31E,40C,45E/W,60E/C,80C/E/W,120W	54-56
"Glow in the Dark" Photoluminescent	14,35	FCT-665	5
Graphic Arts Tapes	15,44,63	FIL-810,-825,-890,-930P,-835B/D	28-29
Gummed Paper Tapes	19	GC-SH7,-SA7	42
Hazard Identification Tapes	4,10-11,14,35	GPM-63	15
High Bond Tapes	54-57	HOOK & LOOP	27
High Temperature Masking Tape	15,40-43	INV-20M,INV-20M-1	27
Hook & Loop	27	KFT-530,KFT-PM2	16
Invisible Mending Tape	27	KPT-1,KPT-2	43
Kraft Paper Tape	16,73	LDPE-5A,-5R,-7R,-7R/UV,-9R	12-13
Label Protection/Lamination Tapes	26-27	LF-5A,LF-5R	39
Lead Foil Tapes	39	LP-16AW,LP-20CC	26
Magnetic Tapes	31	MAG03-I/-10,MAG06-I/-10,MAG03WO/WOE	31
Masking Tapes	15-16,40-43	MMYP-1	44
Mending Tapes	27	MYP-25CA/CS,-3US/RS,-36GS/US/OS,-571PS	40-41
Mylar Polyesters	40-41,44	NST-20,-20BY,-20C,-20F,-20GL,-20GS,-624B,-NST-B	14,35
Office Supply Tapes	27	NST-6FSH,-WHUC	17
Packing List Envelopes	64	OPP-16AW,-18AW,-20AW,-26AW,-32AW,-P	20-21,26,30
Photoluminescent ("Glow in the Dark") Tapes	14,35	OPP-18NR,-20NR,-26NR	24
Pipe Thread Seal Tapes (Teflon™/PTFE)	17	OPP-20A,-22A,-26A,-34A	22
Pipe Wrap Tapes	7-9,12	OPP-20C,-22C,-26C,-26CAW,-P	23,30
Polyester Film Tapes	24,40-41,44	OPP-22CC,-26CC,-34CC	21
Polyethylene Film Tapes (LDPE/UHMW)	12-13,44	PES-32G	24
Polyimide Tapes	43	PGD-6,-24	35
Pouch Tapes	64	PGM-UV14	15
Printed Carton Sealing Tapes	17-19	PP20 (Imprinted Legends)	18
Printers' Rolls (UPVC & BOPP)	30	PP-500,-800,-4298	29
Produce Tapes (UPVC)	26	PTFE-35S	17
PVC Bag & Carton Sealing Tapes	25-26	PWT-10,-10G,-10H,-20	7
Reflective/Retroreflective Tapes	32-34	REF-5,-7,-3S,-5S,-DOT,-5DB,-10DB,-DBF	32-34
Safety Tapes	4-5,7,10-11,14,32-35	SBW-80,-120,SFW-80,-80EH,-100,-120,MSW-75	30
Security Tapes	17-18	SF-VFLD,SF-VFMD	58-59
Silicone Splicing Tapes	40-41	SPP-20HTW-1,20RW-B,20HTW,20HT-D	27
Skid Resistant Tapes	14,35	SST-618,-636,-718,-718L,-736,-736L,-918L,-918LPC,-936L	10-11
Skived Teflon™ (PTFE) Tapes	42	TEV-OVR,-STR	17
Splicing Tapes	40-41	TFE-xx,TFES-xx	42-43
Social Distancing Tapes	17	TR-7502,-7502X,-7901,-7505	62-63
Stationery Tapes	27	T-TAK™	61
Strapping Tapes	28-29	UHMW-3A,-5A,-10A,-15A,-20A	44
Stretch Film - Hand Wrap	30	UPVC-22BS,-24BS,-22,-24C,-25F,-P	25-26,30
Striped Safety Tapes	4,7,10-11,14,32-33		
Tamper Evident Tapes	17		
Teflon™ - Glass Fabric, Skived, & Pipe Thread Seal Tapes	17,42-43		
Transfer Tapes	57,61-63		
Velcro®	27		
Vinyl Tapes (SPVC)	6-11		